| US ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (75-767) WASHINGTON, DC 20460 | EPA REGISTRATION NO. 458~33  | FEB 5 1986 |
|--|--|------------|
|  | TERM OF ISSUANCE Conditional                                       |            |
| NOTICE OF PESTICIDE: REGISTRATION  (Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)       | NAME OF PESTICIDE PRODUCT USOL Organiclear 5 Preservative tor Wood |            |
| Standard Tar Products Co., Inc. 2456 West Cornell Street Milwaukee, WI 53209-6234                                    | ٦ /  | 16/ 166516 |
| L  | L  |            |
|  |  |            |

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA section  $3(c)(7)(\lambda)$  provided that you:

- 1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data.
- 2. Make the labeling changes listed below before you release the product for shipment:
  - a. Add the phrase "EPA Registration No. 458-33."
  - b. Our letter of October 1, 1985 was in error. The signal word and associated precautionary statement on your original label was correct. Change your signal word and precautionary statement from "DANGER" to "WARNING."
- 3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

| ATTACHMENT IS APPLICABLE        |   |           |
|---------------------------------|---|-----------|
| SIGNATURE OF APPROVING OFFICIAL | 11 4. 1/. 6                                 | DATE      |
|                                 | Henry M. Vacoby                             | 2/5/86    |
| EPA Form 8570-6 (Rev. 5-76)     | BESTINIA EDITIONMAY BE USED LINTH SUPPLY IS | EVULUETED |

88867:Forrest: J-4:KENCO: 2/3/86:2/12/86:Klm:V

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Henry M. Jacoby
Product Manager (21)
Fungicide-Herbicide Branch
Registration Division (TS-767C)

Enclosures



EPA Reg. No. 458-GG EPA Est. No. 458-WI-1

# Organiclear TM TM-5 PRESERVATIVE FOR WOOD

STOPS WOOD ROT, DECAY, MILDEW AND PREVENTS TERMITE ATTACK

ACCEPTED
with COMMENTS
in EPA Letter Dated:

PAINTABLE . READY TO USE

To Protect Wood Used Above Ground And Below Ground FEB 5 1986

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 458-33

#### ACTIVE INGREDIENTS:

| Methylene bis (thiocyanate)  | 0.5 % MIN.<br>0.5 % MIN.                |
|--|---|
| INERT INGREDIENTS:   | 99.0 % MAX.                             |
| TOTAL  | 100,0 \$                                |
| DANGER: Keep out of reach of children  See side panel for additional  precautionary statements  NET CONTENTS |   |
| Manufactured by  | ***                                     |
| STANDARD TAR PRODUCTS CO., INC.  | 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 |
| 2456 West Cornell St. Milwaukee, WI 53209  |   |

## PRECAUTIONARI STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

#### DANGER

Corrosive, causes irreversible eye damage and skin damage. Harmful if swallowed, inhaled or absorbed through skin · Causes eye and skin irritation. Use only in well ventilated area · Do not breathe vapor or spray mist · Do not get in eyes, on skin, or on clothing · Wear goggles, face shield or safety glasses, rubber gloves and protective clothing when handling · Wash thoroughly with soap and water after handling.

Keep out of reach of children

#### STATEMENT OF PRACTICAL TREATMENT

In case of eye contact, flush immediately with plenty of water for 15 minutes and get medical attention.

If swallowed, call physician immediately. Do not induce vomiting.

If inhaled, remove to fresh air.

For skin contact, wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash clothes before reuse.

#### ENVIROMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of waste.

#### PHYSICAL AND CHEMICAL HAZARDS

Do not use or store near heat or open flame. Use with adequate ventilation.

Do not use or store inside the home.

#### DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

For Outdoor Use Only.

Use as received without dilution.

Shake Well Before Using.
TO STOP WOOD ROT, DECAY AND MILDEW
Wood should be dry, unpainted, well
seasoned and bark free.

cuating: Apply two or three drenching coats with a mop, sprinkling can or brush. 4015

DIPPING: Soak five minutes or more for each inch of thickness of wood. Posts, poles and timbers should soak 24 to 48 hours.

Allow treated surface to dry (usually all solvent is gone in 24 hours) before painting or varnishing.

Can be painted over when thoroughly dry.

### STORAGE AND DISPOSAL DO NOT USE OR STORE INSIDE THE HOME.

DO NOT REUSE EMPTY CONTAINER. KEEP

AWAY FROM FOOD AND FEED. KEEP CLO-

SURES TIGHT AND UPRIGHT TO PREVENT LEAKAGE. SOAK UP SPILLS OR LEAKS WITH SAND, DIRT OR SYNTHETIC ABSORBENT AND REMOVE TO CONTAINER. DO NOT CONTAMINATE WATER, FOOD, OR FEED BY STORAGE OR DISPOSAL. PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE, OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABÉL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST E.P.A. REGIONAL OFFICE FOR GUIDANCE. HOMEOWNER USE: SEGVINELY WRAP ORIG-INAL CONTAINER IN SEVERAL LAYERS OF NEWSPAPER AND DISCARD IN TRASH! INDUSTRIAL USE: WASTES RESULTING FROM THE USE OF THIS PRODUCT!MAY BE DISPOSED OF ON SITE URAT AN APPROVED WASTE DISPOSAL FACILITY. TRIPLE RINSE (OR EQUIVALENT). THEN OFFER FOR RECYCLING OF RECONDITION. ING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER PROCEDURES APPROVED BY STATE AND LOCAL AUTHORITIES.



### Organiclear TM TM-5

#### PRESERVATIVE FOR WOOD

. PROVIDES PROTECTION for years from decay, mildew and rotting for wooden flooring, for decks and patios, ladders, doors, window frames and sashes, fence posts, stakes and small dimensional lumber, wood siding and shingles. Will not leach from wood.

. PREVENTS ATTACK by termites and other wood-boring insects.

. GIVES CLEAN, PAINTABLE SURFACE for protection of wood above ground. Surfaces will not crack, peel, blister or flake.

ECONOMICAL to use. Increases life of rood. Saves repairs and replacements.

ENETRATING solution soaks in deeply, clean and leaves no sticky surfaces.

CONVENIENT to use. No stirring or mixing. Ready for immediate use. Wood can be treated by coating or soaking.

#### APPROXIMATE COVERAGE

Depending upon method of application and porosity, texture and dryness of wood: 200-400 square feet per gallon.

#### CLEAN UP

Rinse brushes and equipment with water immediately after completion of jobs for fast clean up. Soap and water may be necessary if product begins to dry and becomes sticky on brushes.

#### KEEP FROM FREEZING

IMPORTANT NOTICE TO BUYER: Neither manufacturer nor seller makes any representation of warranty, expressed or implied, concerning this material, other than indicated on the label. Neither shall be held reponsible in any manner for any personal injury, property damange, or other type of loss resulting from the improper handling, storage, and use of this material. See label directions. The buyer accepts and uses this material under these conditions.

Manufacturer will refund the purchase price or replace this product... if within one year of the date of purchase, it is shown to be defective. Manufacturer's liability under any warranty, whether expressed or implied, is limited to one year from date of purchase and does not include any labor, incidential or consequented damanges or losses.