

464-426

4/19/2011

1/5



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

APR 19 2011

OFFICE OF
PREVENTION, PESTICIDES
AND TOXIC SUBSTANCES

Rhonda Vance-Moeser, Senior Regulatory Specialist
The Dow Chemical Company
1790 Building, Office 226
Midland, MI 48667

Subject: Notification per PR Notice 98-10
Antimicrobial 7287
EPA Registration Number: 464-426
Application Date: April 6, 2011
Application Receipt: April 8, 2011

Dear Ms. Vance-Moeser:

This letter acknowledges receipt of your notification submitted under the provisions of FIFRA section 3 (c) 9 and PR Notice 98-10.

Proposed Notification:

The Dow Chemical Company is adding the following qualifier to EPA Reg. No. 464-426:
- "Product not registered for use in California."

General Comments:

Based on a review of the submitted materials, the qualifying statement added is acceptable. A copy of this letter has been made a part of the permanent record for EPA Registration Number 464-426.

If you have questions concerning this letter, please contact me at 703-308-6416 or by email at campbell-mcfarlane.jacqueline@epa.gov or Killian Swift at 703-308-6346 or by email address at: swift.killian@epa.gov. When you are submitting information or data in response to this letter, send a copy of this letter to accompany the submission to facilitate processing.

Sincerely yours,

A handwritten signature in black ink that reads "Jacqueline Campbell-McFarlane".

Jacqueline Campbell-McFarlane
Product Manager 34
Regulatory Management Branch II
Antimicrobials Division (7510P)

Please read instructions on reverse before completing form.

Form approved, OMB No. 2070-0080

Print Form



United States
Environmental Protection Agency
Washington, DC 20460

| | |
|-------------------------------------|--------------|
| <input type="checkbox"/> | Registration |
| <input type="checkbox"/> | Amendment |
| <input checked="" type="checkbox"/> | Other |

OPP Identifier Number

Application for Pesticide - Section I

| | | |
|--|--|--|
| 1. Company/Product Number 464-426 | 2. EPA Product Manager Jacquie Campbell-McFarlane | 3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted |
| 4. Company/Product (Name) The Dow Chemical Company/ Antimicrobial 7287 | PM# 34 | |
| 5. Name and Address of Applicant (Include ZIP Code) The Dow Chemical Company 1803 Building Midland, MI 48674 <input type="checkbox"/> Check if this is a new address | 6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: <input checked="" type="checkbox"/> EPA Reg. No. _____ Product Name _____ | |

Section - II

| | |
|--|--|
| <input type="checkbox"/> Amendment - Explain below. | <input type="checkbox"/> Final printed labels in response to Agency letter dated _____ |
| <input type="checkbox"/> Resubmission in response to Agency letter dated _____ | <input type="checkbox"/> "Me Too" Application. |
| <input checked="" type="checkbox"/> Notification - Explain below. | <input type="checkbox"/> Other - Explain below. |

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

Notification to add a qualifier statement to the label. This Notification adds the qualifier, "Product not registered for this use in California" to the Membrane Systems For Industrial Water use site. Cover letter contains the required Notification statement.

Section - III

| | | | | | |
|---|---|--|--|---|--|
| 1. Material This Product Will Be Packaged In: | | | | 2. Type of Container | |
| Child-Resistant Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No | Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No | Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No | <input type="checkbox"/> Metal <input type="checkbox"/> Plastic <input type="checkbox"/> Glass <input type="checkbox"/> Paper <input type="checkbox"/> Other (Specify) _____ | | |
| * Certification must be submitted | | If "Yes" Unit Packaging wgt. No. per container If "Yes" Package wgt No. per container | | | |
| 3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container | | 4. Size(s) Retail Container | | 5. Location of Label Directions <input type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product | |
| 6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled | | | <input type="checkbox"/> Other _____ | | |

Section - IV

| | | |
|---|---------------------------------------|---|
| 1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.) | | |
| Name Rhonda Vance-Moeser | Title Sr. Regulatory Specialist | Telephone No. (Include Area Code) (989) 636-1884 |
| Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law. | | 6. Date Application Received (Stamped) |
| 2. Signature <i>Rhonda Vance-Moeser</i> | 3. Title Sr. Regulatory Specialist | |
| 4. Typed Name Rhonda Vance-Moeser | 5. Date <i>April 6, 2011</i> | |

**KEEP OUT OF REACH OF CHILDREN
DANGER**

**Precautionary Statements
Hazards to Humans and Domestic Animals
DANGER**

CORROSIVE: Causes irreversible eye damage • May be Fatal if swallowed • Causes skin irritation • Harmful if inhaled or absorbed through skin. • Do not get in eyes, on skin or on clothing. • Avoid breathing spray or mist. • When loading or handling wear protective eyewear (goggles or face shield) Wear long-sleeved shirt and long pants, socks, shoes and chemically resistant gloves • Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals • Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. • Remove and wash contaminated clothing separately before reuse.

Personal Protective Equipment

Applicators and other handlers must wear:
- Coveralls, over long-sleeved shirt and long pants
- socks and chemical resistant footwear
- goggles or face shields
- Chemical-resistant gloves (such as barrier laminate, butyl nitrile/neoprene rubber, PVC or viton)

Engineering Controls

When handlers use closed metering systems the handler requirements may be reduced or modified to long-sleeve shirt, long pants, shoes and socks.

User Safety Requirements

Follow manufacturers' instructions for cleaning & maintaining PPE if no such instructions exist for washables, use detergent and hot water. Keep and wash PPE separately from other laundry

Users must wash hands before eating, drinking, chewing gum, or using the toilet. Users must remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users must remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.

Application Restrictions

Do not apply this product directly in a way that will contact workers or other persons, either directly or through drift. Only protected handlers may be in the area during application.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and aquatic organisms. Apply this product only as specified on this label. Do not contaminate water by cleaning of equipment, or disposal of wastes. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. **Storage:** To maintain product quality, store at temperatures below 35°C. Keep container tightly closed when not in use.

Pesticide Disposal: Pesticide wastes are acutely hazardous. Improper disposal of empty pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

Container Disposal
Option to use for labels on nonrefillable rigid containers of all sizes. Nonrefillable container. Do not reuse or refill this container. Triple rinse or pressure rinse container (or equivalent) promptly after emptying. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

Option to use for labels on refillable rigid tote containers. Refillable container. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning of the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller. To clean container before final disposal, empty contents into application equipment and triple rinse. Pour or pump rinsate into application equipment or rinsate collection system. Then offer for recycling if available, or puncture and dispose of in a sanitary landfill, or by incineration, or by other procedures allowed by state and local authorities.

Notice: Seller warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. SELLER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

ANTIMICROBIAL 7287

To Control Coliform and Other Bacteria in Publicly-Owned Treatment Works; controls bacteria, fungi, and yeasts in paper mills, metalworking fluids containing water, and enhanced oil recovery systems; controls bacteria, fungi, and algae in industrial recirculating water cooling towers and reverse osmosis systems; controls slime-forming bacteria and fungi in air-washer systems.

FOR INDUSTRIAL USE ONLY

Active Ingredient:
2,2-Dibromo-3-nitropropionamide 20%
Inert Ingredient(s): 80%
Total 100%

FIRST AID

| | |
|-------------------------------|---|
| IF IN EYES | <ul style="list-style-type: none"> • Hold eye open and rinse slowly and gently with water for 30 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. • Obtain prompt medical treatment, preferably from an ophthalmologist |
| IF ON SKIN OR CLOTHING | <ul style="list-style-type: none"> • Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15–20 minutes. • Call a poison control center or doctor for treatment advice. |
| IF SWALLOWED | <ul style="list-style-type: none"> • Call a poison control center or doctor immediately for treatment advice. • Have person sip a glass of water if able to swallow. • Do not induce vomiting unless told to do so by the poison control center or doctor. |
| IF INHALED | <ul style="list-style-type: none"> • Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible. • Call a poison control center or doctor for further treatment advice. |

Have product container or label with you when calling a poison control center or doctor or going for treatment.

HOT LINE NUMBER

IN CASE OF AN EMERGENCY endangering life or property involving this product, call collect (989)636-4400.

NOTE TO PHYSICIAN

If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. The decision of whether to induce vomiting or not should be made by a physician. Chemical eye burns may require extended irrigation. Obtain prompt consultation, preferably from an ophthalmologist. If burn is present, treat as any thermal burn, after decontamination. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

E.P.A. Registration No. 464-426
E.P.A. Est. XXX-XX-XXX

NOTIFICATION
Date Reviewed: 4/19/11
Reviewed By: J.M. [Signature]

Produced For



THE DOW CHEMICAL COMPANY
Midland, Michigan 48674
989-636-4400

® TM Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

NET CONTENTS: XXXX gallons
NET WT: XXX lb / XXX kg
LOT NO:

INSTRUCTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with the labeling.

575

NOTE: ADD ANTIMICROBIAL 7287 SEPARATELY TO THE SYSTEM. DO NOT MIX IT WITH OTHER ADDITIVES, IN ORDER TO AVOID DECOMPOSITION OF Antimicrobial 7287 DUE TO THE HIGH pH OF MANY ADDITIVE FORMULATIONS.

PAPER MILLS

For the control of bacterial, fungal, and yeast growths in pulp, paper and paperboard mills, add Antimicrobial 7287 at the rate of 0.15-0.50 lb / ton of pulp or paper (dry basis). Addition may be continuous or intermittent, depending upon the type of system and the severity of contamination. It must be made with a metering pump at a location that will insure uniform distribution of ANTIMICROBIAL 7287 in the mass of fiber and water, such as the beaters, Jordan inlet or discharge, broke chests, furnish chests, save-alls, and white-water tanks.

HEAVILY FOULED SYSTEMS must be boiled out, then treated with 0.15-0.35 lb ANTIMICROBIAL 7287 / ton of paper (dry basis), as necessary for control.

MODERATELY FOULED SYSTEMS must be treated continuously with 0.35-0.50 lb ANTIMICROBIAL 7287 / ton of paper (dry basis) until the slime accumulation is controlled. Addition rates can then be reduced to 0.15-0.35 lb ANTIMICROBIAL 7287 / ton of paper on a continuous or intermittent basis, as needed for control. Dislodged slime may cause breaks in the paper and a clean-up of the paper machine may be advisable.

SLIGHTLY FOULED SYSTEMS must be treated continuously with 0.15-0.35 lb ANTIMICROBIAL 7287 / ton of paper (dry basis) until the slime is controlled, then added on an intermittent basis to maintain control.

METALWORKING FLUIDS CONTAINING WATER

This product is effective in metalworking fluid concentrates which have been diluted in water at ratios of 1:100-1:4. For controlling (or inhibiting) the growth of bacteria, fungi, and yeasts that may deteriorate metalworking fluids containing water, add Antimicrobial 7287 to the fluid in the collection tank. Additions must be made with a metering pump.
INITIAL OR SLUG DOSE: When the system is just noticeably fouled, add 0.25 gal Antimicrobial 7287 / 1,000 gal of metalworking fluid to the system. Repeat until control is achieved.
SUBSEQUENT DOSE: When microbial control is evident, add 0.1-0.2 gal Antimicrobial 7287 / 1,000 gal of metalworking fluid per day, or as needed to maintain control. Additions can be made continuously or intermittently. Slug the system as required.

ENHANCED OIL RECOVERY SYSTEMS

For controlling slime-forming bacteria, sulfide-producing bacteria, yeasts, and fungi in oil field water, polymer or micellar floods, water-disposal systems, or other oil field water systems, add 1-80 ppm Antimicrobial 7287 (0.1-6.4 gal Antimicrobial 7287 per 2400 barrels of water) depending on the severity of contamination. Additions must be made with a metering pump either continuously or intermittently.

CONTINUOUS FEED METHOD

When the system is noticeably fouled, add 10-80 ppm Antimicrobial 7287 (0.8-6.4 gal Antimicrobial 7287 per 2400 barrels of water) continuously until the desired degree of control is achieved. Subsequently, treat with 1-15 ppm Antimicrobial 7287 (0.1-1.2 gal Antimicrobial 7287 per 2400 barrels of water) continuously or as needed to maintain control.

INTERMITTENT OR SLUG METHOD

When the system is noticeably fouled, or to maintain control of the system, add 10-80 ppm Antimicrobial 7287 (0.8-6.4 gal Antimicrobial 7287 per 2400 barrels of water) intermittently for 4-8 hours per day, and from 1-4 times per week, or as needed depending on the severity of contamination.

Addition of Antimicrobial 7287 may be made at the free water knockouts, before or after the injection pumps and injection well headers.

NOTE: FOR CONTROL OF BACTERIA, YEAST, AND FUNGI IN AQUEOUS SOLUTIONS OF BIOPOLYMER USED IN FLOODING OPERATIONS, add 15-80 ppm Antimicrobial 7287 (1.2-6.4 gal Antimicrobial 7287 per 2400 barrels of water). Additions of ANTIMICROBIAL 7287 must be made with a metering pump IMMEDIATELY after preparation of the aqueous biopolymer solution to prevent loss of viscosity.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

Add Antimicrobial 7287 to the basin (or any other point of uniform mixing). Additions should be made with a metering pump; it may be continuous or intermittent, depending on the severity of the contamination when treatment is begun, and the retention time of the system. Optimum performance with this product is attained by continuous or intermittent treatment. If "shock" treatment is used, the blowdown must be discontinued for 24-48 hours.

FOR CONTROL OF BACTERIA

Add 0.00095-0.0095 gal Antimicrobial 7287/1,000 gal of water in the system, depending on the severity of contamination.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, add 0.0048-0.0095 gal Antimicrobial 7287/1,000 gal of water in the system. Repeat until control is achieved.

SUBSEQUENT DOSE:

When microbial control is evident add 0.0024-0.0095 gal Antimicrobial 7287/1,000 gal of water in the system every 4 days, or as needed to maintain control.

BADLY FOULED SYSTEMS must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, add 0.0048-0.0095 gal Antimicrobial 7287/1,000 gal of water to the system.

SUBSEQUENT DOSE: Maintain this level by pumping a continuous feed of 0.00095-0.0048 gal Antimicrobial 7287/1,000 gal of water in the system per day.

BADLY FOULED SYSTEMS must be cleaned before treatment is begun.

FOR CONTROL OF FUNGI AND ALGAE

Add 0.029-0.095 gal Antimicrobial 7287/1,000 gal of water in the system depending on the severity of contamination.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, add 0.048-0.095 gal Antimicrobial 7287/1,000 gal of water in the system. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 0.029-0.095 gal Antimicrobial 7287/1,000 gal of water in the system daily, or as needed to maintain control.

BADLY FOULED SYSTEMS must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, add 0.048-0.095 gal Antimicrobial 7287/1,000 gal of water to the system.

SUBSEQUENT DOSE: Maintain this treatment level by pumping a continuous feed of 0.029-0.095 gal Antimicrobial 7287/1,000 gal of water in the system per day.

BADLY FOULED SYSTEMS must be cleaned before treatment is begun.

MEMBRANE SYSTEMS FOR INDUSTRIAL WATER

Product not registered for this use in California

Antimicrobial 7287 may be used to control bacteria and reduce biofouling in various membrane system types (reverse osmosis, ultrafiltration, nanofiltration, and microfiltration) used for industrial water processing. Acceptable applications include reverse osmosis for the production of boiler make-up water, electronic component rinsing, and industrial wastewater treatment.

NOTE: Reverse Osmosis (RO) concentrate streams must not be discharged to lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Permit (NPDES). Discharge of RO concentrate streams to sewer systems may require approval of the local sewer treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Antimicrobial 7287 may be added to the RO feed water at a rate of 1 to 100 ppm based on the feed water flow rate (0.1 to 10 fl. oz./min per 1000 gallons/min. feed water, or 0.8 to 80 mls/min per cubic meter/min of feed water). Apply product to the service cycle feed water on a regular basis using an addition cycle of at least 30 minutes. The frequency of addition may be daily or as necessary in order to maintain RO productivity performance. For highly fouled systems, a 100 ppm dosage should be applied each day for several hours until the system performance has recovered.

NOTE: Do not add Antimicrobial 7287 in the presence of sodium bisulfite or other reducing agents which are being added to the feed water of the membrane system. In some situations the addition of any reducing agents must be suspended at least 15 minutes prior to the addition of Antimicrobial 7287 in order to avoid neutralization and deactivation of the active ingredient.

Antimicrobial 7287 may be added to the feed tank used for an off-line chemical cleaning procedure. Addition should be at a rate of 20 to 200 ppm based on the total amount of solution in the feed tank (2 to 20 fl. oz. per 1000 gallons, or 16 to 160 mls. per cubic meter). Following the complete transfer of feed solution, re-circulate or soak for 1 to 3 hours to ensure sufficient contact for all RO membrane modules with the DBNPA solution. Frequency of addition should be every 5 days or as needed.

NOTE: Add Antimicrobial 7287 separately to the feed tank system. Do not mix with other chemical additives as this may result in rapid decomposition of Antimicrobial 7287 due to the high pH of many additive formulas. It is important to thoroughly rinse the feed tank system so it is free of any high pH chemicals prior to introducing the Antimicrobial 7287 product.

AIR-WASHER SYSTEMS

Add 0.0015-0.095 gal Antimicrobial 7287/1,000 gal of water in the system, depending upon the severity of contamination to control slime-forming bacteria and fungi in industrial air-washer systems.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, add 0.003-0.095 gal Antimicrobial 7287/1,000 gal of water in the system. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 0.0015-0.047 gal Antimicrobial 7287/1,000 gal of water in the system every 2 days or as needed to maintain control.

Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, add 0.003-0.095 gal Antimicrobial 7287/1,000 gal of water in the system.

SUBSEQUENT DOSE: Maintain this level by pumping a continuous feed of 0.0015-0.047 gal Antimicrobial 7287/1,000 gal of water in the system per day.

Badly fouled systems must be cleaned before treatment is begun.

NOTE: For use only in industrial air-washer systems that maintain effective mist eliminating components.

HYDROTESTING

Product not registered for this use in California

FOR CONTROL OF BACTERIA

Water used to hydrotest pipelines or vessels should contain 100 to 1,000 ppm of ANTIMICROBIAL 7287 per 1,000 gallons water depending on water quality and length of time the equipment will remain idle.

PUBLICLY-OWNED TREATMENT WORKS

TO CONTROL COLIFORM AND OTHER BACTERIA

Add Antimicrobial 7287 at a concentration of 1.0 to 10.0 ppm by weight of water being treated, depending on the severity of contamination in the system. Addition should be CONTINUOUS and must be made with a metering pump at a point in the system where mixing will be rapid and thorough. Add Antimicrobial 7287 to the system in a location where contact time will be 30 minutes or greater before reaching the outfall.

TO USE AS A CO-TREATMENT WITH CHLORINE

Add 0.4-1.5 ppm Antimicrobial 7287 by weight of water treated. Chlorination must result in a minimum detectable residual (i.e., greater than zero but less than the NPDES permit level). Addition must be CONTINUOUS and made at a point just after initial chlorine mixing. Rapid mixing is necessary for maximum effectiveness. ANTIMICROBIAL 7287 must be added at a location where a contact time of 10 minutes or longer will be provided before reaching the outfall.

HIGHLIGHTED COPY



NSF Non Food Compounds Listing
This product is acceptable for treating boilers, steam lines, and/or cooling systems (G7) where neither the treated water nor the steam produced may contact edible products in and around food processing areas.