UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

November 7, 2006

Maureen Miksztal Senior Regulatory Specialist The Dow Chemical Company 1803 Building Midland, MI 48674

Subject:

Amical 48

EPA Registration No.: 464-670 Application Date: October 19, 2006 Receipt Date: October 23, 2006

Dear Ms. Miksztal,

This acknowledges receipt of your notification, submitted under the provision of PR Notice 98-10, FIFRA section 3(c)9.

Proposed Notification

Add the phrase "see outer package label for use directions" to inner packaging.

General Comments

Based on a review of the material submitted, the following comments apply:

The notification application is acceptable and a copy has been inserted in your file for future reference.

Should you have any questions or comments concerning this letter, please contact me at (703) 308-6422.

Sincerely,

Adam Heyward

Product Manager (34)

Regulatory Management Branch II Antimicrobials Division (7510P)

	CONCURRENCES	
YMBOL 7510 P		
JRNAME) (Coly		***************************************
ATE 1/07/06		***************************************
TO E 1000 18 /100)	Britania Branch (B	

									2/5	
SEPA	United States Environmental Protection Agency Washington, DC 20460		proved	Registration Amendment Other		OPP Identifier Number				
		Application	on for Pestic	de - Sec	tion	1				
1. Company/Product Number 464-670	of .		1	2. EPA Product Menager A. Heyward 3. Proposed Classification Restrict None				fication Restricted		
. Company/Product (Name) AMICAL 48			PM# 34	PM#						
5. Name and Address of Applicant (Include ZIP Code)			6. Exp	6. Expedited Reveiw. In accordance with FIFRA Section 3(c)(3)						
The Dow Chemical Company 1803 Building Midland, MI 48674			to:	(b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No						
Check if this	s is a new address		Produ	ct Name						
			Section -)						
Amendment - Explain below. Resubmission in response to Agency letter dated Notification - Explain below. Explanation: Use additional page(s) if necessary. (For section I and Sec The Dow Chemical Company is submitting a notification to add the phrase "Se			phrase "See outer F							
AMICAL 48 sold in bags. Allabel will be applied on the one other changes have been 1001 to willfully make any fa 152.46, this product may be	uter packaging. This no made to the labeling o lse statement to EPA.	tification is con r the confidentia further unders	sistent with the prov al statement of formit tand that if this notifi	isions of PR N ula of this producation is not c action and per	lotice 9 Juct. : onsiste	8-10 and EPA re understand that i ent with the terms	egulations it is a viola of PR N	at 40CFR 1 ation of 18U. otice 98-10 a	52.46, and S.C. Sec.	
1. Material This Product Wil	Be Packaged In:	 						· · · · · · · · · · · · · · · · · · ·		
Child-Resistant Packaging Yes No * Certification must be submitted	Unit Packaging Yes No If "Yes" Unit Packaging wgt.	No. per container	Water Soluble F Yes No If "Yes" Package wgt	No. per		P G P	ntainer fetal lastic lass aper ether (Spe	ocify) fibe	ır pack, bag	
3. Location of Net Contents	Information Container	4. Size(s) Ret	tail Container er pack, 2.5 lb LO	MEL bag	5. Loc	cation of Label [Directions	<u> </u>		
6. Manner in Which Label is		Lithog Paper Stenci	raph glued	Other					-	
			Section - I'	V						
1. Contact Point (Complete	items directly below t	for identificatio			if nece	ssary, to proces	ss this ap	plication.)		
Name Maureen Miksztal			Title Senior Regulator	y Specialist		1	aphona N 2-563-558	io. (Include 33	Area Code)	
i certify that the state i acknowledge that ar both under applicable	ny knowlingliy false or	Certifica this form and misleading sta	all attachments the	ereto are true nishable by fil	, accu ne or ir	rate and comple nprisonment or	rtc.	Dete Appli Reneived (Stam		
2. Signeture	In locat	e	3. Title Senior Regulatory	Specialist						
4. Typed Name Maureen Miksztal				10/19/06						



October 19, 2006

3/5

The Dow Chemical Company 171 River Road Piscataway, NJ 08854 USA

Overnight Delivery

Document Processing Desk (NOTIF)
Office of Pesticides Programs (7504P)
Antimicrobials Division
U. S. Environmental Protection Agency
Room S-4900, One Potomac Yard
2777 South Crystal Drive
Arlington, VA 22202-4501

Subject: AMICAL™ 48 EPA Reg. No. 464-670

Notification of Minor Label Change

Dear Sir/Madam:

Per PR Notice 98-10, The Dow Chemical Company is submitting a notification to the registration for AMICAL™ 48 EPA Reg. No. 464-670. Please find enclosed the following documentation in support of this application:

- Application Form, EPA Form 8570-1
- Draft label with highlighted change

Maureen Willsex

Please contact me at 732-563-5586 with questions or comments regarding this submission. Thank you for your assistance.

Sincerely,

Maureen Miksztal

Senior Regulatory Specialist

cc: Mr. Adam Heyward, PM-34

Enclosure

AMICAL 48

Active Ingredients: Diiodomethyl p-tolyl sulfone......95% Inert Ingredients:................5% TOTAL 100%

E.P.A. Registration No. 464-670 E.P.A. Est. 33657-JP-3 KEEP OUT OF REACH OF CHILDREN

DANGER

PRECAUTIONARY STATEMENTS
Hazards to Humans and Domestic Animals
DANGER. Corrosive. Causes
irreversible eye damage. Harmful
if absorbed through the skin.

Do Not Get In Eyes, On Skin, Or On Clothing • Wear Goggles, Face Shield, or Safety Glasses • Wash Thoroughly With Soap And Water After Handling • Remove Contaminated Clothing and Wash Clothing Before Reuse

Produced for:



THE DOW CHEMICAL COMPANY

Midland, Michigan 48674 U.S.A. (989)636-4400

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow D

77270-10/18/2006-1823 Made in Japan

FIRST AID:				
IF IN EYES:	 Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing eyes. Call a poison control center or doctor for treatment advice. 			
IF SWALLOWED:	 Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to by a poison control center or doctor. Do not give anything by mouth to an unconscious person. 			
IF ON SKIN:	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment.			
IF INHALED:	 Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferable mouth to mouth, if possible. Call a poison control center or doctor for further treatment. 			
HOT LINE NUMBER				

Have the product container or label with you when calling a poison control center or doctor or going for treatment.

IN CASE OF AN EMERGENCY endangering life or property involving this product, call 1-800-424-9300.

NOTE TO PHYSICIAN: Probable mucosal damage may preclude the use of gastric lavage.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not contaminate water when disposing of equipment washwaters. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Store in a dry area. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinstate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. CONTAINER DISPOSAL: Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Then dispose of liner in a sanitary landfill or by incineration if allowed by state and local authorities. If drum is contaminated and cannot be reused, dispose of in the same manner.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with the labeling.

USE IN PAINTS

AMICAL 48 is an effective mildewcide and algicide for exterior and interior paints, fire-retardant insulation coating and air duct coatings. Use levels in paint and duct coating will vary depending upon the formulation and expected severity of field conditions. Generally, AMICAL 48 will impart protection when used at levels of between 1.6-5 lb AMICAL 48 per 100 gallons of paint for severe situations while 1-3 lb AMICAL 48 per 100 gallons of paint are sufficient for less severe conditions. AMICAL 48 should be added during the last few minutes of the pigment grind for maximum dispersion. For mildew control on fire-retardant coating add AMICAL 48 at 0.0015 to 0.3% at point in production process to ensure sufficient mixing with other dry ingredients.

USE IN PIGMENT DISPERSIONS, INKS, EMULSIONS AND EXTENDER SLURRIES

To inhibit the growth of spoilage fungi during storage of water-based suspensions and dispersions. AMICAL 48 will impart protection when dosed at 0.02-0.15% (w/w). AMICAL 48 at a point in the production process where sufficient mixing will assure good suspension of the material as other ingredients are added.

12/2

USE IN ADHESIVES, CAULKS, AND SEALANTS

AMICAL 48 is recommended for use in adhesives and binders, e.g., joint compounds, tile mastics, wallpaper paste, carpet backing, air filer and foil scrim Kraff laminate; and sealants and caulks where mildew growth on the applied or stored product may be a problem. For control of mildew growth add 0.01-0.30% AMICAL 48 at a point in the production process where sufficient mixing will assure good suspension of the material as other ingredients are added.

USE IN LEATHER TANNING

AMICAL 48 is used in protecting chrome or vegetable tanned leather from mold and mildew during in-tannery wet processing and for protecting wet-blue during long storage and long transportation times. For normal protection of chrome-tanned cattle hides (based on white weight of hides) use 0.01-0.02%, for sheep hides (based on drained pickle weight) 0.05-0 08%, and for goat and small skins use levels should be calculated on the dry basis of the skin weight, assuming limed weight to be 20% dry basis and pickled weight to be 33% dry basis. When long hold or export protection is required, use 0.02-0.04% for cattle, 0.08-0.15% for sheep, and on goat and small skins follow recommendations for normal protection. Use level recommendations during retan/color/fatliquor protection of chrome-tanned hides for all hide types are 0.1-0.3 (% on wet blue weight. In all applications, add the dry AMICAL 48 through the drum door, preferably by sprinkling across the width of the drum. This should be done just prior to chrome addition, or together with the formate, if formate is added dry prior to chrome. In the case of retan/color/fatliquor, add AMICAL 48 prior to the prime fatliquor

USE IN WOOD PRESERVATION - (FOR FORMULATING USE ONLY)

AMICAL 48 can be used for control of mildew, sapstain, and wood rotting organisms. Incorporate AMICAL 48 into appropriate vehicles to protect wood from stain and decay. AMICAL 48 can be utilized in either aqueous or solvent-based systems at concentrations ranging from 0.3-1.0% (w/w). Solvent-based systems containing mineral spirits require a suitable co-solvent for the incorporation of AMICAL into the system. Formulators are responsible for obtaining EPA registration of formulated products.

USE IN METALWORKING FLUIDS

AMICAL 48 is recommended for use in metalworking fluids and lubricants to prevent fungal growth. The level of AMICAL 48 to be incorporated into metalworking fluid concentrate will vary depending upon the dilution factor recommended by the manufacturer. For efficient fungistatic activity, a concentration 100 to 3000 ppm of AMICAL 48 in the diluted fluid is suggested. AMICAL 48 should be dissolved in an appropriate solvent prior to addition to the metal working fluid.

USE IN RUBBER AND PLASTIC PRODUCTS

AMICAL 48 is recommended for PVC, polyurethane, rubber, thermoplastic rubber and other polymeric based products, coating, adhesives, foams, and sealants requiring protection against microbial deterioration. For control of microbial deterioration use 0.1-0.8% AMICAL 48 based upon total weight of solids in the formulation. AMICAL 48 can be incorporated into the formulation at any convenient stage of the manufacturing process.

USE IN TEXTILES AND NON-WOVENS (NON-CLOTHING)

Topmorent mildew growth on products such as canvas, carpet, cordaye, drapes, filters, and shower curtains. Use levels depend upon the expected severity of exposure or end-use conditions. In general 0.5 to 5.0 lb of AMICAL 48 per 1000 lb of dry labric (500-5 900 ppm) is needed. AMICAL 48 is best added together with the waler-repellent emulsion of dry to ensure durability.

USE IN PAPER PRODUCTION

This product aids in the control of objectionable fungi in pulp, paper mills and the additive system and for the preservation of pulp, pigment slurries, alum, emulsions, adhesives, defoamers, polymers and paper products. This product is used to inhibit fungal growth which causes discoloration, odor and degradation in paper and paperboard. This product is not cleared for use in the manufacture of paper and paperboard products that come in contact with food.

Additions can be made on a continuous or intermittent basis depending upon the severity of the contamination. Badly touled systems must be cleaned before treatment is begun. Apply at a point in the system where the product will be uniformly mixed. Intermittent or Siug Method - Initial Dose: When the system is noticeably fouled, add this product at the rate of 0.0008 to 0.8 lb per ton of pulp, or paper produced. Addition to the additive system should be made directly at the rate of 0.004 to 3.32 lb (0.48 to 400 ppm) per 1000 gallons. Repeat until control is achieved. Subsequent Dose: When microbial control is evident, add this product at the rate of 0.0008 to 0.4 lb per ton of pulp or paper produced. Treat the system as needed to maintain control. Addition of this product to the additive system may be reduced to 0.004 - 1.68 lb (0.48 to 200 Pam) per 1000 gallons.

Continuous Feed Method - Initial Dose: When the system is noticeably fouled, add this product at the rate of 0.0008 to 0.4 lb per ton of pulp of paper produced. Additions of this product to the additive system should be made directly at the rate of 0.004 to 2.52 lb (0.48 to 300 ppm) per 1000 gallons. Continue until control is achieved. Subsequent Dose: Maintain by continuous feed of this product at the rate of 0.0008 to 0.4 lb per ton of pulp and paper product.

MOLD INHIBITION IN PAPER AND PAPERBOARD

This product is used to inhibit fungal growth which causes discoloration, odor and degradation in paper and paperboard. This product may be applied to the white water or stock at a rate of 0.02 to 3.4 lb per ton of dry fiber produced. For inhibition of wet lap or sheet pulp, this product should be applied to the dewatered pulp surfaces via applicator rolls or shower at 0.02 to 3.4 lb per ton of dry fiber produced. Application can also be made at the size press or water box. Application is made at the rate of 80 to 8,000 ppm of this product in the solution applied to the paper sheet.

PRESERVATION IN PAPER PLANT STORAGE

This product should be added directly to the material to be preserved prior to manufacturing into the finished product, i.e., pulp, alum, broke, polymers, defoamers, emulsions, adhesives, paper mill coating, pigment and slurries. The dosage rate will depend upon the material to be preserved and the storage time. The usual additions should be 0.2 ppm for storage of microbial resistant materials up to 250 ppm for less resistant materials. Under extreme conditions of spoilage the dosage rate should be increased to 4 to 400 ppm. The above recommendations are based on a maximum storage time of two weeks.

USE WITH NITROCELLULOSE

AMICAL 48 is an effective antifungal agent for use in nitrocellulose wet with water for purposes of storage and shipment. Add 0.05 to 0.3% by weight of AMICAL 48 based upon the viet weight of nitrocellulose. AMICAL 48 should be added to the nitrocellulose only by the manufacturer as the last ingregient.

3