PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER **KEEP OUT OF REACH OF CHILDREN**

Corrosive. Causes irreversible eye damage. Causes skin burns. Harmful if inhaled. May be fatal if swallowed. Harmful if absorbed through skin. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

Causes asthmatic signs and symptoms in hyper-reactive individuals.

Do not get in eyes, on skin, on clothing. Avoid breathing vapor. Do not swallow.

Wear googles, protective clothing, and butyl or nitrile gloves.

Wash thoroughly with soap and water after handling.

Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND HANDLING

UCARCIDETM 250 Antimicrobial solutions are incompatible with many commonly used materials of construction such as steel, galvanized iron, aluminum, tin, and zinc. These solutions can be stored and handled in baked phenolic-lined steel, polyethylene, stainless steel, or reinforced epoxy-plastic equipment. This product freezes at about -6°F (-21°C). Therefore, unless the storage tank is inside or underground, heating and insulation may be required. If heating is needed, exposure to high temperatures should be avoided. For short storage times (up to about 1 month), temperatures of up to 100°F (37.8°C) can be tolerated but the preferred maximum storage temperature is about 80°F (26.7°C).

A stainless steel centrifugal pump is suggested for transfer service. Spiral-wound stainless steel with TEFLON® is suitable for paskets and packing.

LIMITED WARRANTY AND DISCLAIMER

Seller warrants that the product conforms to its chemical description as contained on this label and is reasonably fit for the purposes stated on this label when used in accordance with directions under normal conditions of use. THE WARRANTIES MADE IN THIS PARAGRAPH ARE SELLER'S SOLE WARRANTIES WITH RESPECT TO THE PRODUCT AND ARE MADE EXPRESSLY IN LIEU OF AND EXCLUDE ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER EXPRESS OR IMPLIED REPRESENTATIONS AND

BEFORE HANDLING OR USING, READ AND UNDERSTAND CURRENT MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT.





Active Ingredient: Glutaraldehyde Inert Inafedients: 100.0%

KEEP OUT OF REACH OF CHILDREN **DANGER**

If swallowed:

FIRST AID

Call a poison control center or a doctor immediately for treatment advice. DO NOT INDUCE VOMITING.

Do not give anything to drink.

If in eyes:

Hold eve open and rinse slowly and cently with water for 15-20 minutes.

After at least 15 minutes of rinsing or after it is judged that nearly all of the contamination has been removed, contact an Ophthalmologist before attempting to remove the contact lens(es).

Call a poison control center or a doctor immediately for treatment advice.

If on skin or clothing:

Take off contaminated clothing.

Rinse skin immediately with plenty of water for 15-20 minutes.

Call a poison control center or a doctor for treatment advice.

If inhaled:

Move person to fresh air.

If person is not breathing, call 911 or an ambulance, and then give artificial respiration, preferably mouth-to-mouth if possible.

Call a poison control center or a doctor for further treatment advice.

NOTE TO PHYSICIAN: Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of gastric lavage.

Have the MSDS and, if available, the product container or label with you when calling a poison control center or a doctor, or going for treatment.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.



THE DOW CHEMICAL COMPANY

Midland, Michigan 48674 U.S.A. 1-800-258-CHEM

EPA Reg. No. 464-691 EPA Est. No. 10352-WV-2 (A) :464-WV-1 (B) (A)5 gallon pails in pallets; all drums; bulk (B)Single 5 gallon pails only

*Trademark of THE DOW CHEMICAL COMPANY

L90222 (F 10/01) Made In USA

PE0202 CONTAINER SIZE SHIPPING CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (CONTAINS GLUTARALDEHYDE) Net Contents: 55 gallons 55 GALLONS NAME 500 POUNDS ID NUMBER HAZARD CLASS PG II UN 3265 **NET WEIGHT**

IN CASE OF AN EMERGENCY endangering life or property involving this product, call collect 989-636-4400

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling

ACCEPTED

JUN 18 2002

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 464

STORAGE AND DISPOSAL

PESTICIDE DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or your Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Metal Containers or Plastic Containers: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or other procedures approved by state and local authorities. Plastic Containers: May be incinerated, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke. Metal Containers: Must not be incinerated. Do not cut or weld on or near metal containers.