

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

WATER FLOODS

UCARCIDETM 145 LT Antimicrobial should be added to a water flood system at a point of uniform mixing.

Initial Treatment: When the system is noticeably contaminated, add 110 to 5,560 ppm UCARCIDETM 145 LT Antimicrobial to the system (0.1 to 5.6 gallons UCARCIDETM 145 LT Antimicrobial per 1,000 gallons flood water). Repeat until control is achieved.
Subsequent Dose: When microbial control is evident, add 20 to 5,560 ppm UCARCIDETM 145 LT Antimicrobial (0.02 to 5.6 gallons UCARCIDETM 145 LT Antimicrobial per 1,000 gallons flood water) to the system weekly, or as needed to maintain control.

DRILLING, COMPLETION, AND WORKOVER FLUIDS

UCARCIDETM 145 LT Antimicrobial should be added to a drilling fluid system at a point of uniform mixing such as the circulating mud tank.

Initial Treatment: Add 60 to 1,110 ppm UCARCIDETM 145 LT Antimicrobial (0.2 to 4.4 gallons UCARCIDETM 145 LT Antimicrobial per 100 barrels of fluid) to a freshly prepared fluid depending on the severity of contamination.
Maintenance Dosage: Maintain a concentration of 60 to 1,110 ppm UCARCIDETM 145 LT Antimicrobial by adding 0.2 to 4.4 gallons of UCARCIDETM 145 LT Antimicrobial per 100 barrels of additional fluid, or as needed, depending on the severity of contamination.

PACKER FLUIDS

UCARCIDETM 145 LT Antimicrobial should be added to a packer fluid at a point of uniform mixing such as a circulating holding tank. Add 60 to 670 ppm UCARCIDETM 145 LT Antimicrobial (0.2 to 2.8 gallons UCARCIDETM 145 LT Antimicrobial per 100 barrels of fluid) to a freshly prepared fluid depending on the severity of contamination. Seal the treated packer fluid in the wall between the casing and production tube.

GAS PRODUCTION AND TRANSMISSION PIPELINES AND SYSTEMS

UCARCIDETM 145 LT Antimicrobial should be added to a gas production or transmission pipeline via direct injection. The application should be conducted to ensure maximum distribution of the UCARCIDETM 145 LT Antimicrobial through the entire internal surface of the pipeline. To facilitate application, it may be desirable to dilute the UCARCIDETM 145 LT Antimicrobial with an appropriate solvent immediately before use. Injections to the system should be weekly, or as needed to maintain control.

GAS STORAGE WELLS AND SYSTEMS

Individual injection wells should be treated with a sufficient quantity of UCARCIDETM 145 LT Antimicrobial to produce a concentration of 560 to 5,560 ppm UCARCIDETM 145 LT Antimicrobial when diluted by the water present in the formation. Injection should take place before gas is injected (during the summer). Injections should be repeated yearly, or as needed to maintain control.

Individual drips should be treated with a sufficient quantity of UCARCIDETM 145 LT Antimicrobial to produce a concentration of 220 to 2,220 ppm UCARCIDETM 145 LT Antimicrobial when diluted by the water present in the drip. Injections should be repeated yearly, or as needed to maintain control.

HYDROTESTING

Water used to hydrotest pipelines or vessels should contain 110 to 4,440 ppm UCARCIDETM 145 LT Antimicrobial (0.1 to 4.4 gallons UCARCIDETM 145 LT Antimicrobial per 1,000 gallons water), depending on water quality and length of time the equipment will remain idle.

PIPELINE PIGGING AND SCRAPING OPERATIONS

Add UCARCIDETM 145 LT Antimicrobial to a slug of water immediately following the scraper (ideally this water volume can be kept to a minimum and contained between the scraper and a trailing pig). Sufficient UCARCIDETM 145 LT Antimicrobial should be added to produce a concentration of 0.1 to 1.1% (0.1 to 1.1 gallons UCARCIDETM 145 LT Antimicrobial per 100 gallons water), depending on the length of the pipeline and the severity of biofouling.

STORAGE AND DISPOSAL

PESTICIDE DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or your Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.
CONTAINER DISPOSAL: Metal Containers or Plastic Containers: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or other procedures approved by state and local authorities. Plastic Containers: May be incinerated, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke. Metal Containers: Must not be incinerated. Do not cut or weld on or near metal containers.

464-695
10-12-2001

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**DANGER
KEEP OUT OF REACH OF CHILDREN**

Corrosive. Causes irreversible eye damage. Causes skin burns. Harmful if inhaled. May be fatal if swallowed. Harmful if absorbed through skin. Prolonged or frequently repeated skin contact may cause allergic skin reactions in some individuals. Causes asthmatic signs and symptoms in hyper-reactive individuals. Do not get in eyes, on skin, on clothing. Avoid breathing vapor. Do not swallow. Wear goggles, protective clothing, and butyl or nitrile gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

PHYSICAL AND CHEMICAL HAZARDS

Extremely Flammable! Keep away from heat, sparks and open flame.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.


STORAGE AND HANDLING

UCARCIDETM 145 LT Antimicrobial solutions are incompatible with many commonly used materials of construction such as steel, galvanized iron, aluminum, tin, and zinc. These solutions can be stored and handled in baked phenolic-lined steel, polyethylene, stainless steel, or reinforced epoxy-plastic equipment. This product freezes at about -20°F (-29°C). Therefore, unless the storage tank is inside or underground, heating and insulation may be required. If heating is needed, exposure to high temperatures should be avoided. For short storage times (up to about 1 month), temperatures of up to 100°F (37.8°C) can be tolerated but the preferred maximum storage temperature is about 80°F (26.7°C). A stainless steel centrifugal pump is suggested for transfer service. Spiral-wound stainless steel with TEFLON® is suitable for gaskets and packing.

LIMITED WARRANTY AND DISCLAIMER

Seller warrants that the product conforms to its chemical description as contained on this label and is reasonably fit for the purposes stated on this label when used in accordance with directions under normal conditions of use. THE WARRANTIES MADE IN THIS PARAGRAPH ARE SELLER'S SOLE WARRANTIES WITH RESPECT TO THE PRODUCT AND ARE MADE EXPRESSLY IN LIEU OF AND EXCLUDE ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER EXPRESS OR IMPLIED REPRESENTATIONS AND WARRANTIES.

BEFORE HANDLING OR USING, READ AND UNDERSTAND CURRENT MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT.



Active Ingredient: Glutaraldehyde _____ 45.0%
 Inert Ingredients: _____ 55.0%
 100.0%

**KEEP OUT OF REACH OF CHILDREN
DANGER**

FIRST AID

If swallowed:

- Call a poison control center or a doctor immediately for treatment advice.
- DO NOT INDUCE VOMITING.
- Do not give anything to drink.

If in eyes:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- After at least 15 minutes of rinsing or after it is judged that nearly all of the contamination has been removed, contact an Ophthalmologist before attempting to remove the contact lenses).
- Call a poison control center or a doctor immediately for treatment advice.

If on skin or clothing:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or a doctor for treatment advice.

If inhaled:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, and then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or a doctor for further treatment advice.

NOTE TO PHYSICIAN: Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of gastric lavage.

Have the MSDS and, if available, the product container or label with you when calling a poison control center or a doctor, or going for treatment.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.



THE DOW CHEMICAL COMPANY
 Midland, Michigan 48674 U.S.A.
 1-800-258-CHEM
 *Trademark of THE DOW CHEMICAL COMPANY

EPA Reg. No. 464-
 EPA Est. No. 10352-WV-2
 L55997 (F06/01)
 Made In USA
 PE0601

Net Contents: 55 gallons

CONTAINER SIZE	SHIPPING NAME	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (CONTAINS ACETONE, GLUTARALDEHYDE)	
55 GALLONS		ID NUMBER	PG II
465 POUNDS NET WEIGHT	HAZARD CLASS 3E	UN 2924	

IN CASE OF AN EMERGENCY endangering life or property involving this product, call collect 989-636-4400.

ACCEPTED

OCT 12 2001

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 464-695

NOTICE

Do Not Ship or Store with Food, Feeds, Drugs, or Clothing

