## UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460

12/23/2008

SEPA United States Environmental Protection Office of Pesticide Programs

The Dow Chemical Company 1803 Building Midland, Mi 48674

464-700

DEC 2 3 2008

Attention: Maureen Miksztal Senior Regulatory Specialist

## Subject: UCARCIDE ™ 14 Microbiocide

EPA Registration No. 464-700 Amendment Dated November 24, 2008

The amendment, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, is acceptable.

Minor Labeling Changes to the Directions For Use

A stamped copy of the "accepted" labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely

indel

Marshall Swindell Product Manager 33 Regulatory Management Branch 1 Antimicrobials Division (7510P)

Enclosure

## PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS DANGER

#### **KEEP OUT OF REACH OF CHILDREN**

Corrosive. Causes irreversible eye damage. Causes skin irritation. Harmful if inhaled. Harmful if swallowed. Harmful if absorbed through skin. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Causes asthmatic signs and symptoms in hyper-reactive individuals.

Do not get in eyes, on skin, on clothing. Avoid breathing vapor. Do not swallow. Wear goggles, protective clothing, and butyl or nitrile gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

#### ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

#### STORAGE AND HANDLING

UCARCIDE 14 Antimicrobial is incompatible with many commonly used materials of construction such as steel, galvanized iron, aluminum, tin, and zinc. UCARCIDE 14 Antimicrobial can be stored aluminum, tin, and zinč. UCARCIDE 14 Antimicrobial can be stored and handled in bakëd phenolic-lined steel, polyethylene, stainless steel, or reinforced epoxy-plastic equipment. This product freezes at about 27° F (-3° C). Therefore, unless the storage tank is inside or underground, heating and insulation may be required. If heating is needed, exposure to high temperatures should be avoided. For short storage times (up to about 1 month), temperatures of up to 100° F (37.8° C) can be tolerated but the preferred maximum storage temperature is about 80° F (26.7° C).

A stainless steel centrifugal pump is suggested for transfer service. Spiral-wound stainless steel with TEFLON® Polymer is suitable for gaskets and packing.

Handle in a well-ventilated area. If vapors are irritating to the nose or eyes, special ventilation or respiratory protection (MSHA/NIOSH approved air purifying respirator equipped with an organic vapor cartridge) may be required.

#### LIMITED WARRANTY AND DISCLAIMER

Seller warrants that the product conforms to its chemical description as contained on this label and is reasonably fit for the purposes stated on this label when used in accordance with directions under normal on this label when used in accordance with directions under normal conditions of use. THE WARRANTIES MADE IN THIS PARAGRAPH ARE SELLER'S SOLE WARRANTIES WITH RESPECT TO THE PRODUCT AND ARE MADE EXPRESSLY IN LIEU OF AND EXCLUDE ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER EXPRESS OR IMPLIED REPRESENTATIONS AND WARRANTIES.

BEFORE HANDLING OR USING THIS PRODUCT. SEE YOUR EMPLOYER AND READ CURRENT MATERIAL SAFETY DATA SHEET.

#### STORAGE AND DISPOSAL

PESTICIDE DISPOSAL: Do not contaminate water, food or feed by **FESTICIDE DISPUSAL:** Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or your Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Metal Containers or Plastic Containers: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or other procedures approved by state and local authorities. Plastic Containers: May be incinerated, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke. Metal Containers: Must not be incinerated. Do not cut or weld on or near metal containers metal containers.



NOTICE Do Not Ship or Store with Food, Feeds, Drugs, or Clothing

65672-04/29/2008

# **UCARCIDE**<sup>™</sup>

X

HIGHLY EFFECTIVE MICROBIOCIDE FOR USE IN CONTROLLING BACTERIA INCLUDING A HIGHLY EFFECTIVE MICROBIOCIDE FOR USE IN CONTROLLING BACTERIA INCLUDING FORMING BACTERIA AND SULFATE-REDUCING BACTERIA AND FUNGI (YEAST AND MOLDS ALGAE IN AIR WASHERS AND INDUSTRIAL SCRUBBING SYSTEMS, RECIRCULATING COOLIN' PROCESS WATER SYSTEMS INCLUDING THOSE THAT CONTAIN REVERSE OSMOSIS MEMBI AND IN SERVICE WATER AND AUXILIARY SYSTEMS AND HEAT TRANSFER SYSTEMS A WASTEWATER SYSTEMS INCLUDING WASTEWATER SLUDGE AND HOLDING TANKS, AND IN I WASTEWATER SYSTEMS INCLUDING WASTEWATER SLUDGE AND HOLDING TANKS, AND IN I MILLS AND PAPER MILL PROCESS WATER SYSTEMS AND WATER BASED COATINGS FOR I AND PAPERBOARD AND IN OIL WELL DRILLING, OIL FIELD PROCESSING APPLICATIONS, OIL WATER SYSTEMS, OIL AND GAS PRODUCTION AND TRANSMISSION PIPELINES AND SYSTEM: GAS STORAGE FIELDS AND EQUIPMENT; SUCH AS, STEAM-INJECTION WATER HOLDING T FLOOD WATER, FRACTURING FLUIDS, INJECTION WATER, HOLDING POND WATER, DISF WELL WATER, WATER HOLDING TANKS, FUEL STORAGE TANKS AND RELATED REFINERY AI FIELD CLOSED, INDUSTRIAL RECIRCULATING WATER HANDLING SYSTEMS AND AN INDUX SANITIZER FOR USE IN CONTROLLING MICROBIAL CONTAMINATION IN ANIMAL PRODL FACILITIES AND FARM EQUIPMENT SUCH AS POULTRY & TURKEY HOUSES, SWINE HOUSIN FARDOWING APEAS BARNS AND LABGE ANIMAL BUILDINGS HATCHERS SETTERS AND FARROWING AREAS, BARNS AND LARGE ANIMAL BUILDINGS, HATCHERS, SETTERS, AND PROCESSING FACILITIES, CAGES AND TRANSPORT VEHICLES, AND HATCHING EGGS AN SANITIZING INDUSTRIAL OR NON-FOOD CONTACT SURFACES SUCH AS EQUIPMENT FOR PACKING, OR PACKAGING PRODUCTS, PRODUCT TRANSFER LINES, STORAGE TANKS, F AND WALLS AND FOR USE BY MANUFACTURERS AND FORMULATORS IN FORMUL PRODUCTS FOR ANIMAL HOUSING AND INDUSTRIAL SANITIZING APPLICATIONS. FORMUL USING THIS PRODUCT ARE RESPONSIBLE FOR THE EPA REGISTRATION OF THEIR FORMUL PRODUCTS.

> Active Ingredient: Glutaraldehyde . . Alkyl (C14 50%, C12 40%, C16 10%) dimethyl benzyl ammonium chloride ..... 2.5%

## **KEEP OUT OF REACH OF CHILDREN** DANGER **FIRST AID**

#### If swallowed:

- Call a poison control center or a doctor immediately for treatment advice.
   DO NOT INDUCE VOMITING.
- Do not give anything to drink.
- If in eyes:
- Wash immediately and continuously with flowing water for at least 30 minutes. Remove contact lenses after the first 5 minutes and continue washing. Obtain promp
- medical consultation, preferably from an ophthalmologist.
- Call a poison control center or a doctor immediately for treatment advice.
- If on skin or clothing:
- Take off contaminated clothing.
  Rinse skin immediately with plenty of water for 15-20 minutes.
  Call a poison control center or a doctor for treatment advice.
- if inhaled:
- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, and then give artificial respiratic preferably mouth-to-mouth if possible.
- Call a poison control center or a doctor for further treatment advice.

NOTE TO PHYSICIAN: Aspiration may cause lung damage. Probable mucosal may contraindicate the use of gastric lavage.

Have the MSDS and, if available, the product container or label with you when c poison control center or a doctor, or going for treatment.

#### SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENT!

١

Produced for:

Dow

EPA Reg. No. 464-700 EPA Est. No. 10352-WV-2 (A) ; 464-1 EPA Est. No. 10352-WV-1 (C) (A) 5 gallon pails in pallets; all drum: (B) Samples and 5 gallon pails less th (C) Bulk Shipments

#### The Dow Chemical Company

Midland, Michigan 48674 U.S.A. (989)636-4400

®TM Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow Made in U.S.A.

CONTAINER SIZE	CONTAINER SIZE	CONTAINER SIZE
TOTE	55 GALLONS	5 GALLONS
260.8 GALLONS		
2,290 POUNDS	470 POUNDS	44 POUNDS
NET WEIGHT	NET WEIGHT	NET WEIGHT

IN CASE OF AN EMERGENCY endangering life or property involving this product, collect, (989)636-4400.

### MENTS ESTIC ANIMALS

#### CHILDREN

Causes skin irritation. ful if absorbed through tact may cause allergic ic signs and symptoms

nitrile gloves. fling. a reuse

effluent containing this oceans or other waters of a National Pollutant mit and the permitting to discharge. Do not sewer systems without nt plant authority. For Regional Office of the

#### )LING

e with many commonly teel, galvanized iron, nicrobial can be stored ethylene, stainless steel, product freezes at about rage tank is inside or required. If heating is d be avoided. For short ratures of up to 100° F red maximum storage

ted for transfer service. Polymer is suitable for

 irritating to the nose or tection (MSHA/NIOSH with an organic vapor

#### AIMER

ts chemical description for the purposes stated lirections under normal ES MADE IN THIS VARRANTIES WITH VADE EXPRESSLY IN D WARRANTIES OF FOR A PARTICULAR LESS OR IMPLIED

#### THIS PRODUCT. READ CURRENT Τ.

#### POSAL

e water, food or feed by pited. Pesticide wastes ticide, spray mixture or ese wastes cannot be ions, contact your State ency, or the Hazardous onal Office for guidance.

tainers or Plastic en offer for recycling or sanitary landfill, or other Il authorities. Plastic wed by state and local out of smoke. Metal ot cut or weld on or near

ire with Food, Clothing

# **UCARCIDE**<sup>™</sup>

# Antimicrobial

A HIGHLY EFFECTIVE MICROBIOCIDE FOR USE IN CONTROLLING BACTERIA INCLUDING SLIME FORMING BACTERIA AND SULFATE-REDUCING BACTERIA AND FUNGI (YEAST AND MOLDS) AND ALGAE IN AIR WASHERS AND INDUSTRIAL SCRUBBING SYSTEMS, RECIRCULATING COOLING AND PROCESS WATER SYSTEMS INCLUDING THOSE THAT CONTAIN REVERSE OSMOSIS MEMBRANES AND IN SERVICE WATER AND AUXILIARY SYSTEMS AND HEAT TRANSFER SYSTEMS AND IN WASTEWATER SYSTEMS INCLUDING WASTEWATER SLUDGE AND HOLDING TANKS, AND IN PAPER MILLS AND PAPER MILL PROCESS WATER SYSTEMS AND WATER BASED COATINGS FOR PAPER AND PAPER MILL PROCESS WATER STSTEMS AND WATER BASED COATINGS FOR PAPER AND PAPERBOARD AND IN OIL WELL DRILLING, OIL FIELD PROCESSING APPLICATIONS, OIL FIELD WATER SYSTEMS, OIL AND GAS PRODUCTION AND TRANSMISSION PIPELINES AND SYSTEMS, AND GAS STORAGE FIELDS AND EQUIPMENT; SUCH AS, STEAM-INJECTION WATER HOLDING TANKS, FLOOD WATER, FRACTURING FLUIDS, INJECTION WATER, HOLDING POND WATER, DISPOSAL-WELL WATER, WATER HOLDING TANKS, FUEL STORAGE TANKS AND RELATED REFINERY AND OIL FIELD CLOSED, INDUSTRIAL RECIRCULATING WATER HANDLING SYSTEMS AND AN INDUSTRIAL SANITIZER FOR USE IN CONTROLLING MICROBIAL CONTAMINATION IN ANIMAL PRODUCTION FACILITIES AND FARM EQUIPMENT SUCH AS POULTRY & TURKEY HOUSES, SWINE HOUSING AND FARROWING AREAS, BARNS AND LARGE ANIMAL BUILDINGS, HATCHERS, SETTERS, AND CHICK PROCESSING FACILITIES, CAGES AND TRANSPORT VEHICLES, AND HATCHING EGGS AND FOR SANITIZING INDUSTRIAL OR NON-FOOD CONTACT SURFACES SUCH AS EQUIPMENT FOR MIXING, PACKING, OR PACKAGING PRODUCTS, PRODUCT TRANSFER LINES, STORAGE TANKS, FLOORS AND WALLS AND FOR USE BY MANUFACTURERS AND FORMULATORS IN FORMULATING PRODUCTS FOR ANIMAL HOUSING AND INDUSTRIAL SANITIZING APPLICATIONS. FORMULATORS USING THIS PRODUCT ARE RESPONSIBLE FOR THE EPA REGISTRATION OF THEIR FORMULATING

PRODUCTS. Active Ingredient: Glutaraldehyde ..... Alkyl (C14 50%, C12 40%, C16 10%) dimethyl benzyl ammonium chloride ..... 2.5% Inert Ingredients: ..... **KEEP OUT OF REACH OF CHILDREN** DANGER **FIRST AID** if swallowed: Call a poison control center or a doctor immediately for treatment advice.
 DO NOT INDUCE VOMITING. Do not give anything to drink. If in eyes: Wash immediately and continuously with flowing water for at least 30 minutes.
 Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an ophthalmologist. Call a poison control center or a doctor immediately for treatment advice. If on skin or clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes.
 Call a poison control center or a doctor for treatment advice. If inhaled: Move person to fresh air. · If person is not breathing, call 911 or an ambulance, and then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison control center or a doctor for further treatment advice. NOTE TO PHYSICIAN: Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of gastric lavage. Have the MSDS and, if available, the product container or label with you when calling a poison control center or a doctor, or going for treatment. SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS EPA Reg. No. 464-700 Produced for: EPA Est. No. 10352-WV-2 (A) ; 464-WV-1 (B) EPA Est. No. 10352-WV-1 (C) Dow (A) 5 gallon pails in pallets; all drums; bulk (B) Samples and 5 gallon pails less than pallet The Dow Chemical Company (C) Bulk Shipments (K:04/Q8) o P[20408 2 C C C C C C C C C C C C C C C Midland, Michigan 48674 U.S.A. (989)636-4400 ®TM Trademark of The Dow Chemical Company Ċ ("Dow") or an affiliated company of Dow Made in U.S.A. сc Net Contents: 5, 55 gallons or Bulk CONTAINER SIZE CONTAINER SIZE CONTAINER SIZE ¢ 000 000 န်ဍ ဗီဗီဗီကို စိုးရင် c c TOTE 55 GALLONS с ίcίc

#### с ç cc с 2,290 POUNDS 470 POUNDS 44 POUNDS ¢ NET WEIGHT NET WEIGHT NET WEIGHT

c ¢

IN CASE OF AN EMERGENCY endangering life or property involving this product, call collect, (989)636-4400.

260.8 GALLONS

#### DIRECTIONS FOR U

It is a violation of Federal Law to use this product in a manner inconsister AIR WASHERS AND INDUSTRIAL SCRUBBING SYS COOLING AND PROCESS WATER §

This product may be used only in industrial air washers and air washer components.

UCARCIDE 14 Antimicrobial should be added at the application rates system at a convenient point of uniform mixing such as the basin area (SLUG DOSE) or continuously. Badly fouled systems can be shock tree Under these conditions, blowdown should be discontinued for up to 24 hou UCARCIDE 14 Antimicrobial can be used in industrial process water sy and non-medical reverse osmosis membranes (where approved manufacturer) and associated distribution systems.

INTERMITTENT (SLUG DOSE) METHOD

Initial Dose: When the system is noticeably fouled, apply 4.2 to Antimicrobial per 100 gallons of water in the system. Repeat until control Subsequent Dose: When microbial control is evident, add 1.7 to Antimicrobial per 100 gallons of water in the system weekly, or as needed

Badly fouled systems must be cleaned before treatment is begun. CONTINUOUS FEED METHOD

Initial Dose: When the system is noticeably fouled, apply 4.2 to Antimicrobial per 100 gallons of water in the system.

Subsequent Dose: Maintain this treatment level by starting a continu UCARCIDE 14 Antimicrobial per 100 gallons of water in the system per c Badly fouled systems must be cleaned before treatment is begun:

#### SERVICE WATER AND AUXILIARY

UCARCIDE 14 Antimicrobial should be used at the same applicatio described above. It should be added to the system at a point that will a system.

#### HEAT TRANSFER SYSTEM

(Evaporative Condensers, Dairy Sweetwater Systems, Hydro Retorts, and Pasteurizers and Warmers)

UCARCIDE 14 Antimicrobial should be used at the same applicatic described above. It should be added to the system at a point of unitor area or other reservoir or collecting area from which the treated water will system.

#### INDUSTRIAL WASTEWATER SY

(Wastewater Systems, Wastewater Sludge and Wa

UCARCIDE 14 Antimicrobial should be added to a wastewater syste uniform mixing such as the digester. Add 20 to 96 fluid ounces (1.25 p UCARCIDE 14 Antimicrobial per 1000 gallons of wastewater or studge.

#### PAPER MILLS AND PAPER MILL PROCESS

UCARCIDE 14 Antimicrobial should be added to a paper making syste the thin or thick stock chest, save-all tank, process tank or white-water

Initial Treatment: When the system is noticeably contaminated, Antimicrobial per ton or 0.76 to 4.5 Kg of UCARCIDE 14 Antimicrobia basis) as a continuous or slug dose. Repeat until control is achieved. Hout prior to initial treatment.

Subsequent Dose: When microbial control is evident, add 0.9 to 6.0 lb or 0.46 to 3.0 kg of UCARCIDE 14 Antimicrobial per metric ton of pul maintain control.

## WATER BASED COATINGS, PIGMENT: SLURRIES FOR PAPER AND PAPI

NOTE: For use in non-food contact coatings only.

Add 0.3 to 1.8 lbs of UCARCIDE 14 Antimicrobial per 1,000 lbs dry r Antimicrobial per metric ton of dry slurry to produce a concentration of slurry solids) in the mixed slurry.

#### WATER FLOODS

UCARCIDE 14 Antimicrobial should be added to a water flood system a Initial Treatment: When the system is noticeably contaminated, ac Antimicrobial to the system (0.3 to14.5 gallons UCARCIDE 14 Antim Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 60 to 15 (0.06 to 14.5 gallons UCARCIDE 14 Antimicrobial per 1,000 gallons fl needed to maintain control.

#### FRAC FLUIDS

UCARCIDE 14 Antimicrobial reduces bacterial contamination and de used in oil and gas well stimulations. Add UCARCIDE 14 Antimicrol directly into the well head injection pipeline as the water is being pum Dose Range: UCARCIDE 14 Antimicrobial should be added at a ra

#### gallons per 10,000 gallons) depending on the degree of bacterial foul DRILLING, COMPLETION, AND WORK

UCARCIDE 14 Antimicrobial should be added to a drilling fluid system circulating mud tank.

Initial Treatment: Add 150 to 3,000 ppm UCARCIDE 14 Antimicrot Antimicrobial per 100 barrels of fluid) to a freshly prepared fluid dependir Maintenance Dosage: Maintain a concentration of 150 to 3,000 ppm 0.6 to 12.2 gallons of UCARCIDE 14 Antimicrobial per 100 barrels of add the severity of contamination.

#### PACKER FLUIDS

UCARCIDE 14 Antimicrobial should be added to a packer fluid at a poir holding tank. Add 150 to 1,800 ppm UCARCIDE 14 Antimicrobia Antimicrobial per 100 barrels of fluid) to a freshly prepared fluid dependi the treated packer fluid in the wall between the casing and production it.

## c OIL AND GAS PRODUCTION AND TRANSMISSIO

UCARCIDE 14 Antimicrobial should be added to an oil/gas prod cinjection. The application should be added to an oligas prod cinjection. The application should be conducted to ensure max cAntimicrophal throughout the entire internal pipeline surface by adc detect/creasure a residual concentration at the back end of the pipel treatment will be a reduction in bacterial counts and/or reduced con may be desirable to dilute the UCARCIDE 14 Antimicrobial with an a use. The concentration in the solvent should not fall below an activ ppm based on the volume of water in the pipeline. Injections to needed to maintain control.

0

#### DIRECTIONS FOR USE

#### plation of Federal Law to use this product in a manner inconsistent with its labeling. IR WASHERS AND INDUSTRIAL SCRUBBING SYSTEMS/ RECIRCULATING COOLING AND PROCESS WATER SYSTEMS

sduct may be used only in industrial air washers and air washer systems which have mist-eliminating

IDE 14 Antimicrobial should be added at the application rates described below to a water treatment at a convenient point of uniform mixing such as the basin area. Addition may be made intermittently DOSE) or continuously. Badly fouled systems can be shock treated with UCARCIDE 14 Antimicrobial. nese conditions, blowdown should be discontinued for up to 24 hours.

IDE 14 Antimicrobial can be used in industrial process water systems that contain ultra filtration units n-medical reverse osmosis membranes (where approved for compatibility by the membrane cturer) and associated distribution systems.

#### MITTENT (SLUG DOSE) METHOD

Dose: When the system is noticeably fouled, apply 4.2 to 8.5 fluid ounces of UCARCIDE 14 obial per 100 gallons of water in the system. Repeat until control is achieved.

quent Dose: When microbial control is evident, add 1.7 to 4.2 fluid ounces of UCARCIDE 14 obial per 100 gallons of water in the system weekly, or as needed to maintain control.

uled systems must be cleaned before treatment is begun.

NUOUS FEED METHOD

Dose: When the system is noticeably fouled, apply 4.2 to 8.5 fluid ounces of UCARCIDE 14 obial per 100 gallons of water in the system.

uent Dose: Maintain this treatment level by starting a continuous feed of 0.8 to 4.2 fluid ounces of IDE 14 Antimicrobial per 100 gallons of water in the system per day.

uled systems must be cleaned before treatment is begun:

SERVICE WATER AND AUXILIARY SYSTEMS IDE 14 Antimicrobial should be used at the same application rates, and in the same manner as ad above. It should be added to the system at a point that will allow for uniform mixing throughout the

#### HEAT TRANSFER SYSTEMS

(Evaporative Condensers, Dairy Sweetwater Systems, Hydrostatic Sterilizers and Retorts, and Pasteurizers and Warmers )

IDE 14 Antimicrobial should be used at the same application rates, and in the same manner as ad above. It should be added to the system at a point of uniform mixing such as a basin area, sump other reservoir or collecting area from which the treated water will be circulated uniformly throughout the

#### INDUSTRIAL WASTEWATER SYSTEMS

(Wastewater Systems, Wastewater Sludge and Wastewater Holding Tanks)

IDE 14 Antimicrobial should be added to a wastewater system or sludge at a convenient point of mixing such as the digester. Add 20 to 96 fluid ounces (1.25 pints to 3 quarts) (1,600 to 7,600 ppm) IDE 14 Antimicrobial per 1000 gallons of wastewater or sludge.

#### PAPER MILLS AND PAPER MILL PROCESS WATER SYSTEMS

IDE 14 Antimicrobial should be added to a paper making system at a point of uniform mixing such as or thick stock chest, save-all tank, process tank or white water tank.

Treatment: When the system is noticeably contaminated, add 1.5 to 9.0 lb of UCARCIDE 14 robial per ton or 0.76 to 4.5 Kg of UCARCIDE 14 Antimicrobial per metric ton of pulp or paper (dry is a continuous or slug dose. Repeat until control is achieved. Heavily fouled systems should be boiled r to initial treatment

tuent Dose: When microbial control is evident, add 0.9 to 6.0 lb of UCARCIDE 14 Antimicrobial per ton to 3.0 kg of UCARCIDE 14 Antimicrobial per metric ton of pulp or paper (dry basis) as necessary to 1 control.

## WATER BASED COATINGS, PIGMENTS AND FILLER. SLURRIES FOR PAPER AND PAPERBOARD

For use in non-food contact coatings only

3 to 1.8 lbs of UCARCIDE 14 Antimicrobial per 1,000 lbs dry powder or 0.3 to 1.8 Kg UCARCIDE 14 robial per metric ton of dry slurry to produce a concentration of 300 to 1800 ppm as product (based on olids) in the mixed slurry

#### WATER FLOODS

XDE 14 Antimicrobial should be added to a water flood system at a point of uniform mixing. Treatment: When the system is noticeably contaminated, add 300 to 15,000 ppm UCARCIDE 14 robial to the system (0.3 to 14.5 gallons UCARCIDE 14 Ant/microbial per 1,000 gallons flood water). until control is achieved.

quent Dose: When microbial control is evident, add 60 to 15,000 ppm UCARCIDE 14 Antimicrobial 14.5 gallons UCARCIDE 14 Antimicrobial per 1,000 gallons flood water) to the system weekly, or as to maintain control.

#### FRAC FLUIDS

CIDE 14 Antimicrobial reduces bacterial contamination and degradation of fracturing fluids and gets oil and gas well stimulations. Add UCARCIDE 14 Antimicrobial to the frac water storage tanks or into the well head injection pipeline as the water is being pumped down-hole.

Range: UCARCIDE 14 Antimicrobial should be added at a rate of 360 to 17,900 ppm (3.5 - 172.5 per 10,000 gallons) depending on the degree of bacterial fouling in the source water.

#### DRILLING, COMPLETION, AND WORKOVER FLUIDS

IDE 14 Antimicrobial should be added to a drilling fluid system at a point of uniform mixing such as the ng mud tank.

Treatment: Add 150 to 3,000 ppm UCARCIDE 14 Antimicrobial (0.6 to 12.2 gallons UCARCIDE 14 robial per 100 barrels of fluid) to a freshly prepared fluid depending on the severity of contamination.

nance Dosage: Maintain a concentration of 150 to 3,000 ppm UCARCIDE 14 Antimicrobial by adding 2.2 gallons of UCARCIDE 14 Antimicrobial per 100 barrels of additional fluid, or as needed, depending on arity of contamination.

#### PACKER FLUIDS

2IDE 14 Antimicrobial should be added to a packer fluid at a point of uniform mixing such as a circulating 1 tank. Add 150 to 1,800 ppm UCARCIDE 14 Antimicrobial (0.6 to 7.3 gallons UCARCIDE 14 robial per 100 barrels of fluid) to a freshly prepared fluid depending on the sevenity of contamination. Seal ited packer fluid in the wall between the casing and production tube.

#### 21 AND GAS PRODUCTION AND TRANSMISSION PIPELINES AND SYSTEMS

C DiDE 14 Antimicrobial should be added to an oil/gas production or transmission line via direct The application should be conducted to ensure maximum distribution of UCARCIDE 14 trobial throughout the entire internal pipeline surface by adding a sufficient amount of biocide to Deasure a residual concentration at the back end of the pipeline system. Criteria for success of the ant will be a reduction in bacterial counts and/or reduced corrosion rates. To facilitate application, it edistrable to dilute the UCARCIDE 14 Antimicrobial with an appropriate solvent immediately before he concentration in the solvent should not fall below an active concentration range of 500 to 5000 ased on the volume of water in the pipeline. Injections to the system should be weekly, or as 1 to maintain control.

GAS STORAGE W AND SYSTEMS Individual injection wells should be treated with a sufficient quantity of UCARCIDE 14 Antimicrobial to produce a concentration of 1,500 to 15,000 ppm UCARCIDE 14 Antimicrobial when diluted by the water present in the formation. Injection should take place before gas is injected (during the summer). Injections should be repeated yearly, or as needed to maintain control. yearly, or as needed to maintain control.

Individual drips should be treated with a sufficient quantity of UCARCIDE 14 Antimicrobial to produce a concentration of 600 to 6,000 ppm UCARCIDE 14 Antimicrobial when diluted by the water present in the drip. Injections should be repeated yearly, or as needed to maintain control.

#### HYDROTESTING

Water used to hydrotest pipelines or vessels should contain 300 to 12,000 ppm UCARCIDE 14 Antimicrobial (0.3 to 11.6 gallons UCARCIDE 14 Antimicrobial per 1,000 gallons water), depending on water quality and length of time the equipment will remain idle.

#### PIPELINE PIGGING AND SCRAPING OPERATIONS

Add UCARCIDE 14 Antimicrobial to a slug of water immediately following the scraper (ideally this water volume can be kept to a minimum and contained between the scraper and a trailing pig). Sufficient UCARCIDE 14 Antimicrobial should be added to produce a concentration of 0.3 to 3.0% (0.3 to 2.9 gallons UCARCIDE 14 Antimicrobial per 100 gallons water), depending on the length of the pipeline and the severity of biofouling.

#### SANITIZING NON-FOOD CONTACT SURFACES, FARM, ANIMAL, AND POULTRY HOUSING FACILITIES AND EQUIPMENT

#### Not for use in the state of California

DO NOT USE THIS PRODUCT ON FOOD OR FEED

UCARCIDE 14 Antimicrobial is suitable for use on a wide variety of surfaces including stainless steel, aluminum, painted concrete, plastic, glazed tile.

Product Dilution: To sanitize vegetative pathogens (including Klebsiella pneumoniae, Salmonella cholerasuis, Staphylococcus aureus, and Pseudomonas aeruginosa) and viruses (including infectious bursal disease, Avian influenza (H6N2 and H5N1), SARS Associated Coronavirus, Porcine circovirus and fungus (including Aspergillus fumigatus):

1. Remove filth and soil deposits from surfaces prior to treatment. Pre-clean surfaces with a suitable detergent and rinse with water.

- 2. Thoroughly saturate all surfaces using a mop or by spraving with a solution prepared by mixing 0.45 to 1.8 fluid ounces of UCARCIDE 14 Antimicrobial per gallon of water (3.5 to 14.1 milliliters per liter) to produce a solution containing 0.06% to 0.24% active ingredient. For application against Porcine circovirus mix 0.9 to 2.2 fluid ounces of UCARCIDE 14 Antimicrobial per gallon of water (6.9 to 17.3 milliters per liter) to produce a solution containing 0.1 to 0.25% active glutaraldehyde ingredient.
- 3. Immerse all halters, ropes, and other types of equipment used in handling and restraining animals,
- as well as forks, shovels, and scraper used for removing litter and manure.
- Allow to stand for at least 5 minutes, or until thoroughly dried.
- 5. Ventilate thoroughly before reuse.

#### 6. Fresh solution should be prepared daily or more often if the solution becomes diluted or soiled.

Farm Equipment and Animal Housing Buildings

(poultry & turkey grow-out houses, laying houses, swine production and housing, barns and large animal buildings) Before applying UCARCIDE 14 Antimicrobial:

- 1. Remove all poultry and other animals and feed from the premises. Remove all portable equipment and empty all feeders and water troughs. If not removed, all treated feeders and waterers must be thoroughly rinsed with potable water prior to re-use.
- 2. Remove all litter and manure from floors and other surfaces. If litter is not removed, allow to stand after treatment with UCARCIDE 14 Antimicrobial for at least ten minutes before repopulation.
- 3. Using suitable commercially available equipment, saturate all surfaces with diluted UCARCIDE 14 Antimicrobial (see Product Dilution, above).
- 4. Allow to stand for at least 5 minutes, or for longer depending on the organisms being treated (see Product Dilution, above).
- 5. Ventilate enclosed spaces.
- 6. Do not repopulate with poultry or other animals, or use equipment until treatment has been absorbed or dried. Hatchers, Setters, and Chick Processing Facilities
- 1. General sanitizing of environmental surfaces prior to introduction of eggs: Remove all animals from the area. Clean out feathers, fluff, or other debris. Thoroughly saturate all surfaces with a solution prepared by mixing the appropriate amount (see Product Dilution, above) of UCARCIDE 14 Antimicrobial with water. Allow to stand for at least 5 minutes, or for longer depending on the organisms being treated. (See Product Dilution, above.) Ventilate thoroughly before reuse.
- 2. Treatment of air and surfaces after introduction of eggs in high humidity hatchers and setters with water spray cooling: Prepare a solution by mixing the appropriate amount of UCARCIDE 14 Antimicrobial with water. Allow to stand for at least 5 minutes, or for longer depending on the organisms being treated. (See Product Dilution, above.) Fog or atomize this solution into setters or hatchers, using appropriate application . equipment.

Treatment of air and surfaces after introduction of eggs in low humidity hatchers with chilled coil cooling: Fog or atomize this product using appropriate application equipment.

#### Trays, Racks, Carts, Chick Boxes, Cages, and other Hard Surfaces:

Remove all fith and heavy debris from surfaces by scraping or washing. Prepare a solution by mixing the appropriate amount (see Product Dilution, above) of UCARCIDE 14 Antimicrobial with water. Apply by spraying or immension, and allow to drain and air dry. Allow to stand for at least 5 minutes, or for longer depending on the organisms being treated. (See Product Dilution, above.)

#### Trucks and other Vehicles

Remove all filth and heavy debris from surfaces by scraping or washing. Spray surfaces with a solution prepared by mixing the appropriate amount (see Product Dilution, above) of UCARCIDE 14 Antimicrobial with water. Allow to stand for at least 5 minutes, or for longer depending on the organisms being treated.

#### Egg Sanitization

(for treating hatching eggs only)

Prepare a solution by mixing one fluid ounce of UCARCIDE 14 Antimicrobial with one gallon of water. Place in a bath at 105° to 115°F (40° to 45°C). Place freshly laid eggs in plastic trays and dip briefly (10 to 15 seconds), then allow to drain and air-dry.

#### SANITIZING NON-FOOD CONTACT SURFACES, INDUSTRIAL EQUIPMENT AND BUILDINGS

"Not for use in the state of California

Before applying UCARCIDE 14 Antimicrobial, remay friaty friaty friends and the provide the state of the state

DEC 2 3 2008

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 464-700