## GENERAL USF PRECAULTO IS

MAKE ONLY ONE APPLICATION PER CROP.

AFTER TREATMENT WITH SUTAM-ATRAZINE 36-12-WP DO NOT PLANT ANY CROP EXCEPT CORN UNTIL THE FOLLOWING YEAR OR INJURY MAY OCCUR.

FOLLOWING HARVEST OF THE TREATED CROP, THE SOIL SHOULD BE PLOWED AND THOROUGHLY TILLED IN THE FALL OR SPRING TO MINIMIZE POSSIBLE INJURY TO ROTATIONAL SPRING-SEEDED CROPS.

DO NOT USE ON MILO OR SORGHUM. DO NOT USE ON CORN SEED STOCK.

THIS PRODUCT IS RECOMMENDED FOR USE ON MINERAL SOILS ONLY.

APPLIED ACCORDING TO DIRECTIONS AND UNDER NORMAL GROWING CONDITIONS, THE COMBINATION WILL NOT HARM THE TREATED CROP. DURING GERMINATION AND EARLY STAGES OF GROWTH, EXTENDED PERIODS OF UNUSUALLY COLD AND WET OR HOT AND DRY WEATHER, INSECT OR PLANT DISEASE ATTACK THE USE OF CERTAIN SOIL-APPLIED SYSTEMIC INSECTICIDES, IMPROPERLY PLACED FERTILIZERS OR SOIL INSECTICIDES, MAY CREATE ABNORMAL CONDITIONS THAT WEAKEN CROP SEEDLINGS. THE COMBINATION USED UNDER THESE ABNORMAL CONDITIONS COULD RESULT IN CROP INJURY.

CARE SHOULD BE TAKEN TO AVOID USE WHERE ADJACENT DESIRABLE TREES, SHRUBS, OR PLANTS MAY BE INJURED AS A RESULT OF THE ATRAZINE LEACHING THROUGH THE SOIL.

DO NOT STORE NEAR SEEDS OR FERTILIZERS.

DO NOT CONTAMINATE IRRIGATION WATER OR WATER USED FOR DOMESTIC PURPOSES.

KEEP CONTAINER CLOSED WHEN NOT IN USE.

DO NOT TANK MIX SUTAN-ATRAZINE 36-12-WP WITH INSECTICIDES OR FUNGICIDES.

## DIRECTIONS FOR USE

## SPRAY EQUIPMENT AND APPLICATION DIRECTIONS

FOR UNIFORM DISTRIBUTION TEEJET 8003 OR 8004 FAN-TYPE OR SIMILAR NOZZLES WITH OPENINGS OF EQUAL OR GREATER SIZE SHOULD BE USED. SCREENS IN NOZZLES AS WELL AS THOSE IN SUCTION AND IN-LINE STRAINERS SHOULD BE NO FINER THAN 50 MESH SIZE. A SUITABLE PUMP TO DELIVER 10 TO 12 GPM SHOULD BE USED AND OPERATING PRESSURE SHOULD BE 35 TO 40 PSI. PRE-MIX THE PRODUCT OR ADD TO THE SPRAY TANK DURING FILLING. THE SPRAYING EQUIPMENT SHOULD BE PROPERLY CALIBRATED TO DELIVER THE DESIRED RATE IN 10 TO 50 GALLONS OF WATER FER ACRE. SUFFICIENT AGITATION SHOULD BE MAINTAINED TO KEEP THE PRODUCT IN SUSTEMSION. CHECK FREQUENTLY DURING APPLICATION TO BE SURE NOZZLES ARE FREE FROM CLOSGING AND ARE DELIVERING A UNIFORM SPRAY PATTERN. WASH SPRAYER THOROUGHLY AFTER USE WITH CLEAN WATER.

476-2024

BEST DOCUMENT AVAILABLE