

NEW

CLEAR No. 20
5 U. S. GALLONS

QUICK DRYING
formula!

plus new insecticide
added for broader
protection

CUPRINOL[®]

BRAND

It's Triple Acting

ACCEPTED
578-6
1-15-59
UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTERED
UNDER NO. 1798 SUBJECT
SEE ATTACHED COMMENTS

For
Better Looks
For
Better Service
For
Longer Life

PRIMER
CONTROLS GRAIN RAISING • CHECKING

WATER REPELLENT
PREVENTS WARPING • SWELLING

WOOD PRESERVATIVE
PREVENTS ROT • WOOD BORERS*
*See side panel for details.

| | |
|--|--------|
| ACTIVE INGREDIENTS | |
| ZINC NAPHTHENATE | 24.00% |
| EQUIV. TO METALLIC ZINC 2% (TO PRESERVE WOOD) | |
| DIELDRIN* | .50% |
| INERT INGREDIENTS | 75.50% |
| TOTAL 100.00% | |
| *0.43% HEXACHLOROEPOXYOCTAHYDRO-ENDO, EXO-DIMETHANONAPHTHALENE AND 0.07% RELATED COMPOUNDS | |

← Longer protection from this stronger formula

CHEMICAL PRODUCTS DIVISION, DARWORTH INC., SIMSBURY, CONNECTICUT

CUPRINOL
BRAND

CLEAR No. 20
WOOD PRESERVATIVE

CUPRINOL prevents seasoned wood from swelling, shrinking and warping and also controls grain raising and checking.

CUPRINOL prolongs the life of wood by preventing rot, and damage from termites — also teredo and gribble. It retards as well fouling by barnacles and growth of marine vegetation.

This grade is for use under paint or stains or where surfaces are to be left a natural wood finish.

Treated wood after drying twenty-four hours is non-toxic to plant life. Avoid handling treated wood until thoroughly dry.

Avoid prolonged or repeated inhalation of mist or contact with skin. Avoid contamination of food or food-stuffs. Wash with soap and water after handling before eating or smoking. In case of contact with skin or eyes, flush with plenty of water. For eyes, get medical attention. Keep out of reach of children.

COVERAGE

One gallon will cover 250 to 600 square feet (not board feet) depending on the porosity of wood and roughness of surfaces.

CAUTION
COMBUSTIBLE MIXTURE
C. of A. No. 1798
DIRECTIONS FOR USE

The solvent used in CUPRINOL has a flash point of 105°F. Do not use near any burning or glowing materials, heaters or sparks. Use in a well ventilated place.

Note — CUPRINOL does not increase the flammability of wood when the solvent entirely evaporates after treatment.

Continued on other side

CHEMICAL PRODUCTS DIVISION
DARWORTH INC.
SIMSBURY, CONNECTICUT

578-6

1-15-1959

1/2

1958

CUPRINOL BRAND

CLEAR No. 20 WOOD PRESERVATIVE

Continued from other side

Under copper bottom paint use CUPRINOL Green No. 10. DO NOT USE THIS GRADE.

There are other types of CUPRINOL for fabric, rope and nets.

For information ask your dealer or write the company.

Content of the container is ready for use after mixing.

Apply by brushing, spraying or dipping. No protective clothing is required unless the user is allergic to petroleum distillates. When spraying under prolonged commercial conditions, user should wear a mask or respirator of a type approved by the U. S. Department of Agriculture for dieldrin protection.

Paint, varnish, wax or other films and all layers of bark must be removed before applying CUPRINOL. Moisture in wood reduces penetration; therefore, the drier the wood the more effective the treatment.

Use shellac over CUPRINOL to prevent knots bleeding through paint.

All newly exposed surfaces resulting from cutting, sanding or boring of treated wood should be treated with CUPRINOL. Do not use more than one coat under finishes. If severe rot or insect exposure is to be expected apply one generous coat. It may replace the priming coat if three coats of paint are planned. When CUPRINOL is used without the application of finish coats it will protect the wood but the normal change in color due to weathering may be expected, and temporary graying may occur after rain.

Allow a minimum of twenty-four hours drying time and do not finish before treating solution is completely dry in the wood.

Keep container tightly closed to stop evaporation.

Clean CUPRINOL from hands, brushes, containers or other surfaces with kerosene or white gasoline.

**CHEMICAL PRODUCTS DIVISION
DARWORTH INC.
SIMSBURY, CONNECTICUT**

2/2