

518-6

5-24-1971

1/2

Front

Clear N<sup>o</sup> 20



WOOD

PRESERVATIVE



**ACCEPTED**

**MAY 24 1971**

UNDER THE FEDERAL INSECTICIDE  
FUNGICIDE AND RODENTICIDE ACT  
FOR ECONOMIC POISON REGISTERED  
UNDER NO. 518-6. SUBJECT  
TO ATTACHED COMMENTS.

**ACTIVE INGREDIENTS:**

Zinc Naphthenate ... 13.50%  
(equivalent to  
metallic zinc 2%)

**INERT INGREDIENTS .... 86.50%**

**Total 100.00%**

**WARNING: KEEP OUT OF REACH OF CHILDREN.**  
**READ CAUTION ON BACK USDA Reg. No. 518-**

**32 FL. OZ. (1 QT)**


Side 1

**WATER REPELLENT • QUICK DRYING**

Side 2

**STOPS ROT • REDUCES PAINT PEELING**

Back



WOOD

PRESERVATIVE

**FOR EXTERIOR WOOD BEFORE PAINTING AND FOR UNFINISHED WOOD EXPOSED  
TO THE WEATHER. CONTAINS FUNGICIDE AND WATER REPELLENTS TO PREVENT  
ROT, WARPING AND SWELLING.**

**NOT A VARNISH, STAIN OR SEALER.**



Greatly extends the life and beauty of paint by protecting against blistering, cracking and peeling caused by rain and dew. Keeps painted and unpainted surfaces free from unsightly mildew. Adds years to the performance and life of lumber and wood products used in residences and vacation homes.

- |        |             |               |          |         |
|--------|-------------|---------------|----------|---------|
| siding | doors       | window frames | millwork | fascia  |
| sills  | door frames | window sash   | moldings | fencing |

Conforms to Los Angeles Rule 66.

Fence posts, boat hulls and other wood in contact with soil or water require the extra-strength protection of CUPRINOL Green No. 10.

For rich, lasting colors as well as protection against rot and decay, use CUPRINOL Preservative Stains.

**CAUTION: COMBUSTIBLE MIXTURE**

N.Y.F.D. Certificate of Approval No. 3799

Use in a well-ventilated place. Avoid fire, flame, sparks, or heaters.

**DIRECTIONS**

Wood must be dry and free of bark or any finish. (Do not use steel wool.) Apply by brush, roller, spray or dip. Thoroughly cover cut ends and joints. Use one generous application before painting. Allow 24 hours or more before painting to avoid excessive drying time. If no finish is to be used, apply a second coat within one hour of the first, or dip for 3 minutes.

In some unpainted woods, weathering may cause natural extractives to produce uneven shadings. To remove extractives, wash with detergent/oxalic acid solution, let dry and re-apply CUPRINOL.

Clean CUPRINOL from hands, brushes, etc., with mineral spirits, paint thinner or turpentine.

**COVERAGE:** 400 sq.ft. per gallon average, depending on wood porosity and surface roughness.

**CAUTION:** Contains petroleum distillates. Harmful if swallowed. If swallowed, do not induce vomiting. Call physician immediately. Avoid breathing vapor or spray mist. Avoid contact with skin or eyes. Wash with soap and water after handling. Keep out of reach of children.

BY THE MAKERS OF:

POLYSEAMSEAL® Adhesive Caulk  
DARWORTH LATEX CAULK



TM-4® Washaway Paint Remover  
DARWORTH PANEL ADHESIVE