



CUPRINOL[®]

ACCEPTED
DECEMBER 14, 1972
UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTER-
ED UNDER NO. 518-47

STAIN & WOOD PRESERVATIVE



This can contains:
Seashell
#90
EPA Reg No 518-47



Keeps water out
Keeps beauty in
Protects against
mildew and rot



WARNING
KEEP OUT OF REACH
OF CHILDREN
READ CAUTIONS AND
WARNINGS ON BACK

1 GALLON

ACTIVE INGREDIENT
Bis(Trin-butyltin) oxide 0.3%
INERT INGREDIENTS 99.7%
Total 100.0%

Customer	Design	Date
Eng.	C.F.	11-16-71
READ BEFORE ORDERING: Customer agrees that (1) Continental Can Company, Inc. shall not be liable for (a) any error in the attached unless this proof is returned to Continental with such error plainly noted in writing, (b) the failure of any part of the attached to comply with any local, state or Federal law or regulation, (c) any part of the attached which infringes the property rights of others acquired, without limitation thereof, by usage, registration, copyright, letters patent or otherwise and (d) production colors not being exactly the same as the hand proved colors, if any, in the attached, although Continental will duplicate the colors as closely as possible, (2) Customer shall indemnify and hold Continental harmless against the liability described in (1) above, including attorney fees and court costs or for consequential damages, and (3) the liability of Continental for uncorrected errors plainly noted in the attached shall not exceed the actual cost of the containers bearing the noted error. CHANGES INCREASE COSTS AND DELAY PRODUCTION.		
Change as Detailed ☐	Approved as Submitted ☐	Customer Signature
		Date

Same for All STAINS



CUPRINOL

STAIN & WOOD PRESERVATIVE



Wood dipped in Cuprinol resists rot. Protects against mildew discoloration. Exceeds water repellency requirements of Federal Spec. TT-W-572b. 37

For All Exterior & Interior Stain Uses

CUPRINOL STAIN & WOOD PRESERVATIVE combines beauty and protection for fences and all wood structures. It resists mildew discoloration, warping and rot. Cuprinol is available in a variety of colors and with built-in water repellency.

Triple protection

- **Durable, light-fast pigments** - resist the sun's rays and resist fading.
- **Long lasting water repellents** - keep out the moisture which promotes rot, mildew and staining.
- **Effective fungicide** - kills and prevents mildew, mold and other fungi from growing on treated wood.

CUPRINOL STAIN & WOOD PRESERVATIVE is available in a variety of colors and with built-in water repellency.

For wood protection

- **Resists rot** - Cuprinol's built-in water repellents keep moisture out of the wood.
- **Resists mildew** - Cuprinol's built-in fungicide kills and prevents mildew from growing on treated wood.
- **Resists staining** - Cuprinol's built-in pigments resist the sun's rays and resist fading.

Trees, Wood and Cuprinol Stain

Cuprinol Stain & Wood Preservative is available in a variety of colors and with built-in water repellency.

CAUTION: COMBUSTIBLE MIXTURE

N.Y.F.D. Certificate of Approval No. 3799

FOR THE FIRE DEPARTMENT OF THE CITY OF NEW YORK

CUPRINOL is a product of the Darworth Chemical Company, Inc., New York, N.Y.

Directions: BEFORE USE, THOROUGHLY MIX CONTENTS OF CAN. Use occasionally during use to keep color uniform. Use on clean, dry, unpainted wood or on previously stained surface. Apply liberally by brush, roller, spray or by dipping (siding - 10 minutes, millwork 5 minutes). Color will vary somewhat on different woods from the same lot. Re-coating over other colors may also affect the color. A sample flush color is recommended. Do not use on abraded or aged wood.

The water previously absorbed by the wood, the longer and more effective the protection. This water, covering the ends and joints. For best results apply to the shade at 40°-90°F. Do not thin. The stain may be mixed with Clear Cuprinol or the CUPRINOL Stain & Wood Preservative. CUPRINOL PRESERVATIVE STAINS dry to the touch rapidly, but touch-drying requires 24 hours. The stain may be applied at any time after the initial application.

Clean CUPRINOL with hard bristle brush. Do not use water to clean.

Coverage: 1 gallon covers about 100 sq. ft. of wood. After the first coat, a second coat may be applied.

Warning: This product is a combustible mixture. It should be kept away from fire and heat. It should be stored in a cool, dry place. It should be used in a well-ventilated area. It should be used with proper precautions. It should be used with proper precautions.

By the makers of:

Darworth Chemical Company, Inc., New York, N.Y.

Darworth

NEW YORK, N.Y.

Cameraman's Note
Poor Copy