

CAUTION: COMBUSTIBLE MIXTURE

N.Y.F.D. Certificate of Approval No. 1174

Directions

Apply to exterior surfaces of buildings, fences, and other structures. For best results, apply to clean, dry surfaces. Apply with brush, roller, or sprayer. Allow to dry before painting or staining.

Coverage

Approximately 100 sq. ft. per gallon.

Caution

Keep out of reach of children. Do not use in enclosed spaces. Avoid contact with eyes and skin. Wash thoroughly with soap and water after use.

Storage and Disposal

Store in original container in a cool, dry place. Do not store near heat or open flame. Dispose of unused product in accordance with local regulations.

Darworth



CUPE

SOLID COVE

STAIN & W PRESERVA



Keeps water out.
Keeps beauty in.
Protects against
mildew and rot.

**CAUTION: KEEP OUT OF RE
OF CHILDREN. READ CAUTIONS
WARNINGS ON BACK.**

ACTIVE INGREDIENTS	
Bis (Tri-n-butyl-lin) oxide	0.30%
Folpet (N-(trichloromethylthio) phthalimide)	0.44%
INERT INGREDIENTS	99.26%
	100.00%

EPA Reg. No. 518-68
EPA Est. No. 518-CT-1

Customer EB INDUSTRIES		Design CUPROK ST	
Size 610X708	C.E.	B.P.	B:
Business Office Order No. 3519-1548	Production Order No. 9-3193	Design and arrangement	

Read before signing

CUPRINOL®

SOLID COLOR

& WOOD PRESERVATIVE



KEEP OUT OF REACH OF CHILDREN. READ CAUTIONS AND DIRECTIONS ON BACK. 1 GALLON 3.785 LITERS

Chlorine	0.30%
Formaldehyde	0.44%
Water	99.26%
Total	100.00%

CUPRINOL STAIN & WOOD PRESERVATIVE

When it's wood against weather



Resists rot
Mildew discoloration
Exceeds water repellency requirements of Federal Specification TT W 572b 17

...light fast pigments
...Long lasting water repellents
...Effective fungistats
...Durable

LIMITED WARRANTY

Design *CUPRINOL STAIN & WOOD PRESERVATIVE*

Buyer's Approval

Design and arrangement	Spelling and punctuation	Colors
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Sketch BAW proof Color proof

10/25/52

ACCEPTED

CAUTION: COMBUSTIBLE MIXTURE

N.Y.F.D. Certificate of Approval No. 3799

DO NOT USE, POUR, SPILL OR STORE NEAR HEAT OR OPEN FLAME

This product conforms to Air Pollution Standards

Directions.

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. **BEFORE USE THOROUGHLY MIX CONTENTS OF CAN** stir occasionally during use to keep color uniform. Use on clean, dry, primed, unprimed wood or on previously stained, transparent stained surfaces which are free of mildew. Apply liberally by brush, spray or by dipping (soaking 3 minutes, in work 5 minutes). If stain is NOT freely absorbed by wood, allow surface to weather until adequate absorption is attained. The colors will vary somewhat on different woods. Recoating over other colors may affect the color. A sample brush out is recommended. Do not use on abraded plywood or urea-formaldehyde base materials. The more preservative absorbed by the wood, the longer and more effective the protection. Thoroughly cover cut ends and joints. For best results, apply in the shade at 40 - 90 F. Do not thin. To avoid lap marks maintain a wet edge. Clean brushes, etc. with mineral spirits or turpentine. Drying time varies rapidly but thorough drying requires 24 hours. If desired a second coat may be applied at any time after the initial application.

Coverage for these stains ranges from 150 sq. ft. per gallon for rough sawn materials up to 300 sq. ft. per gallon for smooth materials.

Caution.

Harmful if swallowed. May be absorbed through skin. Causes skin irritation. Avoid breathing vapors or spray mist. Use in well-ventilated area. Avoid contact with skin, eyes or clothing. In case of contact, immediately remove contaminated clothing and wash skin with soap and water. For eyes, flush with plenty of water and get medical attention. Wash clothing before reuse.

Storage and Disposal.

Store in original container, tightly sealed, in a cool, dry place. Do not reuse empty container. Dispose of by perforating, crushing, burying and insulating in place. Avoid storage near feed or food products.

This product is toxic to fish, keep out of lakes, streams, ponds. Do not contaminate water by cleaning, disposal or disposal of waste. Apply this product in accordance with the label. Keep out of reach of children.

Darworth

1000 N. 10th St. Milwaukee, Wis. 53233



SEMI

STAIN & PRESERVE



Keeps water out.
Keeps beauty in.
Protects against
mildew and rot.

EPA Reg No 518-68
EPA Est No 518-CT-1

CAUTION
OF CHILDREN
WARNINGS

ACTIVE INGREDIENTS
Bis (Tri-n-butyl-tin)
Folpet (N-trichloro-
phthalimide)
INERT INGREDIENTS

Customer EB INDUSTRIES		
Size G10X708 GAL. JT	C.E.	B.P.
9-13-71	Order Code No. 231-1549	Production Group No. 9-3192
Read before signing		
<p><small>Buyer agrees that if Chemical Company, Inc. shall in any way be liable for any error in the attached order, it shall be the responsibility of the buyer to check the order against the attached invoice and to advise the seller of any error within the time specified in the invoice. The buyer shall be responsible for the accuracy of the order and for the payment of the invoice. The seller shall not be liable for any error in the attached order or invoice. The buyer shall be responsible for the accuracy of the order and for the payment of the invoice. The seller shall not be liable for any error in the attached order or invoice.</small></p>		
Chemical Company, Inc.		

30

CUPRINOL[®]

SEMI-TRANSPARENT

STAIN & WOOD PRESERVATIVE



CAUTION: KEEP OUT OF REACH OF CHILDREN. READ CAUTIONS AND DIRECTIONS ON BACK.

**1 GALLON
3.785 LITERS**

INGREDIENTS	
n-butyl-tin oxide	0.30%
IN-(trichloromethylthio)phthalimide	0.43%
INGREDIENTS	99.25%
	100.00%

CUPRINOL

STAIN & WOOD PRESERVATIVE

When it's wood against weather



Resists rot



Mildew discoloration*



Exceeds water repellency requirements of Federal Spec TT-W-572b. 3.7

CUPRINOL STAIN & WOOD PRESERVATIVE combines beauty and protection. Resists rot, mildew, warp and discoloration. Use on all siding, fences, decks and outdoor furniture. When properly applied will NOT check, peel, flake. **Durable, light-fast pigments** provide long lasting color. **Long lasting water repellents** help resist pigment washoff, warping and staining.

Effective fungistats resist fungi that produce rot and mildew discoloration.

*Mildew discoloration may develop after application on untreated wood. Mildew present prior to staining. Test for mildew by applying a 50:50 solution of bleach and water. Mildew is present if application area lightens. Scrub with bleach solution, rinse with water, and apply 1 qt. household bleach/gal. warm water. Let stand 30 minutes, then rinse with clean water. Apply Cuprinol after area is completely dry.

LIMITED WARRANTY

This product will not be held responsible for any staining or discoloration of wood. THE MANUFACTURER'S LIABILITY UNDER ANY WARRANTY AND THEREAFTER IS LIMITED TO THE REPLACEMENT OF THE PRODUCT AND DOES NOT INCLUDE LABOR OR OTHER CONSEQUENTIAL DAMAGES.

Design **CUPRINOL SEMI-TRANSPARENT STAIN & WOOD PRESERVATION**

Buyer's Approval Sketch B&W proof Color proof

To be filled in by Buyer. Check (X) applicable boxes:

<input type="checkbox"/> Approved as submitted	<input type="checkbox"/> Approved as submitted	<input type="checkbox"/> Approved as submitted
<input type="checkbox"/> Change as detailed	<input type="checkbox"/> Change as detailed	<input type="checkbox"/> Change as detailed

Date signed: _____ Buyer's Signature: _____

CC-1 Form 549H 7-73

61-5-6-030
9-12-79

ACCEPTED

OCT 8 1979

5/8 6-3

CAUTION: COMBUSTIBLE MIXTURE

NYED Certificate of Approval: JN-1-199

Directions

Apply to all exterior surfaces of woodwork, trim, and siding. For best results, apply to clean, dry surfaces. Apply to all exterior surfaces of woodwork, trim, and siding. For best results, apply to clean, dry surfaces. Apply to all exterior surfaces of woodwork, trim, and siding. For best results, apply to clean, dry surfaces. Apply to all exterior surfaces of woodwork, trim, and siding. For best results, apply to clean, dry surfaces.

Coverage

Coverage varies with application method and surface conditions.

Caution

Keep away from children. Avoid contact with eyes. Wash thoroughly with soap and water if contact occurs.

Storage and Disposal

Store in a cool, dry place. Do not use if the container is damaged or leaking. Dispose of unused product according to local regulations.

Darworth



SEI

STAIN & PRESE



Keeps water out.
Keeps beauty in.
Protects against
mildew and rot

EPA Reg. No. 518-68
EPA Est. No. 518-71

CAUTION
OF CHILDREN
WARNINGS

ACTIVE INGREDIENTS
Bis (Tri-n-butyl-tin)
Folpet N-trichloro
phthalic
NEUTRAL INGREDIENTS

Customer	EB INDUSTRIES		
Size	G10X708 GAL-TI	C.E.	B.P.
	7-13	231-1549	9-3192

Read before signing

CUPRINOL

SEMI-TRANSPARENT

& WOOD PRESERVATIVE



CAUTION: KEEP OUT OF REACH OF CHILDREN. READ CAUTIONS AND DIRECTIONS ON BACK. 1 GALLON / 3.785 LITERS

INGREDIENTS: Cuprinol (Copper Nonyl Oxide), Chloromethylene Bisphthalimide, etc.

CUPRINOL

STAIN & WOOD PRESERVATIVE

When it's wood against weather



Exceeds water repellency requirements of Federal Specification W-572b-3

Water repellent, Durable, light-fast pigments, Long-lasting, Mildew resistant, Inhibits mold, Mildew, and rot, Resists staining, Resists fading, Resists cracking, Resists peeling, Resists chalking, Resists blistering, Resists bubbling, Resists delamination, Resists insect damage, Resists fungal growth, Resists bacterial growth, Resists algal growth, Resists lichen growth, Resists moss growth, Resists mildew growth, Resists mold growth, Resists rot growth, Resists decay growth, Resists insect damage, Resists fungal growth, Resists bacterial growth, Resists algal growth, Resists lichen growth, Resists moss growth, Resists mildew growth, Resists mold growth, Resists rot growth, Resists decay growth.

LIMITED WARRANTY

Manufacturer's limited warranty text regarding product performance and coverage.

Design **CUPRINOL**
SEMI-TRANSPARENT STAIN & WOOD PRESERVATION

Buyer's Approval: Approved Not Approved

Spelling and punctuation: Correct Incorrect

Colors: Correct Incorrect

61-5-6 DPC