DEC 24 1975

Un leral baselists.
Fun and Radentists Act,
on a ended, for the pessions
regularised under
The Res. No. 1786



BARCOSOTE

CREOSOTE PENTA WOOD PRESERVER

ACTIVE INGREDIENTS

Refined Coal Tar Creosote Oil 50.000%
Petroleum Hydrocarbons 47.500%
Pentachlorophenol 2.125%
Other Chlorophenols and
Related Compounds 0.375%
total 100 000%

WARNING

KEEP OUT OF REACH OF CHILDREN
See Additional Precautions on Back Panel

ONE U.S. GALLON

UNION AMSCO

BARCOSOTE

D'RECTIONS

Apply by dipping, brush or spraying. BARCOSOTE can be applied to all unpainted wood that is not to be painted (fence posts, foundation timbers and heavy wood members) by dipping, brushing or spraying. One gallon will cover an area of approximately 100 square feet. Wood should be thoroughly dried before application of BARCOSOTE for best penetration. For cold weather application, heat BARCOSOTE to 125°F. For wood which is to be in contact with the soil, a thorough dip application is recommended. However, where impractical apply two thorough coats by the brush or spray method. For niaximum penetration, allow wood to soak for a minimum of 12 hours, when treated by the dip method. Fence posts should be debarked, dry and well seasoned before treating with BARCOSOTE. Wear protective clothing and rubber gloves when handling the freshly treated lumber

USE BARCOSOTE FOR

Preserving fence posts, rails, timbers, gates and planking. Protecting exposed wood against rot and decay. Prevents fungi and molds of wood. Controls termites and powder post beetles.

Treatment of wood shingles and preserving ground line areas of telephone and power poles.

For proter ---- ... (ainst termites treat wood prior to use in construction

WARNING

Avoid contact with skin and clothing as it may cause skin irritation. Before hariding BARCOSOTE or freshly treated wood, har us should be coated with Linseed Oil or grease to protect the skin. Remove clothing that has become soaked with BARCOSOTE. Do not use inside dairy barns, silos, poultry houses or other structures where it may contact food, feed or livestock.

This product is toxic to fish and wildlife. Keep out of lakes, streams or pands. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label. May be fatal or harmful if swallowed. May cause severe burns. Avoid inhalation of spray mist.

DO NOT REUSE CONTAINER.

DESTROY WHEN EMPTY,

USE WITH ADEQUATE VENTILATION.

DO NOT TAKE INTERNALLY — if ingested accidentally, call physician immediately.

DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME

MADE IN U.S.A.

EPA Reg #528-57 EPA Est #528 MN-1

CU

Amsco Division Union Oil Company of California Minneapolis, Minnesota 55414