

MARINE



Sears + Best



ANTI-FOULING BOTTOM PAINT



with TBTF for salt or fresh water

Handwritten notes:
CF
NV3
EPA REG NO 539 272
EPA EST NO 8768 11 1

PRECAUTIONARY STATEMENTS
DANGER: HAZARDS TO HUMANS and DOMESTIC ANIMALS
 Corrosive. Causes irreversible eye damage and burns. Harmful if absorbed through skin, swallowed or inhaled. Do not get on skin, in eyes or on clothing. Wear goggles or safety glasses. Wear protective clothing such as long sleeved cotton shirt, long pants, hat and gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Avoid breathing vapor, dust or chips from sanding. Use with adequate ventilation. Close container after each use.

FIRST AID STATEMENT.
 If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.
 NOTE TO PHYSICIAN: Probably mucosal damage may contraindicate the use of gastric lavage.
 If in eyes: Flush with plenty of water. Get medical attention.
 If on skin: Wash with plenty of soap and water. Get medical attention.

ENVIRONMENTAL HAZARDS.
 This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS:
COMBUSTIBLE. Do not use or store near heat, sparks or open flame. Use with adequate ventilation. NOTE: While spraying and or sanding boat surface wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and by the National Institute for Occupational Safety and Health.

DIRECTIONS FOR USE: IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

STORAGE AND DISPOSAL:
 Do not reuse empty container. Wrap container and put in trash collection. Keep out of reach of children.

Active Ingredients	14.3%
Copper Powder	7.0%
Tributyltin Fluoride	7.3%
Inert Ingredients	77.9%
Metallic Tin 3.00%	100.0%

KEEP OUT OF THE REACH OF CHILDREN.
DANGER
 See Side Panel for Additional Precautionary Statements

30 63654 GOLD BRONZE
32 FL. OZ. (1 qt.)

ALL W...
 THE S...
 EFFECT...
 ING...
 • TBTF (T...
 resistant...
 retard m...
 remains...
 DO NOT SE...
 BEFORE YO...
 blade be...
 condition...
 by a che...
 REMOVE...
 OLD PAINT...
 and LACQU...
 NEW OR UN...
 25% with...
 applying...
 FIBERGLAS...
 THINNE...
 METALS...
 Complet...
 Remove...
 smooth...
 with Seab...
 MARINE...
 three...
 For boat...
 PAINT...
 paint...
 generou...
 time be...
 after...
 NOTE...
 damage...
 direct...
 COVERAGE

LARINE

Sears & Best

ANTI-FOULING TOM PAINT

with TBTF for salt or fresh water

PRECAUTIONARY STATEMENTS
DANGER: HAZARDS TO HUMANS and DOMESTIC ANIMALS
 Corrosive. Causes irreversible eye damage and burns. Harmful if absorbed through skin, swallowed or inhaled. Do not get on skin, in eyes or on clothing. Wear goggles or safety glasses. Wear protective clothing such as long-sleeved cotton shirt, long pants, hat and gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Avoid breathing vapor, dust or chips from sanding. Use with adequate ventilation. Close container after each use.

FIRST AID STATEMENT:
 If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.
 NOTE TO PHYSICIAN: Probably mucosal damage may contraindicate the use of gastric lavage.
 If in eyes: Flush with plenty of water. Get medical attention.
 If on skin: Wash with plenty of soap and water. Get medical attention.

ENVIRONMENTAL HAZARDS:
 This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS:
COMBUSTIBLE. Do not use or store near heat, sparks or open flame. Use with adequate ventilation. NOTE: While spraying and/or sanding boat surface wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and by the National Institute for Occupational Safety and Health.

DIRECTIONS FOR USE: IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

STORAGE AND DISPOSAL:
 Do not reuse empty container. Wrap container and put in trash collection. Keep out of reach of children.

OUT OF THE REACH OF CHILDREN.
DANGER
 See label for Additional Precautionary Statements

30 63654 GOLD BRONZE
32 FL. OZ. (1 qt.)

RECOMMENDED FOR ALL WOOD, PLYWOOD, FIBERGLASS AND PROPERLY PRIMED METAL BOATS
 The SPECIAL WATER RESISTANT ACRYLIC BASE AS A COMBINATION WITH TBTF PROVIDES EFFECTIVE PROTECTION AGAINST MARINE GROWTH, TERRESTRIAL ALGAE AND OTHER MARINE AND LAND ORGANISMS.

FEATURES
 • TBTF (Tributyltin Fluoride) has been proven a most effective anti-fouling toxicant. • The water resistant acrylic base develops a hard, medium gloss finish, yet allows proper release of TBTF to retard most growth or attachment. • Formulated in "fade resistant" rich, bright colors. • TBTF remains effective even if boat is pulled from water and relauached frequently.

DIRECTIONS FOR USE
DO NOT SPRAY! WEAR MASK WHILE SANDING TO AVOID BREATHING DUST. DO NOT PAINT JUST BEFORE YOU PAINT! Surface should be clean and sound. Check appearance of old paint with a knife blade before painting over previously painted surfaces. Old paint that is generally in good condition should be removed. Previous coats of old paint that are hard, brittle or peeling should be removed by a chiseling or powdery feel, should be completely removed. Use SEARS PAINT AND VARNISH REMOVER (except on fiberglass) or power sanding to remove old paint.

OLD PAINT IN GOOD CONDITION: Sand thoroughly to remove old paint. Use with SEARS EPOXY and LACQUER THINNER. Apply two or three finish coats unthinned.

NEW OR UNFINISHED WOOD: Sand thoroughly. Wash with water. Apply with SEARS EPOXY and LACQUER THINNER. Apply two or three finish coats unthinned.

FIBERGLASS: Sand thoroughly to remove gloss. Wash surface with SEARS EPOXY and LACQUER THINNER to remove grease, wax and mg. release agent. Apply two or three finish coats unthinned.

METALS (Steel and Aluminum): Preparation of metal below the waterline is extremely important. Complete insulation from water is necessary to prevent pitting and other corrosion damage. Remove a rust and corrosion with steel wool or by sanding until the metal is bright and smooth. Finish sand with very fine emery cloth to remove protruding metal shavings. Wash with SEARS EPOXY and LACQUER THINNER to remove traces of oil, grease or wax. Prime with SEARS MARINE METAL PRIMER following the instructions given on the label. Apply two or three finish coats unthinned.

APPLICATION
 For boats used in fresh water, apply a minimum of two coats of SEARS ANTI-FOULING TOM PAINT. At least three coats should be used on boats used in salt water. For best results, do not paint in direct sunlight. Stir paint thoroughly before and during application. Apply paint liberally with good quality natural bristle brush or enamel roller. Allow 24 hours between coats. Allow at least forty-eight hours after application of final coat before launching. Clean brushes and other tools with SEARS EPOXY and LACQUER THINNER after use.

NOTE: Scratches and gouges that penetrate the paint to bare metal should be repaired with SEARS MARINE METAL PRIMER and SEARS EPOXY and LACQUER THINNER. Sand damaged areas to finish before painting.

COVERAGE: Approximately 100 sq. ft. per gallon per coat.

Sold by SEARS, ROEBUCK AND CO. Chicago, IL 60684