

Sears **MARINE**

ANTI-FOULING BOTTOM PAINT

with TBTF for salt or fresh water

*** DANGER ***

May cause severe eye burns. May cause eye damage. May be fatal if swallowed. May cause skin irritation or delayed chemical burns. Do not get in eyes, on skin, or on clothing. Vapor harmful. Avoid breathing of vapor or sanding dust. Wear goggles or face shield and rubber gloves while handling.

COMBUSTIBLE...DO NOT USE. POUR, SPILL, OR STORE NEAR HEAT OR OPEN FLAME.

Use with adequate ventilation. Close container after each use. Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard in a safe place. Do not contaminate water by cleaning of equipment or disposal of wastes.

ANTIDOTE STATEMENT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes, and get medical attention, wash skin with plenty of soap and water. Wash contaminated clothing before re use. If swallowed CALL PHYSICIAN IMMEDIATELY.

DO NOT SPRAY!

WEAR MASK WHILE SANDING TO AVOID BREATHING PAINT DUST. THE SPECIAL TANT ACRYLIC RESINS IN COMBINATION WITH TBTF PROVIDE EFFECTIVE PROTECTION AGAINST BARNACLES, TEREDOS, ALGAE, AND OTHER MARINE FOULING ORGANISMS.

RECOMMENDED FOR: All wood, plywood, fiberglass, and properly primed metal boat.

FEATURES

- TBTF (Tant) acrylic resin, butadiene rubber, and other synthetic resins.
- The water-soluble TBTF base does not contain any toxic or corrosive ingredients.
- Retention of color and gloss.
- Excellent adhesion to all surfaces.
- TBTF resins are not affected by heat up to 150°F (65°C) and by water.

DIRECTIONS

BEFORE YOU PAINT

Surface should be clean and sound. Remove all old paint, dirt, grease, and other contaminants. Sand or grind surface to a smooth finish. Remove all sanding dust. Wash surface with clean water. Dry thoroughly. Use TBTF on all surfaces to be painted. Do not use on metal surfaces unless properly primed.

OLD PAINT IN GOOD CONDITION

Apply TBTF over old paint in good condition. Use brush or roller. Apply in two coats. Allow to dry 24 hours before use.

NEW OR UNFINISHED WOOD

Apply TBTF over new or unfinished wood. Use brush or roller. Apply in two coats. Allow to dry 24 hours before use.

WORK AREA

Work in a well-ventilated area. Avoid breathing dust or fumes. Wear protective clothing. Do not use near open flames or heat.

META, Steel, and Aluminum

Apply TBTF over metal surfaces only after proper priming. Use brush or roller. Apply in two coats. Allow to dry 24 hours before use.

LA-1000 and LA-2000

Apply TBTF over LA-1000 and LA-2000 primers. Use brush or roller. Apply in two coats. Allow to dry 24 hours before use.

APPLICATION

Apply TBTF with brush or roller. Apply in two coats. Allow to dry 24 hours before use. Do not use on metal surfaces unless properly primed. Do not use on surfaces that will be in contact with water or other liquids.

NOTE: Scratch and gouges that penetrate the paint to bare metal should be repaired to avoid damage from corrosion or galvanic action. Sand damaged areas to bare metal and follow directions for painting metal.

COVERAGE: Approximately 100 sq. ft. (9.3 sq. meters) per quart.

Sold by SEARS, ROEBUCK AND CO., Chicago, IL 60684

PA 501 NO 60127-AA

PA 101 NO 87881A1

30 63624 BLUE
32 FL.OZ. (1QT.)
(95 LITERS)

DANGER!
KEEP OUT OF REACH OF CHILDREN
See side for other precautions

Active Ingredients
(1) Butyltin Fluoride 80.5%
Inert Ingredients 19.5%
Net Wt. 7.84%

ACCEPTED

577-219