



MARINE

Sears & Best

**ANTI-FOULING
BOTTOM PAINT**

with TBTF for salt or fresh water

EPA REG. NO. 339-279
EPA EST. NO. 8788 IL 1

Active Ingredients
Tributyltin Fluoride 8.3
Inert Ingredients 91.7
Metallic Tin 3.10% 100.0%

**KEEP OUT OF THE REACH OF CHILDREN.
DANGER**

See Side Panel for Additional Precautionary Statements

PRECAUTIONARY STATEMENTS
DANGER: HAZARDS TO HUMANS and DOMESTIC ANIMALS
Corrosive. Causes irreversible eye damage and burns. Harmful if absorbed through skin, swallowed, or inhaled. Do not get on skin, in eyes, or on clothing. Wear goggles or safety glasses. Wear protective clothing such as long-sleeved cotton shirt, long pants, hat and gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Avoid breathing vapor, dust or chips from sanding. Use with adequate ventilation. Close container after each use.

FIRST AID STATEMENT:
If swallowed: Drink promptly a large quantity of milk, egg whites, belach solution or if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.
NOTE TO PHYSICIAN: Probably mucosal damage may contraindicate the use of gastric lavage.
If in eyes: Flush with plenty of water. Get medical attention.
If on skin: Wash with plenty of soap and water. Get medical attention.

ENVIRONMENTAL HAZARDS:
This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS:
COMBUSTIBLE. Do not use or store near heat, sparks or open flame. Use with adequate ventilation. **NOTE:** While spraying and/or sanding boat surface, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and by the National Institute for Occupational Safety and Health.

DIRECTIONS FOR USE: IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

STORAGE AND DISPOSAL:
Do not reuse empty container. Wrap container and put in trash collection. Keep out of reach of children.

30 63624 BLUF
32 FL. OZ. (1 qt.)

ALL WOOD, PL
THE EFFECTS OF
EFFECT OF PROTE
NUTRITION, MA

• TBTF (Tributyltin
resistant acrylic) has
retard most growth
remains effective

DO NOT SPRAY IN
BEFORE YOU PAINT
base before paint
condition should be
by a chalking agent
REMOVER (see test)
OLD PAINT IN GOOD
and LACQUER (see test)
NEW OR UNFINISHED
25% with Sealant
applying two coats
FIBERGLASS (see test)
THINNER (see test)
METALS (steel, brass,
complete removal
have a rust inhibitor
smooth finish
with Sealant (see test)
MARINE METALS (see test)
Marine Metals (see test)

For best results, use
PAINT. At least 1
painting in 10 days
after using a TBTF
the surface of the
boat should be
smooth and free
of rust.
NOTE: This paint
is not a primer.
COVERAGE: 100

MARINE



ANTI-FOULING BOTTOM PAINT

with TBTF for salt or fresh water

KEEP OUT OF THE REACH OF CHILDREN.
DANGER
See Panel for Additional Precautionary Statements

PRECAUTIONARY STATEMENTS
DANGER: HAZARDS TO HUMANS and DOMESTIC ANIMALS
Corrosive. Causes irreversible eye damage and burns. Harmful if absorbed through skin, swallowed, or inhaled. Do not get on skin, in eyes, or on clothing. Wear goggles or safety glasses. Wear protective clothing such as long-sleeved cotton shirt, long pants, hat and gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Avoid breathing vapor, dust or chips from sanding. Use with adequate ventilation. Close container after each use.

FIRST AID STATEMENT:
If swallowed: Drink promptly a large quantity of milk, egg whites, dilute solution or if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.
NOTE TO PHYSICIAN: Probably mucosal damage may contraindicate the use of gastric lavage.
If in eyes: Flush with plenty of water. Get medical attention.
If on skin: Wash with plenty of soap and water. Get medical attention.

ENVIRONMENTAL HAZARDS:
This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS:
COMBUSTIBLE. Do not use or store near heat, sparks or open flame. Use with adequate ventilation. **NOTE:** While spraying and or sanding boat surface, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and by the National Institute for Occupational Safety and Health.

DIRECTIONS FOR USE: IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

STORAGE AND DISPOSAL:
Do not reuse empty container. Wrap container and put in trash collection. Keep out of reach of children.

30 63624 BLUF
32 FL. OZ. (1 qt.)

RECOMMENDED FOR
ALL WOOD, PLYWOOD, FIBERGLASS AND PROPERLY PRIMED METAL BOATS
This paint is a water resistant acrylic resin in combination with TBTF. Provides long life protection against barnacles, weeds, algae and other marine fouling.

FEATURES
• TBTF (Tributyltin Fluoride) has been proven a most effective anti-fouling toxicant. • The water resistant acrylic base develops a hard, medium gloss finish, yet allows proper release of TBTF to retard most growth or attachment. • Formulated in fade resistant, rich, bright colors. • TBTF remains effective even if boat is pulled from water and relaunched frequently.

DIRECTIONS FOR USE
DO NOT SPRAY! WEAR MASK WHILE HANDING TO AVOID BREATHING PAINT DUST.
BEFORE YOU PAINT: Surface should be clean and sanded. Check adhesion of old paint with a knife blade before painting. Sand areas of old paint that are loose or peeling. If old paint is in good condition, sand only the areas of old paint that are loose or peeling. If old paint is in poor condition, sand the entire surface. Remove all sand and dust with a vacuum or blower. If old paint is in poor condition, use a heavy duty sandpaper to remove old paint. Use SEARS PAINT ANTI-SAND REMOVER to remove old paint from fiberglass and metal surfaces.

OLD PAINT IN GOOD CONDITION: Sand the surface with a fine sandpaper. Remove the sand with a vacuum or blower. Apply the paint with a brush or roller. Apply a second coat after the first coat has dried.

NEW OR UNFINISHED WOOD: Sand the surface with a fine sandpaper. Remove the sand with a vacuum or blower. Apply the paint with a brush or roller. Apply a second coat after the first coat has dried.

FIBERGLASS: Sand the surface with a fine sandpaper. Remove the sand with a vacuum or blower. Apply the paint with a brush or roller. Apply a second coat after the first coat has dried.

METALS: Sand the surface with a fine sandpaper. Remove the sand with a vacuum or blower. Apply the paint with a brush or roller. Apply a second coat after the first coat has dried.

APPLICATION
Apply the paint with a brush or roller. Apply a second coat after the first coat has dried.

NOTE: This paint is not intended for use on the interior of a boat. It is not intended for use on the exterior of a boat that will be in contact with water.

COVERAGE: All surfaces. Coverage varies with surface condition and application method.

Sold by SEARS, ROEBUCK AND CO. Chicago, IL 60684