

exterior

WEATHERBEATER

Protects Against Moisture, Mildew and Rot
CONTAINS POLYURETHANE

**WARRANTED
3 WAYS:**

- No Cracking
- No Peeling
- No Blistering

See back of label for complete statement of warranty

OIL BASE SOLID COLOR STAIN AND PRESERVATIVE

WARNING

KEEP OUT OF REACH OF CHILDREN
See Side Panel for Additional Precautionary Statements

ONE GALLON
(3.785L)

Active Ingredients
 Bis(tributyltin)oxide 0.49%
 Folpet N [4-chloromethylthio]phthalimide 0.45%
Inert Ingredients: 99.06%

ACCEPTED

APR 22 1981

539-292

THIS PAINT
IS FREE OF LEAD HAZARDS

SEARS PAINT
FOR GREAT AMERICAN
HOMES LIKE YOURS

EPA Est. No. 8788-NC-01
EPA Reg. No. 539-292

exterior
WEATHERBEATER
Prevent
Mildew and Rot

WARRANTED 3 WAYS:

- No Cracking
- No Peeling
- No Blistering

See back of label for complete statement of warranty

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS and
DOMESTIC ANIMALS**

WARNING
CONTAINS PETROLEUM DISTILLATE
AND DIBUTYL TIN DIOXIDE

HARMFUL IF SWALLOWED

FIRST AID STATEMENT

ENVIRONMENTAL HAZARDS

PHYSICAL OR CHEMICAL HAZARDS
COMBUSTIBLE

DIRECTIONS FOR USE
IT IS A VIOLATION OF FEDERAL LAW
TO USE THIS PRODUCT IN A MANNER
INCONSISTENT WITH ITS
LABELING

STORAGE AND DISPOSAL

Keep out of reach of children

ONE GALLON
(3.785L)

Ingredients: Tributyl tin oxide 0.45%,
Diethyl tin tetrachloride 0.45%,
Diethyl tin tetrachloride 99.06%

Best **WEATHERBEATER**
OIL BASE SOLID COLOR STAIN AND PRESERVATIVE

WEATHERBEATER OIL BASE SOLID COLOR STAIN and PRESERVATIVE is designed for use on weathered shingles, shakes, rough hewn wood. It will mask the grain of the wood yet allow its natural texture to show. Special ingredients protect against wood rot, moisture and mildew. WEATHERBEATER OIL BASE SOLID COLOR STAIN and PRESERVATIVE is so water resistant that it exceeds water repellency requirements of Federal Specification F-151.

WHERE TO USE:

Recommended for new or previously stained wood. Not recommended for decks, docks, outdoor furniture, or wood.

BEFORE STAINING:

Prepare the surface properly for best results. The surface must be clean to achieve proper adhesion. Scrape and wire-brush weathered surfaces to remove all loose flakes. Brush away loose dust and dirt. Scrub with Sears HEAVY DUTY CLEANER to remove imbedded dirt. Rinse completely. Fill the cracks, open construction joints, knots, and holes with WEATHERBEATER STAINABLE WOOD TEXTURE CAULK.

MILDEW: it is important to remove mildew before staining by scrubbing (using a mixture of 1/3 cup Sears Household Bleach and 3 qts. of water). **NOTE TO USER: DO NOT USE AMMONIA. WEAR RUBBER GLOVES TO AVOID SKIN AND BREATH FUMES.**

NOW APPLY STAIN—For best results, use Sears EXTERIOR PAINT PAD, ROUGH SURFACE BRUSH or WEATHERBEATER BRUSH. Roller application is not recommended except with Sears ROUGH SURFACE ROLLER over textured surfaces.

CLEAN-UP: Clean tools immediately with POLENE or BRUSH CLEANER.

APPLICATION: Thorough mixing is essential. Stir periodically while using. For very porous or badly weathered wood, apply a second coat after 24 hours for increased protection and richer color. Prior to application of entire home, brush out in a small inconspicuous spot and let dry to assure that STAIN is desired color.

LIMITED WARRANTY—This Sears Weatherbeater Oil Base Solid Color Stain and Preservative, when applied according to label instructions at a specified application rate, will provide protection over a properly prepared surface for 3 years from date of application. **FOR 3 YEARS FROM DATE OF APPLICATION:**
(1) No cracking
(2) No peeling
(3) No blistering
If stain fails to perform as specified above, Sears will furnish without charge enough product or if you prefer, refund the purchase price or cost of labor for the application of product. This warranty gives you specific legal rights which may vary from state to state. SEARS, ROEBUCK AND CO. Sears


Apply stain to entire length, work with wood grain, rather than against, to avoid overlap patterns. Avoid application of stain in direct sunlight. Follow the shade around the house. Apply at temperatures above 60 F (16 C). Do not apply if temperatures below 45 F (7 C) are expected within 24 hours. True stain color will be evident after application when allowed to dry thoroughly.

COVERAGE: Porous woods—up to 200 square feet (18 sq meters) per gallon. For best protection and color uniformity, apply liberally. More coats give additional protection, but reveal less texture. Color will vary depending on number of coats and type of wood. To assure color uniformity over entire surface always buy enough stain to complete the whole job. During application, intermix gallons of the same color.

Keep from freezing. LABORATORY TESTED
Sold by SEARS, ROEBUCK AND CO.



44



WEATHERBEATER

OIL BASE SOLID COLOR STAIN AND PRESERVATIVE

WEATHERBEATER OIL BASE SOLID COLOR STAIN and PRESERVATIVE is designed to beautify and protect new or weathered shingles, shakes, rough hewn wood. It will mask the grain of the wood yet allow its natural texture to show through. Special ingredients protect against wood rot, moisture and mildew. WEATHERBEATER OIL BASE STAIN and PRESERVATIVE is so water resistant that it exceeds water repellency requirements of Federal Specification TT-W-572b, 3.7.

WHERE TO USE:

Recommended for new or previously stained wood. Not recommended for decks, docks, outdoor furniture and below ground wood.

BEFORE STAINING:

Prepare the surface properly for best results. The surface must be clean to achieve proper adhesion. Scrape and wire-brush weathered surfaces to remove all loose flakes. Brush away loose dust and dirt. Scrub with Sears HEAVY DUTY CLEANER to remove imbedded dirt. Rinse completely. Fill the cracks, open construction joints, knots, and holes with WEATHERBEATER STAINABLE WOOD TEXTURE CAULK.

MILDEW: It is important to remove mildew from the surface before staining by scrubbing (use a long-handled scrub brush) with a mixture of 1 3 cup Sears HEAVY DUTY CLEANER, 1 qt household bleach and 3 qts. of warm water.

NOTE TO USER DO NOT USE DETERGENTS CONTAINING AMMONIA. WEAR RUBBER GLOVES AND SAFETY GLASSES TO AVOID SKIN AND EYE CONTACT. DO NOT BREATHE FUMES.

NOW APPLY STAIN—For best results, use Sears EXTERIOR PAINT PAD, ROUGH SURFACE BRUSH or WEATHERBEATER BRUSH. Roller application is not recommended except with Sears ROUGH SURFACE ROLLER over textured surfaces.

APPLICATION: Thorough mixing is essential. Stir periodically while using. For very porous or badly weathered wood, apply a second coat after 24 hours for increased protection and richer color. Prior to application of entire home, brush out in a small inconspicuous spot and let dry to assure that STAIN is desired color.

Apply stain to entire length, work with wood grain rather than against, to avoid overlap patterns. Avoid application of stain in direct sunlight. Follow the shade around the house. Apply at temperatures above 60 F (16 C). Do not apply if temperatures below 45 F (7 C) are expected within 24 hours. True stain color will be evident after application when allowed to dry thoroughly.

COVERAGE: Porous woods—up to 200 square feet (18 sq. meters) per gallon. For best protection and color uniformity, apply liberally. More coats give additional protection, but reveal less texture. Color will vary depending on number of coats and type of wood. To assure color uniformity over entire surface always buy enough stain to complete the whole job. During application, intermix gallons of the same color.

CLEAN-UP: Clean tools immediately after use with Sears TIR-POLENE™ or BRUSH CLEANER.

LIMITED WARRANTY—This Sears WEATHERBEATER Stain, when applied according to label instructions at a spreading rate not to exceed 200 square feet per gallon over a properly prepared surface, and provided that substrate and previously applied coatings remain intact, will have the following qualities **FOR 3 YEARS FROM DATE OF APPLICATION:**

- (1) No cracking
- (2) No peeling
- (3) No blistering

If stain fails to perform as specified above, contact your nearest Sears store and Sears will furnish without charge enough additional stain to correct the condition, or, if you prefer, refund the purchase price. This warranty does not include labor or cost of labor for the application of any stain.

This warranty gives you specific legal rights, and you may have other rights which may vary from state to state.

SEARS, ROEBUCK AND CO., Sears Tower, BSC 41-3, Chicago, IL 60684

Keep from freezing. LABORATORY TESTED FOR QUALITY
Sold by SEARS, ROEBUCK AND CO., Chicago, IL 60684



44

45