

exterior

# WEATHERBEATER

Protects Against Moisture, Mildew and Rot  
CONTAINS POLYURETHANE

**WARRANTED  
3 WAYS:**  
■ No Cracking  
■ No Peeling  
■ No Blistering  
\* See back of label for  
complete statement of warranty

## BLENDING BASE

### for use with SEARS OIL BASE STAIN AND PRESERVATIVE

#### WARNING

**KEEP OUT OF REACH OF CHILDREN**  
See Side Panel for Additional Precautionary Statements

**ONE GALLON**  
(3.785L)

Active Ingredients:  
Bis(isobutyl)tin oxide 0.53%  
Folpet N [1-trichloro(methyl)thio]phthalimide 0.49%  
Inert Ingredients: 98.98%

43



SEARS PAINT  
FOR GREAT AMERICAN  
HOMES LIKE YOURS

EPA Est. No. 8788-NC-01  
EPA Reg. No. 539-293

539-293

*Sears • Best*

exterior

# WEATHERBEATER

Protects Against Moisture, Mildew and Rot  
CONTAINS POLYURETHANE

**WARRANTED  
3 WAYS:**

- No Cracking
- No Peeling
- No Blistering

See back of label for complete statement of warranty.

# BLENDING BASE

# Use with SEARS BASE STAIN PRESERVATIVE

**KEEP OUT OF REACH OF CHILDREN**  
See back of label for Cautionary Statements

**ONE GALLON**  
3.785L

Active Ingredients  
Benzoin Resin 4.5  
Eugenol 4.5  
Inert Ingredients 4.5

PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS  
**WARNING**  
CONTAINS POLYURETHANE AND IS TOXIC TO AQUATIC LIFE

• HARMFUL IF SWALLOWED

FIRST AID STATEMENT

ENVIRONMENTAL HAZARDS

PHYSICAL OR CHEMICAL HAZARDS  
COMBUSTIBLE

DIRECTIONS FOR USE  
IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING

STORAGE AND DISPOSAL

Keep out of reach of children

*Sears • Best*

# WEATHERBEATER

## BLENDING BASE for use with WEATHERBEATER

**WEATHERBEATER BLENDING BASE** used with WEATHERBEATER BASE STAIN PRESERVATIVE allows the flexibility of showing as much of the wood grain and wood tone that will show through. Special ingredients can create your own version of semi-transparent colors.

Recommended for new or previously stained wood. Not recommended for use on untreated wood.

**BEFORE STAINING:**  
Prepare the surface properly for best results. The surface must be clean to achieve proper adhesion. Sand and wire-brush weathered surfaces to remove all loose fibers. Brush away loose dust and dirt. Scrub with Sears HEAVY DUTY CLEANER to remove imbedded dirt. Rinse completely. Fill cracks, open construction joints, knots and holes with WEATHERBEATER STAINABLE WOOD TEXTURE CO.


**MIXING RECOMMENDATION** Start with a small mixture of blending base to one part WEATHERBEATER OIL BASE SOLID COLOR STAIN as a test to determine how much grain will show through. Brush out a small inconspicuous spot and let dry. Repeat the process, varying the amount of blending base until the desired transparency is achieved. Once the proper tone is set, mix enough to finish the entire job, thereby assuring color uniformity. It is recommended that total solution be mixed in a clean large container at the same time and then poured back into smaller containers for convenience. Thinned down versions of SOLID COLOR may appear slightly different in color due to wood tone showing through. WEATHERBEATER BLENDING BASE is specifically designed to be mixed with WEATHERBEATER OIL BASE SOLID COLOR STAIN and should not be mixed with any other oil or latex product. Blending base is not a product to be tinted on a colorant machine used by itself.

**NOW APPLY STAIN**—For best results, use Sears EXTREME PAINT PAD, ROUGH SURFACE BRUSH or WEATHERBEATER BRUSH. Roller application is not recommended except with ROUGH SURFACE ROLLER over textured surfaces.

**APPLICATION:** Thorough mixing is essential. Stir periodically while using. For very porous or badly weathered wood, apply a second coat after 24 hours for increased protection and richer color. After application of entire home, brush out in a small inconspicuous spot and let dry to assure that STAIN is desired color.

Apply stain to entire length, work with wood grain, rather than against, to avoid overlap patterns. Avoid application of stain in direct sunlight. Follow the shade around the house. Apply at temperature 50-70°F.

539-293



# WEATHERBEATER

## BLENDING BASE for use with SEARS OIL BASE STAIN AND PRESERVATIVE

**WEATHERBEATER BLENDING BASE** used with **WEATHERBEATER OIL BASE SOLID COLOR STAIN** and **PRESERVATIVE** allows the flexibility of showing as much of the wood's natural grain as is desired, without losing the stain's important wood preservative and water sealing properties. By mixing **WEATHERBEATER OIL BASE STAIN** and the blending base, you can create your own version of semi-transparent colors. The more blending base mixed with the solid color stain, the more grain and wood tone that will show through. Special ingredients protect against moisture, wood rot and mildew.

### WHERE TO USE:

Recommended for new or previously stained wood. Not recommended for decks, docks, outdoor furniture and below ground wood.

#### BEFORE STAINING:

Prepare the surface properly for best results. The surface must be clean to achieve proper adhesion. Scrape and wire-brush weathered surfaces to remove all loose flakes. Brush away loose dust and dirt. Scrub with Sears **HEAVY DUTY CLEANER** to remove imbedded dirt. Rinse completely. Fill the cracks, open construction joints, knots, and holes with **WEATHERBEATER STAINABLE WOOD TEXTURE CAULK**.

**MILDEW:** It is important to remove mildew from the surface before staining by scrubbing (use a long-handled scrub brush) with a mixture of 1/3 cup Sears **HEAVY DUTY CLEANER**, 1 qt. household bleach and 3 qts. of warm water.  
**NOTE TO USER: DO NOT USE DETERGENTS CONTAINING AMMONIA. WEAR RUBBER GLOVES AND SAFETY GLASSES TO AVOID SKIN AND EYE CONTACT. DO NOT BREATHE FUMES.**

**MIXING RECOMMENDATION** Start with a small mixture one part blending base to one part **WEATHERBEATER OIL BASE SOLID COLOR STAIN** as a test to determine how much grain will show through. Brush out a small inconspicuous spot and let dry. Repeat the process, varying the amount of blending base until the desired transparency is achieved. Once the proper tone is set, mix enough to finish the entire job, thereby assuring color uniformity. It is recommended that total solution be mixed in a clean large container all at the same time and then poured back into smaller containers for convenience. Thinned down versions of **SOLID COLOR** may appear slightly different in color due to wood tone showing through. **WEATHERBEATER BLENDING BASE** is specifically designed to be mixed with **WEATHERBEATER OIL BASE SOLID COLOR STAIN** and should not be mixed with any other oil or latex product. Blending base is not a product to be tinted on a colorant machine nor used by itself.

**NOW APPLY STAIN**—For best results, use Sears **EXTERIOR PAINT PAD, ROUGH SURFACE BRUSH** or **WEATHERBEATER BRUSH**. Roller application is not recommended except with Sears **ROUGH SURFACE ROLLER** over textured surfaces.

**APPLICATION:** Thorough mixing is essential. Stir periodically while using. For very porous or badly weathered wood, apply a second coat after 24 hours for increased protection and richer color. Prior to application of entire home, brush out in a small inconspicuous spot and let dry to assure that **STAIN** is desired color.

Apply stain to entire length, work with wood grain, rather than against, to avoid overlap patterns. Avoid application of stain in direct sunlight. Follow the shade around the house. Apply at temperatures

above 60° F (16° C). Do not apply if temperatures below 45° F (7° C) are expected within 24 hours. True stain color will be evident after application when allowed to dry thoroughly.

**COVERAGE:** Porous woods—when mixed with **WEATHERBEATER OIL BASE STAIN** and **PRESERVATIVE** this product will cover up to 200 square feet (18 sq. meters) per gallon. For best protection and color uniformity, apply liberally. More coats give additional protection, but reveal less texture. Color will vary depending on number of coats and type of wood. To assure color uniformity over entire surface always buy enough stain to complete the whole job.

**CLEAN-UP:** Clean tools immediately after use with Sears **TIR-POLENE™** or **BRUSH CLEANER**.

**LIMITED WARRANTY**—This Sears **WEATHERBEATER** Blending Base when properly mixed with Sears **WEATHERBEATER OIL BASE STAIN** in accordance with label instructions, and when applied at a spreading rate not to exceed 200 square feet per gallon over a properly prepared surface, and provided that substrate and previously applied coatings remain intact, will have the following qualities:

#### FOR 3 YEARS FROM DATE OF APPLICATION:

- (1) No cracking
- (2) No peeling
- (3) No blistering

If stain fails to perform as specified above, contact your nearest Sears store and Sears will furnish without charge enough additional stain to correct the condition or, if you prefer, refund the purchase price. This warranty does not include labor or cost of labor for the application of any stain.

This warranty gives you specific legal rights, and you may also have other rights which may vary from state to state.  
SEARS, ROEBUCK AND CO., Sears Tower, BSC 41-3, Chicago, IL 60684

Keep from freezing. **LABORATORY TESTED FOR QUALITY**  
Sold by **SEARS, ROEBUCK AND CO., Chicago, IL 60684**

539-293