


CHARN



THIS PAINT
IS FREE OF LEAD HAZARDS

EPA Est. No. 88-NC-01
EPA Reg. No. 559-296

Sears

exterior

CLEAR FINISH AND WOOD PRESERVATIVE

Protects Against Moisture, Mildew and Rot
CONTAINS POLYURETHANE

KEEP OUT OF REACH OF CHILDREN
WARNING

ONE GALLON

SEARS CLEAR FINISH AND WOOD PRESERVATIVE is designed to protect shingles, shakes and rough hewn wood against moisture, wood rot and mildew. Without color being added this finish will enhance the appearance of natural wood by allowing both the texture and grain to show through. Provides an excellent base coat for stain or paint on bare wood. **SEARS CLEAR FINISH** is so water resistant that it exceeds water repellency requirements of Federal Specification TT-W-572b 37.

DIRECTION FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Recommended for new, green, stained or weathered wood. Not recommended for decks, docks, outdoor furniture or below ground wood.

BEFORE APPLICATION:

Prepare the surface properly for best results. The surface must be clean. Scrape and wire-brush weathered surfaces to remove all loose flakes. Brush away loose dust and dirt. Scrub with Sears **HEAVY DUTY CLEANER** to remove imbedded dirt. Rinse completely. Fill the cracks, open construction joints, knots, and holes with **WEATHERBEATER STAINABLE WOOD TEXTURE CAULK**.

MILDEW: It is important to remove mildew from the surface before staining by scrubbing (use a long-handled scrub brush) with a mixture of 1/3 cup Sears **HEAVY DUTY CLEANER**, 1 qt. household bleach and 3 qts. of warm water.

NOTE TO USER: DO NOT USE DETERGENTS CONTAINING AMMONIA. WEAR RUBBER GLOVES AND SAFETY GLASSES TO AVOID SKIN AND EYE CONTACT. DO NOT BREATHE FUMES.

NOW APPLY FINISH: For best results, use Sears **EXTERIOR PAINT PAD, ROUGH SURFACE BRUSH** or **WEATHERBEATER BRUSH**. Roller application is not recommended.

APPLICATION: Thorough mixing is essential; stir periodically while using. Prior to application of entire area brush out in a small inconspicuous spot and let dry to assure that clear finish brings out desired natural wood tone.

Apply clear finish to entire length, work with wood grain, rather than against, to avoid overlap patterns. Avoid application of finish in

direct sunlight. Follow the shade around the house. Apply at temperatures above 60° F (16° C). Do not apply if temperatures below 45° F (7° C) are expected within 24 hours.

SPREADING RATE: Porous woods—up to 200 square feet (18 sq. meters) per gallon. For best protection and wood tone uniformity, apply liberally. More coats give additional protection and gives a glossier finish. During application, intermediate rains.

CLEAN-UP: Clean tools immediately after use with Sears **TIR-POLENE** or **BRUSH CLEANER**.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING

CONTAINS PETROLEUM DISTILLATE

HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN, OR ON CLOTHING. May cause skin irritation. Close container after each use. Wear rubber gloves and protective clothing when handling freshly treated lumber. Wear a fresh air mask when spraying.

FIRST AID STATEMENT:

Change contaminated clothing at once. Wash skin with soap and water. If swallowed do not induce vomiting. Drink promptly a large quantity of milk, egg whites, gelatin solution, or if these are not available, drink large quantities of water. Get immediate medical attention. In case of eye contact, flush with water for 15 minutes and get medical attention.

ENVIRONMENTAL HAZARDS:

This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL OR CHEMICAL HAZARDS:

COMBUSTIBLE—Do not use, pour, spill, or store near heat or open flame. Avoid storage near feed or food products. Vapors will cause injury if adequate ventilation is not maintained.

STORAGE AND DISPOSAL:

Do not reuse empty container. Wrap container and put in trash collection. Do not use, pour, spill, or store near heat or open flame. Avoid storage near feed or food products.

KEEP OUT OF THE REACH OF CHILDREN

SEARS LABORATORY TESTED FOR QUALITY • PROTECT FROM FREEZING

©1984 SEARS, ROEBUCK AND COMPANY