

DIRECTIONS FOR USE

Apply PURITAN #5577 to the water in the cooling tower at the rate of 1/2 ounce per 100 gallons of water. Repeat applications should be made at 7 day intervals.

For more information contact:

W. H. Rorer & Co., Inc.

1000 North 17th Street

Philadelphia, Pa. 19103

Phone: 215-763-1000

For more information regarding PURITAN #5577, contact your local distributor or write to W. H. Rorer & Co., Inc., 1000 North 17th Street, Philadelphia, Pa. 19103. PURITAN #5577 is a registered trademark of W. H. Rorer & Co., Inc.

For more information regarding PURITAN #5577, contact your local distributor or write to W. H. Rorer & Co., Inc., 1000 North 17th Street, Philadelphia, Pa. 19103.

For more information contact:

W. H. Rorer & Co., Inc.

1000 North 17th Street

Philadelphia, Pa. 19103

Phone: 215-763-1000

**INDUSTRIAL RE-CIRCULATING WATER
COOLING TOWER ALGAECIDE**

PURITAN #5577

Control Algae and Slimes in Industrial Water Cooling Systems

Helps keep water cooling tower systems clean and free of visible algae slimes

ACTIVE INGREDIENTS:
Cyanuric Acid
Sodium Dichloroacetate
Water Soluble

DANGER

Keep out of reach of children. Do not use if container is open.



W. H. Rorer & Co., Inc.

ACCEPTED
February 15 1973
When PURITAN #5577 is used as directed it will aid in controlling algae and slimes, thereby preventing the development of unsanitary conditions in industrial water cooling towers. It will also help to produce clean water for industrial use.

UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND ROENTICIDE ACT
FOR ECONOMIC POISON REGISTER
UNDER NO. 277-241

DANGER

FIRST AID