

NET CONTENTS 5 GALLONS

CREOSOTE OIL

Active Ingredients

Coal Tar Hydrocarbons 50%

Coal Tar Acids 15%

Other Ingredients 35%

Wt.

8 MAY 1971
Hazard Division
EPA

DIRECTIONS FOR USE

An excellent wood preservative giving low cost protection against decay and insect attack. Creosote oil should be applied evenly in the form of a spray or dip. It can also be painted on with an ordinary brush. Allow the oil to penetrate and make occasional applications before placing underground.

Will prolong the life of timber several times that of untreated wood.

Cut out places where decay or rot has started before application.

Fence posts, poles, foundation timbers and heavy wooden timbers should be free of bark, dry and well seasoned and immersed in product for a period of 24 to 48 hours to be an effective wood preserver.

Lumber intended to be in contact with the soil should be dipped for a minimum of 3 minutes or treated by the brush or spray method, receive two or more coats of the product.

CAUTION

Do not use inside dairy barns, silos, or other structures where it may contact food, feed or livestock.

AS A STAIN

Creosote oil also may be used as a stain for building exteriors, fences, and other wooden objects which are exposed to the weather, giving a light brown color. Due to its great penetrating properties creosote oil seals the wood and keeps out moisture, thereby increasing the life of the wood.

WARNING:

KEEP OUT OF REACH OF CHILDREN

MAY BE LETHAL IF SWALLOWED OR ABSORBED THROUGH SKIN. MAY PRODUCE SEVERE BURNS. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling.

In case of contact, immediately flush eyes or skin with water for 15 minutes. For cases of other than eye contact, remove clothing and wash with soap and water.

If swallowed, drink plenty of water. Do not induce vomiting. Consult a physician immediately.

The product is toxic to fish and aquatic animals. Do not discharge into water or dispose of wastes.

Apply this product only as directed on this label.

Combustible material. Do not use near open flame.

Do not reuse empty container. Return to dealer for proper disposal or burning. Do not place in incinerator or burn.



EPA REG NO 551218

EPA EST 551MA1

CREOSOTE OIL

5 GALLONS