

ACCEPTED
OCT 20 1981
for the Federal Government
under the Federal Acquisition Regulation
48 CFR 101-11.6

SHERWIN
Williams



CLEAR WOOD FINISH
WITH PRESERVATIVE
CLEAR
Vehicle by Weight 100.00%
Alkyd Resin modified
with Linoleic, Lin-
oleic, Oleic and
Stearic Acids 18.28%
Driers and
Additives 1.43%
Mineral Spins 81.31%
Bis (tributyltin)
Oxide 0.34%
Bi (trichloromethyl)
Thioetheroxide 0.66%
100.00% 100.00%
A-D 81
A17 C 2
NON-PHOTOCHEMICALLY
REACTIVE

Protects the Natural Beauty of Wood

CLEAR WOOD FINISH WITH PRESERVATIVE

For Wood Siding, Shakes, and Shingles
Water Repellent • Protects Wood from Rot, Deterioration, and Mildew

ONE GALLON

CLEAR 104-5749

3.785 liters

KEEP OUT OF THE REACH OF CHILDREN.

WARNING! COMBUSTIBLE. HARMFUL OR FATAL IF SWALLOWED
OR ABSORBED THROUGH THE SKIN. CAUSES EYE AND SKIN IRRITATION.
See back panel for additional Precautionary Statements

ACTIVE INGREDIENTS
Bis (tributyltin) oxide 34%
Fos-phol (N-[[[trichloromethyl]oxy]phthalimide]) 66%
INERT INGREDIENTS 0.00%
TOTAL 100.00%
EPA Reg. No. 577-538 EPA Est. No. 577-CA-1, 577-CA-2, 577-CA-1,
577-IL-1, 577-MO-1, 577-NJ-1, 577-TX-1

Protects the Natural Beauty of Wood CLEAR WOOD FINISH WITH PRESERVATIVE

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

A clear, water repellent wood preservative designed for maximum penetration on bare and unfinished exterior wood surfaces. It protects from water damage, rot, mildew, and deterioration. Clear Wood Finish can be used either by itself or under other finished coats to prolong the life of the wood.

Clear Wood Finish contains IBTO, a wood preservative, and FOPEI, a mildewicide and fungicide. Its water repellency allows water to bead up and roll off.

STORAGE AND DISPOSAL: Do not use or store inside the home. Do not reuse empty container. Wrap container and put in trash collection. Keep away from food and feed. Do not transfer contents to other containers for storage.

SURFACE PREPARATION:

Clear Wood Finish may be applied to any new or weathered uncoated exterior shingles, shakes, rough sawn or smooth siding, decks and fences. Use on Pine, Fir, Redwood or Cedar Woods or plywood. Some smooth new lumber should be sanded to open the pores to permit proper penetration or should be allowed to weather several months. If Clear Wood Finish is to be covered with a finish coat, allow it to dry thoroughly (at least 24 hours) before applying the top coat. If a colored natural appearance is desired, SHERWIN WILLIAMS SEMI-TRANSPARENT WOOD PRESERVATIVE STAIN is recommended as a top coat. If a latex finish is desired, an alkyl exterior wood primer must be applied first. Application of top coats over this product may result in areas of high gloss which will become more uniform with weathering.

Do Not Apply to Previously Painted stained, varnished or any sealed surfaces. The old finish must be completely removed for Clear Wood Finish to penetrate effectively. Do not use on composition board or wood roofs.

APPLICATION:

Clear Wood Finish may be applied by brush, roller, or airless spray. Smaller pieces may be dipped. Apply a full coat and let the wood absorb as much as it will to get the best protection. Do not use excessive coats which may result in a gloss finish. Allow 24 to 48 hours drying time depending on temperature and humidity. Covers 150 to 250 sq. ft. per gallon (4 to 6 sq. m per l) depending on porosity of wood. Clean up brushes, rollers, and spray equipment with mineral spirits.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMAN AND DOMESTIC ANIMALS WARNING!

HARMFUL OR FATAL IF SWALLOWED. If swallowed, DO NOT INDUCE VOMITING. CALL PHYSICIAN AT ONCE. Use only in well ventilated area. Do not breathe vapor or spray mist. When spraying wear a vapor/particulate respirator approved under NIOSH/MESA SCHEDULE 23C. Do not get in eyes or on skin or clothing. Wear rubber gloves and protective clothing when applying or handling freshly treated lumber.

FIRST AID: If on skin wash with soap and water. Remove and wash contaminated clothing before re-use. If in eyes immediately flood with water for at least 15 minutes. Call a physician. If swallowed, do not induce vomiting. Call a physician.

ENVIRONMENTAL HAZARDS: This product is toxic to fish and wildlife. Do not apply directly to lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of waste.

PHYSICAL OR CHEMICAL HAZARDS: COMBUSTIBLE. To avoid spontaneous combustion soak oily cloths in water after use or place in a closed metal container away from buildings and other combustible materials. Do not use or store near heat or open flame.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF THE REACH OF CHILDREN.**

WP 4 51

SATISFACTION GUARANTEED

This coating is a result of extensive research and testing by The Sherwin-Williams Company. We guarantee your satisfaction in the use of this product or your purchase price will be cheerfully refunded.

© 1981 The Sherwin-Williams Company

**SHERWIN
Williams**

The Sherwin-Williams Company
Cleveland, Ohio 44101

ACCEPTED

OCT 26 1981

Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 577-535