UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460

DEC **2006**



SEPA Reference Office of Pesticide Programs

The Sherwin-Williams Company Environmental, Health and Regulatory Services 101 Prospect Avenue, N. W. Cleveland, OH 44115-1075

Attention: Madelyn K. Harding, Corporate Manager

Regulatory Affairs

Subject: Semi-Transparent Wood Preservative Stain

EPA Registration No. 577-539

Amendment Dated September 29, 2006

The amendment, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, is acceptable.

- Revised Product Labeling

A stamped copy of the "accepted" product labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely

Marshall Swindell

Product Manager (33)

Regulatory Management Branch 1 Antimerobials Division (7510P)

FRONT PANEL

Sherwin-Williams Semi-Transparent Wood Preservative Clear Base A14T5

Exterior Oil Alkyd

for decks and wood siding quality performance

- · for new or weathered wood
- highlights natural grain & texture of wood
- superior penetrating stain

OR

- Exterior Alkyd
- Water Repellent
- Protects Wood from Rot, Deterioration, and Mildew

IPRODUCT IDENTIFICATION NUMBERS1

ACCEPTED with COMMENTS EPA Letter Dated: For Semitransparent preservatives:

Must Be Tinted Before Using

For Clear Preservative: Do Not Tint

Under the Federal Insecticide, Ringicide, and Rodenficide Act as amended, for the pesticide, registered under EPA Reg. No.

KEEP OUT OF REACH OF CHILDREN. WARNING! COMBUSTIBLE! VAPOR HARMFUL. IRRITATES EYES, SKIN AND RESPIRATORY TRACT. HARMFUL OR FATAL IF SWALLOWED

See back panel for additional Precautionary Statements

For Semitransparent preservatives:

3.73 liter / 3 at 1 pt 14 fl oz

BEFORE COLOR IS ADDED

For Clear Preservative:

1 U.S. Gal

3.781.

ACTIVE INGREDIENTS

Bis(tri-n-butyltin)oxide	0.34%
Folpet [N-trichloromethylthio)phthalimide]	0.66%
WEDT WORES TO	
INERT INGREDIENTS	99.00%

TOTAL 100.00%

Contains petroleum distillates

EPA Reg. No. 577-539

EPA Est. No. 577-CA-1, 577-GA-1, 577-IL-1, 577-MD-1, 577-NJ-1, 577-TX-1, 577-OH-1, 577-KY-1, 577-NC-1, 577-FL-1, 577-IL-2, 577-KS-1, 577-CA-3

BACK OR SIDE PANEL

CAS No.	Ingredient
64742-47-8	Mineral Spirits
Unknown	Alkyd Polymer
14807-96-6	Talc

VOC:

ca 628-673 gms/L - 5.24-5.6 1 lbs/gal

NON-PHOTOCHEMICALLY REACTIVE DO NOT THIN

H	HEALTH	2
F	FLAMMABILITY	2
R	REACTIVITY	0
	PERSONAL PROTECTION	

FIRST AID

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.

IF SWALLOWED: Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

HAVE THE PRODUCT CONTAINER OR LABEL WITH YOU WHEN CALLING A POISON CONTROL CENTER OR DOCTOR, OR GOING FOR TREATMENT.

For additional information in case of emergency, call the National Pesticide Information Center toll free at 1-800-858-7378.

Note to Physician

Contains petroleum distillate - vomiting may cause aspiration pneumonia.

g:\fifra\labels\stores a14t5\539 amend 20060928.doc

PRECAUTIONARY STATEMENT HAZAPDS TO HUMAN AND DOMESTIC ANIMALS WARNING! HARMFUL OR FATAL IF SWALLOWED

Warning, Causes skin irritation. Harmful if inhaled. Do not get on skin or on clothing. Avoid breathing spray mist.

Contents are combustible. Keep away from heat and open flame. CONTAINS ALIPHATIC HYDROCARBONS. VAPOR HARMFUL. Use only with adequate ventilation. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Keep container closed when not in use.

ENVIRONMENTAL HAZARDS

This chemical is highly toxic to fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other water unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your state Water Board or Regional Office of EPA.PHYSICAL OR CHEMICAL HAZARDS

To avoid spontaneous combustion, soak oily cloths in water after use or place in a closed metal container away from buildings and other combustible materials. Combustible. Do not use or store near heat or open flame.

PERSONAL PROTECTION EQUIPMENT (PPE) Applicators and all other handlers must wear:

- Coveralls over short sleeved shirt and short pants
- Socks and chemical resistant footwear
- Chemical-resistant gloves, such as barrier laminate, nitrile rulbber, neoprene rubber or viton
- Respoirator with dust/mist filter (MSHA/NIOCH approval number prefix TC-21C) or a NIOSH approved respirator with any R, P, or HE filter.

with COMMENT'S
EPA Letter Dated:

Under the Federal Interded, Ringicide, and Federal Interded, and Russide, Act as amended, for the pessucide, registered under LPA Reg. No.

USER SAFETY RECOMMENDATIONS –Users should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. Users should remove clothing immediately if product gets inside. Then wash thoroughly and put on clean clothing. Users should remove clothing immediately after handing this product. As soon as possible, wash thoroughly.

NOTICE: DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

For Semitransparent preservatives:

[Optional Product Name] Beautifies and highlights the rich grain and texture of wood. Provides uniform and natural color plus protection. Water repellent. Protects from rot, deterioration, and mildew. For above ground use on exterior wood. Covers unfinished or previously stained (semi-transparent only) wood siding, shingles, shakes, fences, railings, picnic tables, furniture, decks and floors. A semi-transparent wood preservative stain designed for maximum penetration on bare exterior wood surfaces. Also provides for protection from water damage, rot, mildew, and deterioration. [PRODUCT NAME] contains TBTO and FOLPET - wood preservative, mildewcide and fungicide. Its water repellency allows water to bead up and roll off.

OR For Clear Preservative:

FOR ABOVE-GROUND USE ON WOOD EXPOSED TO MOISTURE AND WEATHER.

Beautifies and highlights the rich grain and texture of wood. A clear_wood preservative designed for maximum penetration on bare exterior wood surfaces. Also provides for protection from water damage, rot, mildew, and deterioration. Covers unfinished wood siding, shingles, shakes, fences, railings, picnic tables, furniture, decks and floors. For above ground use on wood exposed to moisture and weather. [PRODUCT NAME] contains TBTO and FOLPET - wood preservative, mildewcide and fungicide. Its water repellency allows water to bead up and roll off.

DIRECTIONS FOR USE--It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.


Do not apply this product in a way that it will contact workers or other persons or pets. . Do not allow this product to drift.

STORAGE AND LISPOSAL -Do not contaminate water, food, or feed by storage and discosal

Pesticide Storage: Store in cool and dry place away from heat and flame. Do not transfer to other containers for storage.

Pesticide Disposal: Wastes resulting from the use of this product may be objected of on site or at an approved waste disposal facility.

Container Disposal: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of container in a sanitary landfill, or by other procedures approved by state and local authorities.



For Clear Preservative:

SURFACE PREPARATION

Remove dirt and debris. Sand down badly weathered surfaces to fresh wood. Remove previous finishes

Remove mildew by scrubbing with a mixture of one quart liquid bleach in three quarts of water. Wear protective glasses or goggles and waterproof gloves. Quickly wash off mixture that touches skin. Do not add detergents or ammonia to bleach/water mixture.

APPLICATION

Stir thoroughly before and occasionally during use. Under normal environmental and application conditions, thinning--not required. Use at 50°F and above. Apply uniformly with brush, pad or spray. Covers 100 to 200 square feet per gallon on rough or porous surfaces. Up to 350 square feetper gallon on smooth, non-porous surfaces. Allow to dry 24 hours under normal drying conditions (70°F & 50% humidity) before recoating or walking on. Important Minimize lapping by: 1) Do not apply in direct sun or on hot surface. 2) Always apply into a wet edge. 3) Apply up and down along vertical siding and across horizontal siding.

4) Use two coats on badly weathered or unfinished wood and whenever prominent, unsightly lap marks appear on first coat. Do not use on composition board or wood roofs. Be sure decks and floors are either bare or well worn before coating. Please note: Coatings wear under foot traffic which may leave a different appearance in the wear area versus unworn areas.

CLEAN UP - Use a paint thinner or mineral spirits for cleaning tools and equipment following manufacturer's safety instructions. Any solvent soaked material, such as rags, should be placed in water when discarded.

OR

For Semitransparent preservatives:

STAINING INSTRUCTIONS

Surface Preparation: Remove dirt and debris. Sand down badly weathered surface to fresh wood. Remove mildew by scrubbing with a mixture of one quart household liquid bleach to three quarts of water. Wear protective glasses or goggles and waterproof gloves. Quickly wash off any of the solution that touches your skin. Do not mix bleach and detergents. Previous finishes, other than semi-transparent stain, must be removed. Application - Stir thoroughly before and occasionally during use. Use at 50°F (10°C) and above. Apply uniformly with brush, pad or spray. Cover 100 to 200 sq. ft. (9 to 19 sq. meters) per gallon on rough or porous surfaces. Up to 350 sq. ft. (33 sq. meters) per gallon on smooth, non-porous wood surfaces.

Important! All stains tend to lap mark (darker color where two freshly painted areas overlap). Minimize laps by: 1) Don't stain in direct sun or on hot surfaces. 2) Always stain into a wet edge—stain up and down along vertical siding and across horizontal siding. 3 Use two coats on badly weathered or unfinished wood, and whenever prominent unsightly lap marks appear on first coat.

Do not use on composition board or wood roofs. Be sure decks and floors are either bare or well worn before staining. Please note: Stains wear under foot traffic leaving a different color in the wear area versus unworn areas. Allow 24 hours drying if a second coat is necessary or before walking on. **CLEAN UP** - Use paint thinner or mineral spirits for cleaning tools and equipment following manufacturer's safety instructions. Any solvent soaked material such as rags should be placed in water when discarded.

ACCEPTED
with COMMENTS
EPA Letter Dated:

Under the Federal Insecticide, Fungicide, and Rodenticide act as amended, for the pesticide, registered under EPA Reg. No.

SATISFACTION GUARANTEED
This coating is a result of extensive research and testing by
. We guarantee your satisfaction in the use of this
product or your purchase price will be cheerfully refunded.

Or

[COMPANY OR DISTRIBUTOR NAME] LIMITED WARRANTY

This product will perform as stated on this label following label instructions. If the product fails to meet this warranty, you will be supplied additional product equal to the quantity purchased or, at your option, a refund of the purchase price of the product will be made at the place of purchase.

The Sherwin-Williams Company Cleveland, Ohio 44115 Phone number 1-216-566-2000 With COMMENTS
EPA Lieffer Dated:

Under the Federal Insecticities
amended, for the pesiticide,
registered under EPA Reg. No.

577-539