UNITED STATES

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

WASHINGTON, D.C. 20460

OCT 1 2 2010

OFFICE OF PREVENTION, PESTICIDES AND TOXIC SUBSTANCES

The Sherwin-Williams Company 101 West Prospect Avenue Cleveland, OH 44115-1075

Subject: Semi-Transparent Wood Preservative Stain EPA Registration Number 577-539 Your Notification Dated August 6th, 2010 EPA Received Date August 10th, 2010

The notification referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, FIFRA, as amended, to update the Container Disposal statements as per PR Notice 2007-4, is acceptable.

10/12/2010

A copy of the notification has been made part of the file.

If you have questions concerning this letter, please contact Karen M. Leavy at (703)-308-6237.

Sincerely,

Marshall Swindell Product Manager 33 Regulatory Management Branch I Antimicrobials Division(7510P)

United States Environmer Office of Pesticide I			egistration Amendment		OOP Identifier Number
			Antenditient		
LPA Washington, Application for Pesticide:	DC 20400		Juliel		
		Section I			<u> </u>
1. Company/Product Number 577-539			2. EPA Product Manager M. Swindell		3. Proposed Classification
4. Company/Product (Name) Semi-Transparent Wood P	reservative Stair	1	РМ# 33		X None 🗆 Restricted
5. Name and Address of Applicant (Include) THE SHERWIN-WILLIAMS COMPA 101 WEST PROSPECT AVENUE CLEVELAND, OH 44115-1075			6. Expedited Review. In a product is similar or ident EPA Reg. No.	ical in compos	Ū.
□ Check if this is a new address			Product Name		
		Section I			
XX Amendment – Explain belo	W	L	Final printed labe Dated	els in respor	ise to Agency letter
Resubmission in response to A	gency letter dated 1	/21/05	"Me Too" Applica	ation.	<u></u> -
Notification – Explain below.		Oti	her – explain below.		
Explanation: Use additional page(s) if necessary. (For	section I and Se	ction II.)		
Label Amendment to comply v					
		Section II	I		
1. Material This Product Will Be			Weter Calific Deal		2. Type of Container
Child Resistant Packaging □ Yes*	Unit Packaging		Water Soluble Pack	caging	□ Metal
□ No	□ No		\square No		□ Plastic
Certification must be submitted.	If Yes, Unit Package w	No. per rt. Container		per ntainer	□ Glass □ Paper □ Other (Specify)
3. Location of Net Contents Inform	ation	4. Size(s) of R	of Retail Container 5. Location of Label Directions		
Label Container				🗆 On Lab	beling accompanying product
6. Manner in Which Label Is Affixe		Lithograph Paper glued Stenciled	🗆 Other ()
		Section IV		·····	
1. Contact Point (Complete items directly below for identifi Name Madelyn K. Harding	cation of individual to be contac	Title	s this application.) egulatory Affairs	Telephon (216) 56	e No. (Include Area Code) 6-2630
Certification I certify that the statements I have n					
any knowingly false or misleading state 2. Signature	ment may be punisha	ble by fine or imp 3. Title	risonment of both unde		laws So Date Application Received
madelign KH	and '	Manager, Re	egulatory Affairs		
4. Typed Name		4. Date			ις (ί ιιις (
Madelyn K. Harding		8-6-2010			ι ιζις ιζιςι

EPA Form 8570-1 (Rev. 12-90 Previous editions are obsolete. White – EPA File Copy (Original) Yellow Applicant copy g\FIFRA\Form 8570-1 Application\577-539 Form 8570-1 No. 155107.doc

 \mathbf{x}'

l

2	7
	•



Environmental, Occupational Health & Regulatory Services 101 Prospect Avenue NW Cleveland, Ohio 44115-1075 Facsimile: (216) 566-2730

BY FEDERAL EXPRESS

August 6, 2010

Mr. Marshall Swindell (PM 33) Document Processing Desk (NOTIF) Office of Pesticide Programs (7504P) U. S. Environmental Protection Agency Room S-4900, One Potomac Yard 2777 South Crystal Drive Arlington, Virginia 22202-4501

> RE: EPA Registration Number 577-539, Semi-Transparent Wood Preservative Stain Application for Pesticide Amendment Per PR Notice 2007-4: Pesticide Management and Disposal; Standards for Pesticide Containers & Containment

> > **QUALIFIES FOR FAST TRACK REVIEW**

Dear Mr. Swindell,

This letter with the attached Application serve as Application for an Amendment to the label of EPA Registration Numbers 577-5 39 to comply with PR Notice 2007-4 on Container Disposal Statements.


This submission includes one copy showing the new Container Disposal statement plus five "clean" copies of the label.

Thank you for your prompt attention to this matter. If you have any questions regarding this submission, please do not hesitate to contact me at 216-566-2630.

Sincerely. Madelep & Hard'

Madelyn K. Harding, Senior Corporate Manager Regulatory Affairs

Attachment:	Application for Amendment of EPA Reg. No. 577-539
	Highlighted Label Copy showing proposed change
	Five Clean Copies of Proposed Label



Label Amendment of 8-06-10 Page 1 of 4

FRONT PANEL

P

Sherwin-Williams Semi-Transparent Wood Preservative Clear Base A14T5

Exterior Oil Alkyd

for decks and wood siding quality performance

- for new or weathered wood
- highlights natural grain & texture of wood
- superior penetrating stain

OR

- Exterior Alkyd
- Water Repellent
- Protects Wood from Rot, Deterioration, and Mildew

[PRODUCT IDENTIFICATION NUMBERS]

For Semitransparent preservatives: Must Be Tinted Before Using

For Clear Preservative: Do Not Tint

KEEP OUT OF REACH OF CHILDREN. WARNING! COMBUSTIBLE! VAPOR HARMFUL. IRRITATES EYES, SKIN AND RESPIRATORY TRACT. HARMFUL OR FATAL IF SWALLOWED

See back panel for additional Precautionary Statements

For Semitransparent preservatives: 3.73 liter / 3 qt 1 pt 14 fl oz

For Clear Preservative: 1 U.S Gal 3.78 L

υ	ిం		0 0 0		j.		J.		ر
ပ် ၁ ပ	່ວ ວິວ ວິວ	ပ	3000 0000	0000	000	S	د ر د	ς ι ι	ιί
	ື		ບວັວ	<u> </u>	دن ر		ر: س ر ز	J	د,

BEFORE COLOR IS ADDED

0000	రు	లు
0	0 0	ر `ن
చింది	<u>ວ</u> ບ	ാ
5	ິດປີ	2000
0000	õ	ر د ر د

ACTIVE INGREDIENTS

Bis(tri-n-butyltin)oxide	0.34%
Folpet [N-trichloromethylthio)phthalimide]	
INERT INGREDIENTS	
TOTAL	

Contains petroleum distillates

EPA Reg. No. 577-539

EPA Est. No. 577-CA-1, 577-GA-1, 577-IL-1, 577-MD-1, 577-NJ-1, 577-TX-1, 577-OH-1, 577-KY-1, 577-NC-1, 577-FL-1, 577-IL-2, 577-KS-1, 577-CA-3

BACK OR SIDE PANEL

<u>CAS No.</u> 64742-47-8 Unknown 14807-96-6	<u>Ingredient</u> Mineral Spirits Alkyd Polymer Talc
VOC:	ca 628-673 gms/L - 5.24-5.6 1 lbs/gal
JON-PHOTO OO NOT THIN	CHEMICALLY REACTIVE

Н	HEALTH	2
F	FLAMMABILITY	2
R	REACTIVITY	0
	PERSONAL PROTECTION	

FIRST AID

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.

IF SWALLOWED: Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person. *IF IN EYES:* Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.

Call a poison control center or doctor. F ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately

JF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

HAVE THE PRODUCT CONTAINER OR LABEL WITH YOU WHEN CALLING A POISON CONTROL CENTER OR DOCTOR, OR GOING FOR TREATMENT. For additional information in case of emergency, call the National Pesticide Information Center toll free at 1-800-858-7378.

Note to Physician

Contains petroleum distillate - vomiting may cause aspiration pneumonia.

PRECAUTIONARY STATEMENT
HAZARDS TO HUMAN AND DOMESTIC ANIMALS
WARNING! HARMEOL ORFATAL IF SWALLOWED
Warning. Causes skin irritation. Harmful if inຫຼືaied. De not get on ຮຸkin or on
clothing. Avoid breathing spray mist. 🌼 🖓 ບັນ 🖓 🖓 ເຊິ່ 🖓 ເຊິ່ 🖓 ເຊິ່ ເຊິ່ ເຊິ່ ເຊິ່ ເຊິ່ ເຊິ່ ເຊິ່ ເຊິ່
Contents are combustible. Keep away from heat and open flame. CONTAINS
ALIPHATIC HYDROCARBONS. VAPOR HARMFUL, Use only with adequate
ventilation. If you experience eye watering, headachຮູ້ຮູ້, or ຜູ້ເzີ້z ness, increase fresh
air, or wear respiratory protection (NIOSH approved) or leave the area. Keep
container closed when not in use. ອັດລະບໍ່ດີ ເຊິ່ງ
ENVIRONMENTAL HAZARDS
This chemical is highly toxic to fish and aquatic invertebrates. Do not discharge
effluent containing this product into lakes, streams, ponds, estuaries, oceans or other
water unless in accordance with the requirements of a National Pollution Discharge
Elimination System (NPDES) permit and the permitting authority has been notified in
writing prior to discharge. Do not discharge effluent containing this product to sewer
systems without previously notifying the local sewage treatment plant authority. For
guidance contact your state Water Board or Regional Office of EPA.PHYSICAL OR
CHEMICAL HAZARDS
To avoid spontaneous combustion, soak oily cloths in water after use or place in a
closed metal container away from buildings and other combustible materials.
Combustible. Do not use or store near heat or open flame.
DO NOT TAKE INTERNALLY
KEEP OUT OF THE REACH OF CHILDREN

PERSONAL PROTECTION EQUIPMENT (PPE) Applicators and all other handlers must wear:

- Coveralls over short sleeved shirt and short pants
- Socks and chemical resistant footwear
- Chemical-resistant gloves, such as barrier laminate, nitrile rulbber, neoprene rubber or viton
- Respoirator with dust/mist filter (MSHA/NIOCH approval number prefix TC-21C) or a NIOSH approved respirator with any R, P, or HE filter.

USER SAFETY RECOMMENDATIONS –Users should wash hands before eating, .drinking, chewing gum, using tobacco, or using the toilet. Users should remove clothing immediately if product gets inside. Then wash thoroughly and put on clean clothing. Users should remove clothing immediately after handing this product. As soon as possible, wash thoroughly.

NOTICE: DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

For Semitransparent preservatives:

FOR ABOVE-GROUND USE ON WOOD EXPOSED TO MOISTURE AND WEATHER.

Beautifies and highlights the rich grain and texture of wood. A semi-transparent wood preservative stain designed for maximum penetration on bare exterior wood surfaces. Also provides for protection from water damage, rot, mildew, and deterioration. Covers unfinished or previously stained (semi-transparent only) wood siding, shingles, shakes, fences, railings, picnic tables, furniture, decks and floors. For above ground use on wood exposed to moisture and weather. [*PRODUCT NAME*] contains TBTO and FOLPET - wood preservative, mildewcide and fungicide. Its water repellency allows water to bead up and roll off.

OR For Clear Preservative:

FOR ABOVE-GROUND USE ON WOOD EXPOSED TO MOISTURE AND WEATHER.

Beautifies and highlights the rich grain and texture of wood. A clear_wood preservative designed for maximum penetration on bare exterior wood surfaces. Also provides for protection from water damage, rot, mildew, and deterioration. Covers unfinished wood siding, shingles, shakes, fences, railings, picnic tables, furniture, decks and floors. For above ground use on wood exposed to moisture and weather. [*PRODUCT NAME*] contains TBTO and FOLPET - wood preservative, mildewcide and fungicide. Its water repellency allows water to bead up and roll off.

DIRECTIONS FOR USE--It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL -Do not contaminate water, food, or eee by storage and disposal.

0000 0000

Pesticide Storage: Store in cool and dry place away from heat and flame. Do not transfer to other containers for storage.

Pesticide Disposal: Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

Container Disposal: As control on the control of the control one of the control on Ingle these contention of a nation encoding. Then affer the recycling: The control of reductors and dispose of to a secolary leadable of by other procedures approved by state and tecal authomics.

İnfigile America'n Sicila Sientik. ™lash-difter fan Kerlynsing om nenamdiften inge-en plandgine -sing 918965: of stelf%jiner in Soonders, len difter of by Offici (philitetic-signifterie) 8-ni ander softwirtics

SURFACE PREPARATION

Remove dirt and debris. Sand down badly weathered surfaces to fresh wood. Remove previous finishes

Remove mildew by scrubbing with a mixture of one quart liquid bleach in three quarts of water. Wear protective glasses or goggles and waterproof gloves. Quickly wash off mixture that touches skin. Do not add detergents or ammonia to bleach/water mixture.

APPLICATION

Stir thoroughly before and occasionally during use. Under normal environmental and application conditions, thinning--not required. Use at 50°F and above. Apply informly with brush, pad or spray. Covers 100 to 200 square feet per gallon on rough or porous surfaces. Up to 350 square feetper gallon on smooth, non-porous surfaces. Allow to dry 24 hours under normal drying conditions (70°F & 50% humidity) before recoating or walking on. **Important** Minimize lapping by: 1) Do not apply in direct sun or on hot surface. 2) Always apply into a wet edge. 3) Apply up and down along vertical siding and across horizontal siding.

4) Use two coats on badly weathered or unfinished wood and whenever prominent, unsightly lap marks appear on first coat. Do not use on composition board or wood roofs. Be sure decks and floors are either bare or well worn before coating. Please note: Coatings wear under foot traffic which may leave a different appearance in the wear area versus unworn areas.

CLEAN UP - Use a paint thinner or mineral spirits for cleaning tools and equipment following manufacturer's safety instructions. Any solvent soaked material, such as rags, should be placed in water when discarded.

OR

For Semitransparent preservatives:

ບໍ່ລັດ ວິດ ລິບອີບ ລັດ STAINING INSTRUCTIONS Surface Preparation: Remove dirt and debris. Sand down badly weathered surface to fresh wood. Remove mildew by scrubbing with a mixture of one guart household liquid bleach to three guarts of water. Wear protective glasses or goggles and waterproof gloves. Quickly wash off any of the solution that touches your skin. Do not mix bleach and detergents. Previous finishes, other than seim-transparent stain, must ວັວບວ ວັ be removed. Application - Stir thoroughly before and occasionally during use. Use at 50°F (10°C) and above. Apply uniformly with brush, pad or spray. Cover 100 to 200 sq. ft. (9 to 19 sq. meters) per gallon on rough or porous surfaces. Up to 350 sq. ft. (33 sq. meters) per gallon on smooth, non-porous wood surfaces. Important! All stains tend to lap mark (darker color where two freshly painted areas overlap). Minimize laps by: 1) Don't stain in direct sun or on hot surfaces. 2) Always stain into a wet edge-stain up and down along vertical siding and across horizontal siding. 3 Use two coats on badly weathered or unfinished wood, and whenever prominent unsightly lap marks appear on first coat. Do not use on composition board or wood roofs. Be sure decks and floors are either bare or well worn before staining. Please note: Stains wear under foot traffic leaving a different color in the wear area versus unworn areas. Allow 24 hours drying if a second coat is necessary or before walking on. CLEAN UP - Use paint thinner or mineral spirits for cleaning tools and equipment following manufacturer's safety instructions. Any solvent soaked material such as

rags should be placed in water when discarded.

SATISFACTION GUARANTEED

This coating is a result of extensive research and testing by ____

_____. We guarantee your satisfaction in the use of this product or your purchase price will be cheerfully refunded.

Or

[COMPANY OR DISTRIBUTOR NAME] LIMITED WARRANTY This product will perform as stated on this label following label instructions. If the product fails to meet this warranty, you will be supplied additional product equal to the quantity purchased or, at your option, a refund of the purchase price of the product will be made at the place of purchase.

The Sherwin-Williams Company Cleveland, Ohio 44115 Phone number 1-216-566-2000