

577-556

12/08/2010

1/4



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

WASHINGTON, D.C. 20460

DEC - 8 2010

OFFICE OF
PREVENTION, PESTICIDES
AND TOXIC SUBSTANCES

The Sherwin-Williams Company
101 West Prospect Avenue
Cleveland, OH 44115-1075

Subject: Premium Grade Soft Copper No. 1
EPA Registration Number 577-556
Your Amendment Dated November 23rd, 2010
EPA Received Date November 23rd, 2010

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, FIFRA, as amended, to revise the product labeling, is acceptable.

A stamped copy of the labeling is enclosed for your records.

If you have questions concerning this letter, please contact Karen M. Leavy at (703)-308-6237.

Sincerely,

A handwritten signature in cursive script that reads "M Swindell".

Marshall Swindell
Product Manager 33
Regulatory Management Branch I
Antimicrobials Division(7510P)

PREMIUM GRADE SOFT COPPER NO.1

N50 R101

ACTIVE INGREDIENT

CUPROUS OXIDE	23.00%
INERT INGREDIENTS:	77.00%
TOTAL	100 %

This product contains petroleum distillates.

Equivalent to 20% metallic copper

KEEP OUT OF REACH OF CHILDREN

Warning!

Combustible! Vapor Harmful. Irritates Eyes, Skin and Respiratory Tract.
See Side Panel for Additional Precautionary Statements

EPA Registration No. 577-556
EPA Est. No. 577-VA-01

50 Gallons Net Contents

**ACCEPTED
with COMMENTS
EPA Letter Dated:**

DEC - 8 2010

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No. 577-556

**SEAGUARD#1 PREMIUM GRADE ANTI-FOULING
"SOFT" COPPER FREE ERODING FORMULATION
DIRECTIONS FOR USE**

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Recommended: Seaguard Premium Grade Anti-fouling, Soft Copper is to be used on wood surfaces. Seaguard Premium Grade Anti-fouling is a soft copper formulation that allows the coating to dissolve freely, thus preventing any residual film build-up. The anti-fouling properties are uniquely tailored for the east coast of the United States.

Surface Preparation: For wood surfaces-clean surface thoroughly with water and scrub with stiff bristle brush. Any fouling residue should be removed with a wire brush before applying Seaguard Premium Grade Anti-fouling.

Application: Seaguard Premium Grade Anti-fouling is formulated to be applied by spray, brush, or roller. If applied by spray, an agitator equipped spray pot should be used, with the agitator running just fast enough to keep the anti-fouling pigments in uniform suspension. Thinning is not usually necessary, but Seaguard No. 800 Thinner [Sherwin-Williams R2K4 150 Flash Naphtha] may be used. For optimum anti-fouling performance, 2 coats of Premium Grade Anti-fouling should be applied at 2.0 mil Dry Film Thickness each. Vessel launching should be made within 7 days of anti-fouling application.

Allow to dry 4-6 hours between coats.

For professional use only.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE DISPOSAL: Pesticide that can not be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

CONTAINER DISPOSAL

Nonrefillable container. Do not reuse or refill this container. Offer for recycling, if available, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.

Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

ACCEPTED
WITH COMMENTS
EPA Letter Dated:

DEC - 8 2010

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 577-556

4/4

FIRST AID

IF SWALLOWED: Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a *poison control center or doctor*.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.

HAVE THE PRODUCT CONTAINER OR LABEL WITH YOU WHEN CALLING A POISON CONTROL CENTER OR DOCTOR, OR GOING FOR TREATMENT.

Note to Physician

Contains petroleum distillate - vomiting may cause aspiration pneumonia

NOTICE: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm

PRECAUTIONARY STATEMENTS

WARNING: HAZARDS TO HUMAN AND DOMESTIC ANIMALS

HAZARDS TO HUMANS: Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. Wash contaminated clothing before reuse. Never give anything by mouth to an unconscious person. Call a physician immediately. Avoid storage and usage near food and feed products. When used in confined areas or while spraying and/or sanding boat surface, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health, under the provisions of 30 CFR 11.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not contaminate waters by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter waters. Dispose wastes debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE. FLASH POINT APPROXIMATELY 80 °F. Keep away from heat and open flame. Pesticide, container or rinse solution that cannot be used according to label instructions must be disposed of according to Federal or approved State procedures under Subtitle C of the Resource Conservation and Recovery Act.

Manufactured by
The Sherwin-Williams Co.
Portsmouth, Virginia 23704

ACCEPTED
with COMMENTS
EPA Letter Dated:
DEC - 8 2010

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No. 577-556