

577-557

PM-32

3-20-98

10/4

ACCEPTED

MAR 20 1998

Under the Federal Insecticide, Fungicide, and
Rodenticide Act as amended, for the
pesticide, registered under
EPA Reg. No. 577-557

PROPOSED LABEL COPY
EPA APPLICATION NO. 154978
page 1

FRONT PANEL:

**Thompson's Wood Protector
Clear Preservative**

from the makers of Thompson's Water Seal brand waterproofer

Clear

- Waterproofs to prevent moisture damage
- Prevents mildew growth, discoloration and wood rot
- UV protection against graying
- Quick, one-coat coverage
- Long-lasting, penetrating oil

NET ONE U.S. GALLON 3.785 Liters

KEEP OUT OF REACH OF CHILDREN.

**CAUTION. COMBUSTIBLE! VAPOR HARMFUL. IRRITATES EYES, SKIN AND
RESPIRATORY TRACT.**

Before using, carefully read Precautionary Statements elsewhere on label.

ACTIVE INGREDIENT:

3-Iodo-2-Propynyl Butyl Carbamate	0.5%
Inert Ingredients:	99.5%
TOTAL	100.0%

CONTAINS PETROLEUM DISTILLATES.

EPA Reg. No. ~~52782-1~~ EPA Est. No. 52782-MS-01

577-557

BACK PANEL:

PROPOSED LABEL COPY
 EPA APPLICATION NO. 154978
 page 2

**Thompson's Wood Protector
 Clear Preservative**

What is Thompson's Wood Protector Clear Preservative?

Thompson's Wood Protector Clear Preservative is a clear, highly-penetrating, oil-based waterproofing preservative especially formulated for protecting wood above ground level. This penetrating formula offers three-way protection for wood:

1. Waterproofing protection that helps prevent warping, shrinking and splitting caused by moisture;
2. Excellent wood preservative that helps prevent the formation of mildew, sapstain and wood rot; and
3. UV sunscreens agents work to retard color change and damage caused by sunlight and enhance the longevity of the preservative ingredient.

WHERE TO USE:

- | | | | |
|-----------------|--------------------------|--------------|-------------------------------|
| -Decks | -Pressure Treated Lumber | -Plywood | -Outdoor Wood Furniture |
| -Doors | | -Wood Fences | -Other Exterior Wood Surfaces |
| -Particle Board | -Wood Shingles | -Wood Shakes | |
| -Siding | -Barns | -Shutters | |
- Not recommended for use on previously painted or stained wood.

HELPFUL HINTS:

- Only one coat is necessary in most applications. Do not saturate surfaces, puddle or build to wet film.
- Excessive oiliness, particularly on horizontal surfaces, may be removed by scrubbing with detergent and water.
- Weathered wood will appear darker after application. A trial patch is recommended before you start.
- Not recommended for use on painted or recently stained surfaces.
- Overspray of product onto metal or glass should be removed immediately with paint thinner or mineral spirits.
- Cover plants and shrubs. If using a sprayer, move all objects that could come in contact with overspray.
- For best preservative and water repellency action, reapplication is recommended every 3 to 4 years. For maximum protection from color change and other damage caused by the sun, reapplication is recommended every year. Vertical and horizontal surfaces will experience color changes at different rates.

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PREPARATION: Wood must be thoroughly dry since Thompson's Wood Protector will not fully penetrate wet or damp surfaces. Surface should be clean and porous enough to allow penetration. For best results on wood that has been weathered or discolored from mold or mildew, clean with Thompson's Deck Wash according to the package directions and cautions. Let area dry completely before applying Thompson's Wood Protector.

APPLICATION:

1. Apply when both air and surface temperatures are above 50° F and will remain above 50° F for at least 48 hours.
2. Shake well before using. Do not thin.
3. Apply by brush, roller, dipping or spraying.
4. Only 1 light coat is necessary in most applications. Do not saturate surfaces, puddle or build to wet film.

SIDE PANEL:

COVERAGE:

Actual coverage will vary depending on wood porosity and surface roughness
One Coat is Sufficient.

	Approximate Coverage <u>Sq. Ft./Gal.</u>
Cedar, Oak, Redwood, Exotic Woods (i.e. Mahogany)	300-400
All other woods (i.e., Pine, Pressure-Treated, Plywood)	200-300
One Coat is Sufficient.	

DRYING TIME: Allow 24-48 hours. Penetration will vary depending on the porosity and water content of the surface. Wait a minimum of 30 days before painting over Thompson's Wood Protector with oil-based paint.

CLEAN UP: Clean brushes and equipment with paint thinner or mineral spirits. Overspray or accidental spillage can be wiped up or cleaned immediately with paint thinner or mineral spirits.

For sizes one gallon and less:

STORAGE AND DISPOSAL:

Avoid storage near food or food products. Do not reuse empty container. Securely wrap original container in several layers of newspaper and discard in trash.

For sizes over one gallon:

STORAGE AND DISPOSAL:

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or dispose of in a sanitary landfill, or by incineration if allowed by state and local authorities.

RECYCLING INFORMATION: This can is made from an average of 25% recycled steel (10% post-consumer).

If you have questions regarding this or any other Thompson's products, please call The Thompson's Company Consumer Help Line at 1-800-367-6297.

SATISFACTION GUARANTEE:

The Thompson's Company guarantees that this product will meet your satisfaction. If you are not completely satisfied with product performance for any reason, return your sales receipt with the purchase price circled and a brief description of the nature of your complaint, and we will refund your total purchase price.

LIMITED WARRANTY:

This is not a warranty or guarantee for any purpose other than as expressly set forth therein. The Thompson's Company shall not be liable for cost of labor or direct, incidental or consequential damages or any other remedy. The Thompson's Company Division, 825 Crossover Lane, Memphis, TN 38117.

PRECAUTIONARY STATEMENTS:

Hazards to Humans and Domestic Animals

CAUTION! CONTAINS PETROLEUM DISTILLATES. MAY BE HARMFUL IF SWALLOWED.

Avoid contact with skin, eyes or clothing. Avoid breathing vapor or spray mist. Use in well ventilated area.

FIRST AID:

Ingestion: Do not induce vomiting. Call physician or Poison Control Center immediately.

Eye Contact: Immediately flush eyes with water, remove contact lenses, and continue to flush eyes for 15 minutes. If irritation persists, get medical attention.

Skin Contact: Wash skin thoroughly with soap and water. Wash contaminated clothing thoroughly with soap and water before reuse.

Inhalation: Remove to fresh air. If necessary, give artificial respiration or oxygen. Call a physician.

Environmental Hazard: Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water by cleaning of equipment or disposal of wastes.

Physical Hazards: Combustible. Do not use or store near heat or open flame.

NOTICE: Delayed effects from long term exposure. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

NOTICE: This product contains a chemical known to the State of California to cause cancer.

For the lower VOC version:

Maximum VOC 350 g/L (2.9 lbs./gal.)

For the higher VOC version:

Maximum VOC 550 g/L (4.6 lbs./gal.)

Manufactured by:

The Thompson's Company

Memphis, TN 38117

Stock No.:

I.C. No.: