

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

MAR 27 2003

The Sherwin-Williams Company  
101 West Prospect Avenue  
Cleveland, OH 44115-1075

Attn: Madelyn K. Harding


Subject: Sherwin-Williams Seaguard Hard Vinyl Anti Foulant  
EPA Reg. No. 577-560  
Notification of Additional EPA Establishment Number

This will acknowledge receipt of your notification to add the EPA Establishment No. 577-GA-01 to Sherwin-Williams Seaguard Hard Vinyl Anti Foulant label, submitted under the provision of FIFRA Section 3(c)9. Based on a review of submitted material, the following comments apply.

This notification is acceptable. This information has been made part of your file.

If you have any questions concerning this letter, please contact Solange Garvey at (703) 308-8911.

Sincerely,



Marshall Swindell  
Product Manager 33  
Regulatory Management Branch I  
Antimicrobial Division (7510C)

CONCURRENCES

SYMBOL							
SURNAME							
DATE							

Front of Label

# Sherwin-Williams Seaguard Hard Vinyl Anti-Foulant

## Marine Finishes

For protecting underwater hull surfaces from marine fouling

Product Color and Number (varies based on color)

<b>ACTIVE INGREDIENT</b>	
Cuprous Oxide .....	51.35%
<b>INERT INGREDIENTS</b> .....	<b>48.65%</b>
<b>TOTAL</b> .....	<b>100.00%</b>

CONTAINS PETROLEUM DISTILLATES

5 U.S. Gal  
18.92 L

EPA Reg. No. 577- 560

EPA Est. No.  
577-VA-01  
577-NJ-02  
577-CA-04  
577-GA-01

VOC: 500 g/L (4.2 lbs./gal.)

(VOC WILL VARY DEPENDING ON SPECIFIC COLOR)

KEEP OUT OF REACH OF CHILDREN.

## WARNING

FLAMMABLE! VAPOR HARMFUL. IRRITATES EYES, SKIN AND  
RESIRATORY TRACT.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

*Back or Side of Label*

## **DIRECTIONS FOR USE**

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

Mix thoroughly prior to use. Apply at 5.0-8.0 mils wet per coat / 3.0-5.0 mils dry per coat.

Apply by brush, roller or spray.

Recoat Time: 2 hours minimum

Launch Time: 4 hours minimum after last coat of anti-foulant.

Thinning: As needed up to 5% by volume with Vinyl Reducer R7K133 or Solvent Retarder R6K10.

Application Temperature: 50 °F –100 °F

Note: First coat of Seaguard Anti-fouling paint must be applied to final coat of epoxy primer while the epoxy primer is still tacky, usually within 3-5 hours.

Surface Preparation: All surfaces referenced below must be free of all surface contaminants and moisture prior to application of primer or anti-foulant.

Previously Painted Surface with Vinyl Anti-Foulant:

Clean surface thoroughly by hydroblasting and/or scrubbing with an abrasive pad using fresh water to remove all marine growth and surface contamination. Remove all loose, flaking paint and feather the edges by sanding. For best results, sand existing anti-fouling paint film with 100 to 120 grit abrasive and wipe clean. Apply 2-3 coats of Seaguard Anti-Fouling Paint.

Steel: Remove all oil and grease from surface by Solvent Cleaning per SSPC-SP1. Minimum surface preparation is Near White Metal Blast Cleaning per SSPC-SP10. Blast clean all surfaces using a sharp angular abrasive for optimum surface profile (2-3 mils). Remove all weld spatter and ground all sharp edges by grinding to a minimum ¼" radius. Apply 2-3 coats of Dura-Plate 235 Epoxy at 4-8 mils dft per coat. Apply 2-3 coats of SeaGuard Anti-Fouling Paint.

Wood: Apply first coat of SeaGuard Anti-foulant reduced 20% with Reducer R7K133. Apply 1-2 additional coats of SeaGuard Anti-Fouling Paint.

Fiberglass: Remove all dirt, oil, grease, and mold release agents. Be sure to change wiping rag frequently. Sand surface with 80 grit abrasive. Apply 2-3 coats of Dura-Plate Epoxy at 4-8 mils dft per coat.

This product is effective in preventing marine growth such as barnacles, bugulas, etc. Can be used in fresh or salt waters.

Shelf Life: 12 months

Non-photochemically reactive

For marine applications only.

### **STORAGE AND DISPOSAL**

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

#### **PESTICIDE DISPOSAL**

Pesticide that can not be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

#### **CONTAINER DISPOSAL**

Triple rinse or (equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

### **FIRST AID**

**IF SWALLOWED:** Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

**IF IN EYES:** Flush with plenty of water. Get Medical Attention.

**IF ON SKIN:** Wash with plenty of soap and water. Get medical attention.

**IF INHALED:** Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

### **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.**

Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

**NOTICE:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

575

**PRECAUTIONARY STATEMENTS**

**WARNING: HAZARDS TO HUMAN AND DOMESTIC ANIMALS**

**HAZARDS TO HUMANS:** Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. Wash contaminated clothing before reuse. Never give anything by mouth to an unconscious person. Call a physician immediately. Avoid storage and usage near food and feed products. When used in confined areas or while spraying and/or sanding boat surface, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health, under the provisions of 30 CFR 11.

**ENVIRONMENTAL HAZARDS**

This product is toxic to fish. Do not contaminate waters by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter waters. Dispose wastes debris in an approved landfill.

**PHYSICAL OR CHEMICAL HAZARDS**

**FLAMMABLE. FLASH POINT APPROXIMATELY 80 °F.** Keep away from heat and open flame. Pesticide, container or rinse solution that cannot be used according to label instructions must be disposed of according to Federal or approved State procedures under Subtitle C of the Resource Conservation and Recovery Act.

The Sherwin-Williams Company  
Cleveland, Ohio 44115