

# HAVILAND SUPERIOR SPRAY OIL

Haviland Superior Spray Oil is formulated with a straight cut, high purity, narrow distillation range base oil which has been refined to surpass the following minimum specifications:

Saybolt Universal Viscosity at 100°F.	66-74 seconds
Gravity, API (minimum)	33
Unulfonated residue (minimum)	92
Pour Point (maximum)	20°F.
Distillation at 10 m.m. Hg., °F.	
50% point	425 ± 12°F.
10-90% range (maximum)	95°F.

**ACTIVE INGREDIENT:**

Petroleum Oil .....	99.25%
INERT INGREDIENTS: .....	.75%
Total	100.00%

**DIRECTIONS FOR USE**

To control	Superior Spray Oil Amount per 100 gal.	Time of Application
<b>PESTS OF APPLES</b>		
European Red Mite	2 Gal.	Green Tip to Pre-pink
European Fruit Lecanium	2 Gal.	Dormant
Fruit Tree Leafroller	3 Gal.	Dormant
San Jose' Scale	2 Gal.	Delayed Dormant
Forbes Scale	2 Gal.	Delayed Dormant
<b>PESTS OF PEARS</b>		
Pear Psylla	2 Gal.	Dormant before the eggs are laid.
European Red Mite	2 Gal.	Dormant
Pear Leaf Blister Mite	3 Gal.	Dormant
<b>PESTS OF PEACHES, PLUMS, AND CHERRIES</b>		
European Red Mite	2 Gal.	Dormant
Cottony Peach Scale	3 Gal.	Dormant
European Fruit Lecanium	2 Gal.	Dormant

USDA Reg. No. 595-212

Net Contents 54 Gallons

**MIXING DIRECTIONS**

While filling sprayer, the pump and agitator should be running. If a fungicide or insecticide is to be sprayed with spray oil, add these when sprayer is about ¼ full. When sprayer is ½ full after fungicide or insecticide has been thoroughly mixed, add proper amount of Haviland Superior Spray Oil.

Superior Spray Oils have been successfully combined with Thylate, Cyprex, Ferbam, Fixed Copper, B.H.C., Lindane, Guthion, Malathion, Trithion, Parathion, Kelthane and Tedion.

**CAUTION: Keep Out of Reach of Children**

Be sure spray tank is clean and free from all Lime-sulfur or other sulfur deposits. Be certain that Haviland Superior Spray Oil is compatible with other insecticides or fungicides which might be used, either in the same spray tank or applied shortly after the oil application. Do not apply this material to varieties which are known to be sensitive to oil sprays. Do not use Superior Spray Oil with or USE WITHIN 6 DAYS OF THE FOLLOWING SPRAY CHEMICALS: Captan, Dichlone, Sulfur, Lime-sulfur, Phaltan, Sevin, Karathane, Folpet, or any other material not proven to be compatible with Superior Spray Oils.

Do not apply Superior Spray Oil when the temperature is below 40°F. or above 90°F. or at any time when there are indications that the temperature may fall to freezing within 24 hours after spraying.

When combining Haviland Superior Spray Oil in the same spray tank with other insecticides or fungicides be sure to follow the label recommendations for safe handling of these materials. Use all protective equipment and clothing for use as is needed.

Harmful if swallowed. Do not breath spray mist.

Do not contaminate water by cleaning of equipment, or disposal of wastes.

**NON-WARRANTY**

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.



**HAVILAND**

ACCEPTED WITH COMMENTS