
H S-P-F

**WOOD PRESERVER
AND INSECTICIDE**

U.S.D.A. Reg. No. 619-30

ACTIVE INGREDIENTS: 97%

Coal Tar Neutral Oils

INERT INGREDIENTS: 3%

Water, Carbon

S.P.F. protects against rot and termites. Gives additional life and service to wood construction in contact with masonry and in damp, dark places where wood rots easily. It is a preserver and rustic brown stain for boathouses, camps, farms, fences, shingles, trellises and walks.

DIRECTIONS

As a wood preserver and stain apply by brush, dip or spray. Apply second coat after first has dried. Posts and rough lumber should be free of bark, dry and well seasoned. Season checks, knots, ends and mortises should be well saturated with S.P.F. Especially soak surfaces in contact with ground or masonry surfaces.

For Termite Control dig trench up to 30 inches, but in no case below base of footings. Treat soil with not less than two gallons of S.P.F. per five cubic feet of soil or one gallon per linear foot of trench. Protect grass, plants and shrubbery by forming a tar paper barrier between trench and plants.

CAUTION: Keep out of Reach of Children

May cause Skin Irritation. Avoid prolonged or repeated contact with skin, or prolonged breathing of Vapors. (If substance gets on skin, wash thoroughly. Flush eyes with water and see a doctor.)

CONTENTS: ONE GALLON

James Huggins & Son, Inc.

MALDEN, MASSACHUSETTS

