

Code No. 73350

1 GALLON

40% PENTA Concentrate
Dilute 1 to 10

MIXING

If wood surface is to be painted, mix one gallon of PENTA FIX with 10 gallons of kerosene and stir vigorously. Permit to dry thoroughly after application before painting.

If surface is not to be painted, dilute this product with 10 parts of crank-case, diesel or fuel oil. Thick oil will be more difficult to use.

Watering and feed troughs, grain bins and corn cribs may be treated safely. Make certain wood is thoroughly dry before it is used in building. Otherwise this product may impart a temporary unpleasant odor or taste.

DIRECTIONS

For Poles and Timbers

Wood should be peeled and seasoned. Dry wood is easier to treat than is green wood. Fill a steel drum with PENTA FIX diluted as explained above. Soak butt ends of posts from 12 to 48 hours depending on hardness of wood, seasoning and extent of treatment desired. Above ground end of wood should be soaked about one half as long as butt end. Lumber will require a long dip tank rather than a drum.

For Spraying or Painting on New Lumber or Existing Buildings

Brush Application—Apply freely. Two coats should be given, allowing wood to dry between coats, if wood is to be placed in contact with ground.

Spray Application—Two applications should be given all wood which is to come in contact with ground. Low pressure coarse spray is desirable. Hold nozzle about 3 inches from wood. Keep away from fire, open flame, etc. Indoors wear goggles and synthetic gloves. Provide good ventilation. Do not smoke while spraying. Avoid inhaling fumes of spray. Brush and spray applications should be used preferably as a supplement to proper soil poisoning (see section for Killing Termites).

Covering Capacity—A gallon of the diluted mixture will cover between 100 and 200 sq. ft.

PENTA FIX

penta
wood
preservative

CONTROLS: WOOD ROT and
DECAY
KILLS: TERMITES and
POULTRY MITES
Prevents sap staining,
minimizes shrinkage
and swelling.
PAINTABLE and
PENETRATING
LENGTHENS LIFE OF
WOOD

NOTE: PENTA FIX is concentrated for economy.
It should be thinned 10 to 1 with fuel oil
or kerosene (see mixing directions)
before using.

CONTENTS:

ACTIVE

INGREDIENTS:

Pentachlorophenol* ..34%

Other Chlorophenols & Related Compounds ..6%

Aromatic Petroleum

Derivatives35%

INACTIVE

INGREDIENTS: ..25%

*Contains 40% Pentachlorophenol as determined by Federal Specifications TT-W-570

ACCEPTED

UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTERED
ED UNDER NO.

Comment



CAUTION: Keep out of reach of children.
See side panel for additional cautions.

THOMPSON CHEMICALS CORPORATION
LOS ANGELES, CALIFORNIA • ST. LOUIS, MISSOURI

For Killing Termites

PENTA FIX kills termites. A penetrating spray will help to keep them out of wood. However, soil as well as timber should be treated. All points of entry or contact such as wood, pipes, masonry piers should be treated. A treated layer of earth 8 to 12 inches wide should separate potential points of termite entry from untreated earth. Dig a trench 8 to 12 inches wide around building foundation approximately 30 inches deep, but not below the top of the footing, if this is shallower. Apply the diluted product at the rate of 5 gallons per 10 linear feet of trench for trenches up to 15 inches deep, and 10 gallons per 10 linear feet for deeper trenches.

PENTA FIX is injurious to vegetation, therefore avoid contact with grass, shrubbery or flowers. Remove from within 3 feet of trenches or protect with tar paper.

For Killing Poultry Mites

Thoroughly clean poultry house nests, dropping boards and floors. Then sprinkle, brush or swab this product from the ground to about three feet above the roosts. Saturate cracks with this product. If infestation is very bad, swab entire poultry house. PENTA FIX will kill ticks, powder post beetles and other wood-inhabiting insects as well as mites. It also stops mold and wood rot.

Thoroughly ventilate and allow poultry house to dry 48 hours before returning birds.

WARNING

Do not allow this product to come into contact with eyes, skin or clothing. It will cause extreme irritation upon coming into contact with skin. If there is contact, immediately wash hands and face thoroughly with warm water and plenty of soap.

This product is harmful if swallowed or absorbed through skin. Do not inhale vapor, fumes or spray mist.

NOTICE

Seller makes no warranty of any kind, expressed or implied, concerning the use of this product. Buyer assumes all risk in use or handling, whether in accordance with directions or not.

MADE IN U S A LFF
USDA Reg No 642 41

