

VARSOIL

VARSOIL

VARSOIL

PETROLEUM SOLVENT

CAUTION

KEEP AWAY FROM HEAT AND OPEN FLAME
KEEP CONTAINER CLOSED
AVOID CONTACT WITH SKIN
USE WITH ADEQUATE VENTILATION
IF SWALLOWED, DO NOT INDUCE VOMITING
CALL A PHYSICIAN

DRY CLEANING FLUID

PAINT THINNING

BRUSH CLEANING

METAL CLEANING

GRASS & WEED CONTROL

ACTIVE INGREDIENT 100% MINERAL SPIRITS

CAUTION-COMBUSTIBLE

HARMFUL OR FATAL IF SWALLOWED
KEEP OUT OF REACH OF CHILDREN


Read Carefully Caution on Side Panels

CAUTION

KEEP AWAY FROM HEAT AND OPEN FLAME
KEEP CONTAINER CLOSED
AVOID CONTACT WITH SKIN
USE WITH ADEQUATE VENTILATION
IF SWALLOWED, DO NOT INDUCE VOMITING
CALL A PHYSICIAN

EPA REGISTRATION NO. 644 56

TRADEMARKS REG. U.S. PAT. OFF.
MADE IN U.S.A.



2 U.S. GALLONS

VAR SOL

MINERAL SOLVENT

VAR SOL

THINNING FLUID

PAINT THINNING

BRUSH CLEANING

METAL CLEANING

WEED CONTROL

100% MINERAL SPIRITS

NON-FLAMMABLE

DANGEROUS IF SWALLOWED

KEEP OUT OF REACH OF CHILDREN

Caution on Side Panels



2 U.S. GALLONS

CAUTION

KEEP AWAY FROM HEAT AND OPEN FLAME

KEEP CONTAINER CLOSED

AVOID CONTACT WITH SKIN

USE WITH ADEQUATE VENTILATION

IF SWALLOWED, DO NOT INDUCE VOMITING

CALL A PHYSICIAN

EPA REGISTRATION NO. 644 56

TRADEMARKS REG. U.S. PAT. OFF.
MADE IN U.S.A.

DIRECTIONS

FOR FABRIC DRYCLEANING—Before drycleaning, test the inside of a seam or an extra piece of material for color fastness.

The article to be cleaned must be dry. Brush carefully and spot-clean by placing a pad of clean cloth under the spot and rubbing it gently with another clean cloth moistened with VARSOL.

Place the article in a suitable clean receptacle, pour on VARSOL to completely cover. Dip the article several times in the VARSOL, then squeeze out (do not wring) the excess. Place the article to dry on a hanger in the shade out of doors or in a well ventilated room.

FOR PAINT THINNING—VARSOL is a superior mineral spirits-type solvent and may be used for thinning most oil paints. Use according to the directions of the paint manufacturer.

FOR BRUSH CLEANING—Squeeze excess paint from brush immediately after use. Pour about one inch of VARSOL into a clean receptacle and thoroughly work VARSOL through the bristles. Remove excess solvent from the brush and discard the used VARSOL. Repeat this with small amounts of fresh VARSOL until bristles appear clean.

FOR METAL CLEANING—VARSOL may be used for cleaning grease and oil from metal parts. Cleaning may be accomplished by immersing the item in VARSOL, or by wiping with a cloth soaked in the solvent.

FOR GRASS AND WEED CONTROL—VARSOL may be used for easy control of grass and weeds. It is useful under fences and in similar hard to reach locations. It will help to maintain a vegetation-free ring around most mature shrubs and trees, flower beds, and along the foundations of buildings. Dallisgrass and other tall growing grasses on lawns may be controlled by spot treatments. VARSOL kills lawn grass, but as soil is not sterilized, bare spots may be filled in by regrowth.

Apply VARSOL as a coarse spray to thoroughly wet the leaves and stems of weeds. Treat again when new growth occurs. For application, garden sprayers and hand sprinkler cans may be used.

HUMBLE OIL & REFINING COMPANY
HOUSTON, TEXAS 77001

2 U.S. GALLONS

HT 101