

Arab



Ready to use **WOOD**
PRESERVATIVE
CLEAR

FOR LUMBER-MILLWORK-PLYWOOD-FLOORING
PREVENTS DECAY, SWELLING, SHRINKING,
WARPING, SAP STAIN
KILLS TERMITES
MEETS N.W.M.A. STANDARDS
FOR MILLWORK PRESERVATIVE

Active ingredients	
Pentachlorophenol*	4.5
Other Chlorophenols and related compounds*	0.5
Aromatic Spirits	86.7
Inert ingredients	8.3
Total	100.0

* Technical Pentachlorophenol as defined in Federal Specification TT-W-570

WARNING: KEEP OUT OF REACH OF CHILDREN
SEE BACK PANEL FOR ADDITIONAL CAUTIONS.
NET CONTENTS ONE QUART LIQUID

5-24-72
654-80

USE ARAB WATER REPELLENT PAINTABLE WOOD PRESERVATIVE ON

- Dimensional Lumber
- Doors & Frames
- Farm Buildings
- Decorative Fences
- Garage Doors
- Lawn Furniture
- Millwork
- Porches & Steps
- Screen & Storm Sash
- Sheathing
- Shutters
- Siding
- Trellises
- Window Sash & Jambs
- Wood Shingles
- EVERYTHING made of WOOD

ALSO AVAILABLE

- Arab Stain in a variety of choice of several beautiful colors
- One coat does it - Stains, Waterproofer, Preserves

DIRECTIONS FOR USE

TREATMENT OF MILLWORK, DIMENSIONAL LUMBER AND OTHER NEW WOOD.

Wood should be clean, dry, without finish and cut to size ready for use.
DIP METHOD: Use a suitable open tank and completely immerse wood. Millwork should be treated for three minutes and other types of wood should be treated for five minutes for each inch of thickness. The most critical spots for control of dimensional changes are the cut ends. These should be thoroughly soaked for best results. Estimated Coverage: 5 to 10 gallons per thousand board feet depending on the type of wood.
BRUSH APPLICATION: Two heavy applications should be made to all surfaces with particular attention to the cut ends. Second application may be made after the first application has soaked into the surface. Estimated Coverage: 200 square feet per gallon. Treated wood may be painted as soon as solvents have evaporated.

SPECIAL INSTRUCTIONS FOR SUBTERRANEAN TERMITES:

Wood treated as above prior to use in construction will be resistant to termite attack. Untreated portions of the building are not protected. Protection of the entire building from subterranean termites is best accomplished by soil treatment. Ask your dealer for Arab U-Do-It, the do-it-yourself termite control.

WARNING

Keep Out of Reach of Children. Harmful if inhaled, swallowed or absorbed through the skin. Causes skin irritation. Do not breathe vapor or spray mist. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling. Combustible mixture, do not use or store near open flame. Avoid contamination of feed and foodstuffs. Do not apply on or near vegetation, including trees.
Wear protective clothing and rubber gloves when handling the freshly treated lumber.
This product is toxic to fish and wildlife. This product is toxic to birds. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.
Do not reuse empty container. Destroy by perforating or crushing. Bury or discard in a safe place away from water supplies.

THE ADVANTAGES OF ARAB WATER REPELLENT PAINTABLE WOOD PRESERVATIVE

WATER REPELLENT

Contains water repellent materials that control shrinking, swelling and checking, warping, and grain raising.

PAINTABLE

Provides protective base for paint, varnish and enamel. Treated wood may be painted after 24 hours, or less if solvent has evaporated.

PREVENTS ROT, DECAY AND MOLD

PROTECTS AGAINST INSECTS

Termites, Carpenter Ants, Powder Post Beetles and other wood boring insects.

CLEAR

Does not discolor wood.

NO UNPLEASANT ODOR

MEETS SPECIFICATIONS

Arab Water Repellent Paintable Wood Preservative meets specifications of the National Woodwork Manufacturers Association and the Western Pine Association as well as those of the United States Army, Navy and Air Force.

Any wood likely to be exposed to dampness or the elements should be protected.

FCC 1971

EPA REGISTRATION NO. 654-80

MANUFACTURED BY
FEDERAL CHEMICAL CO., INC.
Indianapolis, Indiana
MAKERS OF FAMOUS
ARAB PEST CONTROL PRODUCTS SINCE 1929