

Parsons
LETHOGAS[®]
FUMIGANT



GRAIN WEEVIL



Forms a Gas Quickly
 Upon Exposure to Air

NOT A FIRE HAZARD

DESTROYS BY CONTACT AND GAS FUMES

GRAIN WEEVIL

Elevators, Granaries, Freight Cars, Mills, Stores



GRAIN WEEVIL

ACTIVE INGREDIENTS — 100%

Ethylene Dichloride	73.50%
Carbon Tetrachloride	24.50%
Ethylene Dibromide	2.00%

Manufacturing Chemists Since 1916

Parsons



GRAIN WEEVIL



EMERGENCY TREATMENT—If swallowed, call a physician and induce vomiting by giving a tablespoonful of salt in a glass of warm water, and repeat until vomit fluid is clear. Never give anything by mouth to an unconscious person. If inhaled, remove victim to fresh air immediately. Have victim lie down and keep him warm and quiet. If breathing has stopped, give artificial respiration. Call a physician at once.

EPA EST. REG. NO. 1959-MI-1
 EPA REG. NO. 1969-98

NET CONTENTS



GALLON

DIRECTIONS

Better results of LETHOGAS depends upon the amount used, the time of exposure, construction of bin and temperature of the grain.

The ideal temperature is from 65 to 95 degrees or warmer. Satisfactory results may not be obtained at a temperature below 70 degrees F unless the amount of LETHOGAS is increased. If 60 degrees to 70 degrees increase by 1/2, if 32 degrees to 60 degrees use double amount.

DOSAGE PER 1,000 BUSHELS

	Elevators	Steel Bins	Wood Bins
WHEAT	2 Gallons	3 Gallons	6 Gallons
CORN	5 Gallons	5 Gallons	6 Gallons

SMALL QUANTITIES can be fumigated in barrels, drums, metal tanks, in milk cans, or lard cans. Covers are usually available for such containers or can be made from two thicknesses of canvas or blankets.

Use—1 pint per 20 bushels—2 table-spoonful per bushel—1 bushel equals one and one fifth cubic feet.

ELEVATOR CONVEYORS—Spray or pour liquid into top openings, then close tightly.

EMPTY FLOUR MACHINES—Keep 1/2 gage or rolled cloth saturated with LETHOGAS and hang inside where the gas or fumes will reach infested parts.

BINS OR OTHER TIGHT ENCLOSURES—Where grain in bin is only 1 to 3 feet deep, level off surface of grain and sprinkle LETHOGAS on top of grain and immediately cover with burlap bags or tarpaulins. Close door and leave room immediately after treating. **KEEP AS AIR-TIGHT AS POSSIBLE FOR 72 HOURS.**

FREIGHT CARS—Sprinkle or distribute LETHOGAS evenly over each three foot layer of grain until bin or car is full. Confine grain for 48 hours.

REDUCES MOISTURE CONTENT—Use according to fumigating directions.


REDUCES SPONTANEOUS COMBUSTION—Helps to control musty or smutty odors of grain when used at double the rate for fumigation.

LETHOGAS when exposed to warm air forms a gas many times heavier than air. Therefore, should always be applied at top—It goes downward, never upward.

DANGER: Keep containers closed. Contains volatile materials. Do not get into eyes, on skin or clothing. Avoid contact with flame or hot surface. Use with adequate ventilation. Wash thoroughly with water. Harmful or fatal if swallowed or inhaled. Avoid Breathing of Vapor. Remove people, birds, and pets from room to be fumigated. Do not re-enter treated areas without an airtight respirator or a full-face gas mask with a canister for protection against toxic vapors. Avoid getting LETHOGAS liquid on forehead or painted surfaces of preserved surfaces. Do not get LETHOGAS liquid on eyes or contact with face.

Do not reuse empty containers. Destroy by perforating or crushing. Burn or discard in a safe place away from water supply.

SONS



AT MEALS—If swal-
and in case vomiting
ful of salt in a glass
eat until vomit fluid
nothing by mouth to
return to fresh air im-
lie down, and keep
If breathing has
respiration. Call a

NO. 1919-AM-1
O. 1969-98

24, 1975

1-11-78
255-6000

LETHOGAS

FUMIGANT

"It is the Gas that Kills"

NOTICE TO PURCHASER—Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.

L177410

GALLON

PARSONS CHEMICAL WORKS, Inc.
Grand Ledge, Michigan 48837

36

BEST DOCUMENT AVAILABLE