

Wyandotte™

PASTURITE®

Brewery Pasteurizer Water Inhibitor Against Corrosion, Scale and Slime

DANGER

KEEP OUT OF REACH OF CHILDREN.

Corrosive. Causes eye damage and skin irritation. Do not get in eyes or on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food. Do not re-use empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

First Aid:
If in eyes, flush with plenty of water. If on skin, wash with plenty of water. If swallowed, give water. If breathing is difficult, give oxygen. If unconscious, give artificial respiration. If inhaled, give oxygen. If inhaled, give oxygen. If inhaled, give oxygen.

ACTIVE INGREDIENTS

Methyldodecylbenzyl trimethyl ammonium chloride	2.4
Methyldodecylxylylenebis trimethyl ammonium chloride	0.6
Sodium Metasilicate pentahydrate	40.0
Sodium Carbonate	34.0

INERT INGREDIENTS

TOTAL	23.0%
TOTAL	100.0

DIRECTIONS

Before starting Pasturite treatment, clean pasteurizer thoroughly. ■ For water having a hardness up to 12 grains, add ½ to 1 pound of Pasturite for each 100 gallons of water in each tank after every 8 hours of operation, for control of scale and corrosion. ■ For water having hardness of 12 to 18 grains, use from 1 to 1½ pounds of Pasturite per 100 gallons of water. ■ Rinse all containers with potable water after passing through pasteurizers.

This product is toxic to fish. ■ Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. ■ Do not contaminate water by cleaning of equipment, or disposal of wastes. ■ Apply this product only as specified on this label.

EPA REG. NO. 66-11

EPA Est. 662-MI-1

FOR INDUSTRY USE ONLY

325 LBS. NET WEIGHT

Freight Classification: Disinfectant, OTM

