SKANE[®] M-8

Industrial Mildeweide - For Use as an Industrial Mildeweide in Coatings, Paints, Building Materials, Wallpaper Pastes and Adhesives, Aqueous Adhesives and Tackifiers. Store Between 32-100°F

ACTIVE INGREDIENT: 2-n-Octyl-4-isothiazolin-3-one 55%		ì	PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS	
INERT INGREDIE KEEP OU IF ON SKIN: IF IN EYES: IF INHALED: IF SWALLOWED: NOTE TO PHYSICI/ use of gastric lavage. N depression and convuis	NTS: Total: 100% T OF REACH OF CHILD DANGER FIRST AID • Take off contaminated clothing. • Rinse skin immediately with plenty o 20 min. • Call a poison control center or doctor • Hold eye open and rinse slowly and 4 water for 15-20 min. Remove contac present after first 5 min. then continu • Call a poison control center or doctor • Move person to fresh air. • If person is not breathing, call 911 or ambulance, then give artificial respir- preferably mouth-to-mouth. • Call a poison control center or doctor • Move person to fresh air. • If person is not breathing, call 911 or ambulance, then give artificial respir- preferably mouth-to-mouth. • Call a poison control center or doctor • Do not induce vomiting unless told to poison control center or doctor. • Have person sip a glass of water if al swallow. N: Probable mucosal damage may contr	55% REN f water for 15- r for advice. genty with et lenses, if e rinsing eye. r for advice. r an ation, r for advice. r o do so by a ble to maindicatie the ratory	 DANGER CORROSIVE CAUSES SEVERE EYE DAMAGE AND SKIN BURNS MAY CAUSE ALLERGIC SKIN REACTION HARMFUL IF INHALED HARMFUL IF SWALLOWED Do not get in eyes, on skin, or on clothing. Wear goggles and rubber gloves. Avoid breathing vapor or mist. Keep container closed. Use with adequate ventilation. Do not take internally. Wash thoroughly after handling. ENVIRONMENTAL HAZARDS This product is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label. 	

- 404

100

Ø

0

12001

1

Page

دلا

Avg. Gross: LB KG Net: LB KG

Avg. Tare: LB KG

Lot

()

35

. . . .

Number

Product Code (91)

«LN1»

Container: Code Number «SN1»

Label Number MOCK

P

er G

	PROHIBITIONS This product is corrosive to mild steel. Do not store or transport in unlined metal containers. Do not contaminate with strong oxidizing or reducing agents. Do not contaminate water, food, or feed by storage or disposal or cleaning of equipment. PESTICIDE DISPOSAL Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. CONTAINER DISPOSAL METAL CONTAINERS Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities. PLASTIC CONTAINERS Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by incineration, or, if allowed by state and local authorities. GENERAL: CONSULT FEDERAL, STATE, OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES. CONDITIONS OF SALE AND WARANTY Rohm and Hass warrans that this product conforms to its chemical description and is reasonably fit for the purpose game on the label only when used in accordance with habt directions used raged and use of the MERCHANTABULITY OR FITNESS, FOR A PARTICULAR USE. Handling, storage, and use of the MERCHANTABULITY OR FITNESS, FOR A PARTICULAR USE. Handling, storage, and use of the MERCHANTABULITY OR FITNESS, FOR A PARTICULAR USE. Handling, is neglectiveness or other unintended consequences resulting from, but not limited to, failure to follow directions with the directions or use and the base of the bedro to the base of the product by Bayer or User are beyond the control of Rahm and Hast and Seller. Risks use as an effectiveness or other unintended consequences resulting from, but not limited to, failure to follow directions with the dinferencons use	DIRECTIONS FOR USE It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Skane M-8 mildeweide is for use as an industrial mildeweide in coatings, paints, building materials, wallpaper pastes and adhesives, aqueous adhesives and tackifiers. COATINGS For use as a mildeweide in coatings such as latex and solvent-based paints, semi-transparent stains and solid stains. Use 1.0 to 3.0 pounds of Skane M-8 mildeweide per 100 gallons of coating formulation. If necessary, a higher dosage up to 4.0 pounds of Skane M-8 per 100 gallons may be used depending upon level of control required. In latex coatings, Skane M-8 should be added during the letdown phase of paint manufacture. To insure uniform distribution throughout the coating, it is recommended that Skane M-8 be premixed with propylene glycol and coalescent. The premix should be added slowly, with good agitation, just prior to the addition of the thickener. In solvent-based coatings, a coupling solvent such as butyl Cellosolve [®] may be used to assist in mixing Skane M-8. CONCENTRATES Skane M-8 should be added to the polymer latex concentrate at a level to ensure that the final use-dilution will contain L0 to 3.0 pounds of Skane M-8 mildeweide per 100 gallons of	 BUILDING MATERIALS For use as a mildewcide in building materials such as elastomeric roof and wall coatings and mastics, caulks, sealants, joint cements, spackling, stucco, and grouting. Use 1.0 to 3.0 pounds of Skane M-8 mildewcide per 100 gallons of formulation. WALLPAPER PASTES AND ADHESIVES For use as a mildewcidal preservative to protect materials such as polyvinyl acetate, starch and dextrin-based pastes from fungai attack after they are applied. Use 0.1 to 1.5 pounds of Skane M-8 mildewcide in 100 pounds of formulation. AQUEOUS ADHESIVE AND TACKIFIER PRESERVATION For use as a mildewcidal preservative in water soluble and water dispersed adhesives such as animal glues, vegetable glues, natural rubber latices, polyvinyl acetate, styrene-butadiene, polyurethane, epoxy, acrylic latices, and tackifiers derived from rosin and hydrocarbon resins. Use 0.10 to 0.20 pounds of Skane M-8 mildewcide per 100 pounds of formulation. Skane M-8 mildewcide weighs 8.5 pounds per gallon.
STORAGE RUSE OF MUSE POINTS PRODUCT coating formulation. Date of Manufacture: location for date Dosage levels of Skane M-8 mildeweide will depend upon the type Date of Manufacture: location for date Dosage levels of Skane M-8 mildeweide will depend upon the type Date of Manufacture: location for date Dosage levels of Skane M-8 mildeweide will depend upon the type EPA Reg. No. 707-100 The stabilishment number	assumed by the Buyer or User. IN NO CASE WILL ROHM AND HAAS OR SELLER BE HELD LIABLE FOR CONSEQUENTIAL, SPECIAL, OR INDIRECT DAMAGES RESID.TING FROM THE HANDLING. STORAGE, OR USE OF THIS PRODUCT Date of Manufacture: location for date EPA Reg. No. 707-100	 1.0 to 3.0 pounds of Skane M-8 mildeweide per 100 gallons of coating formulation. Dosage levels of Skane M-8 mildeweide will depend upon the type of formulation, the presence and level of zinc oxide in the system, 	

ACCEPTED

AUG 0 6 2001

• -

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 707-100