



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

November 3, 2016

Joanne Ryder
Regulatory Manager
Rohm and Haas Company
100 Independence Mall West
Philadelphia, PA 19106-2399

Subject: Notification per PRN 98-10 – Update logo, emergency number, warranty statement, and additional label language; add package size of 275 gallons
Product Name: Skane M-8
EPA Registration Number: 707-100
Application Date: 8/16/2016
Decision Number: 520743

Dear Ms. Ryder:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

If you have any questions, you may contact Aline Heffernan at 703-347-8602 or via email at heffernan.aline@epa.gov.

Sincerely,

A handwritten signature in black ink, appearing to read "Julie Chao".

Julie Chao, Product Manager 33
Regulatory Management Branch 1
Antimicrobials Division (7510P)
Office of Pesticide Programs

SKANE™ M-8

Produced for: (for use when manufactured by a contract manufacturer)

ROHM AND HAAS COMPANY

A Wholly Owned Subsidiary of The Dow Chemical Company

100 Independence Mall West

Philadelphia, PA, 19106-2399

Phone: 215-592-3000

Dow Diamond

®™*Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

NOTIFICATION

707-100

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

11/3/2016

ACTIVE INGREDIENT:

2-n-Octyl-4-isothiazolin-3-one

45.00%

OTHER INGREDIENTS:

55.00%

Total:

100.00%

KEEP OUT OF REACH OF CHILDREN

DANGER

FIRST AID

IF ON SKIN:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 min.
- Call a poison control center or doctor for treatment advice.

IF IN EYES:

- Hold eye open and rinse slowly and gently with water for 15-20 min.
- Remove contact lenses, if present, after first 5 min. then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

IF INHALED:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

IF SWALLOWED:

- Call a poison control center or doctor immediately for treatment advice.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Have person sip a glass of water if able to swallow. Do not give anything by mouth to an unconscious person.

Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

IN CASE OF AN EMERGENCY endangering life or property involving this product, call collect 989-636-4400

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be necessary.

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

CORROSIVE

CAUSES SEVERE EYE DAMAGE AND SKIN BURNS

MAY CAUSE ALLERGIC SKIN REACTION

HARMFUL IF INHALED

HARMFUL IF SWALLOWED

Do not get in eyes, on skin, or on clothing. Avoid breathing vapor. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Wear chemical-resistant gloves such as nitrile or butyl rubber, goggles, face shield, chemical-resistant apron worn over long sleeved shirt, long pants, socks, chemical resistant footwear and a NIOSH approved respirator with an organic

vapor (OV) cartridge or canister with any N, R, P or HE pre-filter. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove and wash contaminated clothing before reuse. Follow the manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. Discard clothing and other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them.

ENVIRONMENTAL HAZARDS

This product is toxic to fish, aquatic invertebrates, oysters and shrimp. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. Antisapstain treated lumber must be stored under cover, indoors, or at least 100 feet from any pond, lake, stream, wetland, or river to prevent possible runoff of the product into the waterway. Treated lumber stored within 100 feet of a pond lake stream, or river must be either covered with plastic or surrounded by a berm to prevent surface water runoff into the nearby waterway. If a berm or curb is used around the site, it should consist of impermeable material (clay, asphalt, concrete) and be of sufficient height to prevent runoff during heavy rainfall events.

STORAGE AND DISPOSAL

PESTICIDE STORAGE

This product is corrosive to mild steel. Do not store or transport in unlined metal containers. Do not contaminate with strong oxidizing or reducing agents. Do not contaminate water, food, or feed by storage or disposal or cleaning of equipment. Store between 32-100°F.

PESTICIDE DISPOSAL

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

Nonrefillable container. Do not reuse or refill this container. Triple rinse or pressure rinse container (or equivalent) promptly after emptying. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by procedures approved by state and local authorities.

Refillable container. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning of the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller. To clean container before final disposal, empty contents into application equipment and triple rinse. Pour or pump rinsate into application equipment or rinsate collection system. Then offer for recycling if available, or puncture and dispose of in a sanitary landfill, or by incineration, or by other procedures allowed by state and local authorities.

NOTICE

Seller warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. SELLER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Date of Manufacture: location for date
EPA Reg. No. 707-100
EPA Est. No. establishment number

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Do not use treated material for construction of beehives.

COATINGS

For use as a mildewcide in coatings such as latex and solvent-based paints, semi-transparent stains and solid stains. Use 0.1 to 0.3 pounds of this product per 100 pounds of coating formulation. If necessary, a higher dosage up to 0.4 pounds of product per 100 pounds may be used depending upon level of control required.

In latex coatings, this product should be added during the letdown phase of paint manufacture. To ensure uniform distribution throughout the coating, it is recommended that this product be premixed with propylene glycol and coalescent. The premix should be added slowly, with good agitation, just prior to the addition of the thickener. In solvent-based coatings, a coupling solvent such as Butyl Cellosolve® may be used to assist in mixing this product.

CONCENTRATES: This product should be added to the polymer latex concentrate at a level to ensure that the final use-dilution will contain 0.1 to 0.3 pounds of product per 100 pounds of coating formulation. Dosage levels of this product will depend upon the type of formulation, the presence and level of zinc oxide in the system, and the climate in which the material will be exposed.

DISPERSED PIGMENTS

This product is recommended for use as a mildewcide in the manufacture and storage of dispersed pigments, extender slurries and colorants. Use levels range from 0.01 % - 0.25% of this product by weight to provide 45 to 1125 ppm of active ingredient. Add this product at a point in the production process where sufficient mixing will assure good suspension of the material as other ingredients are added.

METALWORKING FLUID PRESERVATION

This product is recommended for the control of fungi in the manufacture and use of soluble, synthetic, and semi-synthetic metalworking fluids. **This product** is not recommended for use in systems or fluids which are subject to foaming or systems with high levels of tramp oil.

METHOD OF ADDITION: **This product** should be directly dispensed into the metalworking concentrate or use-dilution metalworking fluid using a metered pump or manual pouring and uniformly dispersed throughout the fluid.

FLUID CONCENTRATES

This product should be added to the metalworking concentrate at a level to ensure that the final use-dilution fluid will contain 55-167 ppm of product (25-75 ppm active ingredient).

USE-DILUTION FLUID

INITIAL DOSE: For a noticeably fouled system, add 0.47-1.44 pounds (7-21 fluid ounces) of **product** per 1000 gallons of emulsion. This will provide 55-167 ppm product (25-75 ppm active ingredient). Repeat until control is achieved.

SUBSEQUENT DOSE: For maintenance of a nonfouled system, add 0.09-0.58 pounds (1.3-8.6 fluid ounces) of **product** per 1000 gallons of emulsion every 4 weeks. This will provide 11-67 ppm product (5-30 ppm active ingredient). Increased frequency of treatment may be required depending upon rate of dilution of the preservative with the makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness and system design.

Grossly contaminated systems must be cleaned before treatment is begun.

HYDRAULIC FLUID PRESERVATION

This product is recommended as a preservative in the manufacture and use of soluble oils, high water-based and invert-emulsion hydraulic fluids.

METHOD OF ADDITION: **This product** should be directly dispensed into the hydraulic concentrate or use-dilution hydraulic fluid using a metering pump or manual pouring and uniformly dispersed throughout the fluid.

FLUID CONCENTRATES

This product should be added to the hydraulic fluid concentrate at a level to ensure that the final use-dilution fluid will contain 55-167 ppm of product (25-75 ppm active ingredient).

USE-DILUTION FLUID

INITIAL DOSE: For a noticeably fouled system, add 0.47-1.44 pounds (7-21 fluid ounces) of **product** per 1000 gallons of emulsion. This will provide 55-167 ppm product (25-75 ppm active ingredient). Repeat until control is achieved.

SUBSEQUENT DOSE: For maintenance of a nonfouled system, add 0.09-0.58 pounds (1.3-8.6 fluid ounces) of **product** per 1000 gallons of emulsion every 4 weeks. This will provide 11-67 ppm product (5-30 ppm active ingredient). Increased frequency of treatment may be required depending upon rate of dilution of the preservative with the makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, and/or system design.

Grossly contaminated systems must be cleaned before treatment is begun.

BUILDING MATERIALS

[Not registered for this use in the State of California – optional statement]

For use as a mildewcide in building materials such as elastomeric roof and wall coatings and mastics, caulks, sealants, joint cements, spackling, stucco, and grouting. Use 0.1 to 0.3 pounds of **product** per 100 pounds of formulation.

WALLPAPER PASTES AND ADHESIVES

[Not registered for this use in the State of California – optional statement]

For use as a mildewcidal preservative to protect materials such as polyvinyl acetate, starch and dextrin-based pastes from fungal growth after they are applied. Use 0.1 to 0.15 pounds of **product** in 100 pounds of formulation.

AQUEOUS ADHESIVE AND TACKIFIER PRESERVATION

[Not registered for this use in the State of California – optional statement]

For use as a mildewcidal preservative in water soluble and water dispersed adhesives such as animal glues, vegetable glues, natural rubber latices, polyvinyl acetate, styrene-butadiene, polyurethane, epoxy, acrylic latices, and tackifiers derived from rosin and hydrocarbon resins. Use 0.10 to 0.20 pounds of **product** per 100 pounds of formulation.

LEATHER PRESERVATIVE

[Not registered for this use in the State of California – optional statement]

This product is recommended for the prevention of mold, bacteria, and fungi in the storage and transport of wet leather stock such as pickled, chrome-tanned, and vegetable-tanned leather.

Use **this product** at the levels specified in the following table to prevent microbial growth on processed hides. The level used will depend on storage conditions and the length of protection required. Pre-dilute **this product** 45-180 times with water and add the diluted product to the chrome liquor at the start of the tanning process.

<u>Wet Hide</u> <u>Weight (lbs.)</u>	<u>Recommended</u> <u>Dose Level</u>	<u>Gallons</u> <u>Product</u>	<u>Pounds</u> <u>Product</u>	<u>ppm of</u> <u>Product</u>	<u>ppm Active</u> <u>Ingredient</u>
10,000	Minimum	0.16	1.4	140	64
10,000	Maximum	0.79	6.6	666	300

This product weighs 8.5 pounds per gallon

Net Content:
Batch: