

Reduced copy (approximately 3/4 size)
to fit on 8 1/2" x 11" paper

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC
ANIMALS**

DANGER

CORROSIVE
CAUSES EYE DAMAGE AND SKIN BURNS
MAY CAUSE ALLERGIC SKIN REACTION
MAY BE HARMFUL IF INHALED
MAY BE FATAL IF SWALLOWED OR ABSORBED
THROUGH THE SKIN

Do not get into eyes, on face, or on skin. Wear goggles when
mixing. Wash face, hands, and clothing immediately with
plenty of water if contact occurs. If contact occurs with
skin, wash immediately with plenty of water. Wash clothing
separately. See also other precautions.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and aquatic life. Do not discharge into
lakes, streams, ponds, or public water supply. Do not discharge into
an NPDES permit. For customer contact, your Regional Office of
the EPA. Do not contaminate water by cleaning of equipment or
disposal of waste. Apply this product only as specified on the
label.

NOTICE: Seller warrants that the product conforms to its chem-
ical description and is reasonably fit for the purpose stated on the
label when used in accordance with directions under normal
conditions of use, but neither the warranty nor any other warranty
of merchantability or fitness for a particular purpose, express or
implied, extends to the use, storage or handling of this product in a
manner other than as directed by label instructions, or under
abnormal conditions or under conditions not reasonably fore-
seeable to seller and buyer as mentioned in any contract.

KATHON® WT
INDUSTRIAL MICROBICIDE FOR USE IN
RECIRCULATING WATER COOLING TOWERS,
WOOD MOLD AND MILDEW CONTROL,
OIL FIELD INJECTION WATERS
AND AIR WASHER SYSTEMS

ACTIVE INGREDIENTS:

Chloro 2-methyl 4-isothiazolin 3-one	86%
Methyl 4-isothiazolin 3-one	26%

INERT INGREDIENTS:

	88.8%
TOTAL	100.0%

DANGER

KEEP OUT OF REACH OF CHILDREN

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Do not induce vomiting. Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

IF INHALED: Remove immediately to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Call a physician.

IF ON SKIN: Wash immediately with soap and water. Remove and wash contaminated clothing before reuse.

IF IN EYES: Flush with plenty of water for at least 15 minutes. Call a physician.

NOTE TO PHYSICIAN:

Do not use if patient is hypersensitive to sulfonamide. Use of gastric lavage. Measures against circulatory shock, respiratory and renal depression may be required.

SEE OTHER PRECAUTIONARY STATEMENTS

MANUFACTURED BY
ROHM AND HAAS COMPANY
PHILADELPHIA, PA.

EPA Est. No. 707-PA-1
SPL. Reg. No. 707-128

NET CONTENTS _____
GALLONS

**DIRECTIONS FOR USE
GENERAL CLASSIFICATION**

**INDUSTRIAL RECIRCULATING
WATER COOLING TOWERS**

For the control of bacteria, fungi, and algae in industrial recirculating water cooling towers.

INITIAL DOSE: Add 1.0 fluid ounce of Kathon WT per 1000 gallons of water in the system. Repeat until control is achieved.

SUBSEQUENT DOSE: Add 0.25 fluid ounces of Kathon WT per 1000 gallons of water in the system. Repeat until control is achieved.

OIL FIELD INJECTION WATERS

For the control of bacteria, fungi, and algae in oil field injection waters.

INITIAL DOSE: Add 1.0 fluid ounce of Kathon WT per 1000 gallons of water in the system. Repeat until control is achieved.

SUBSEQUENT DOSE: Add 0.25 fluid ounces of Kathon WT per 1000 gallons of water in the system. Repeat until control is achieved.

AIR WASHER SYSTEMS

Add to the air washer sump or chill water sump to insure uniform mixing. 15.6 to 86 ppm Kathon WT (0.17 to 1.0 pounds or 2 to 11 fluid ounces of Kathon WT per 1000 gallons of water in the system) depending upon the severity of contamination to control bacteria, fungi, and algae which cause fouling in industrial air washer systems.

INTERMITTENT OR SLUG METHOD

Initial Dose: When the system is noticeably fouled, apply 31.3 to 86 ppm Kathon WT (0.33 to 1.0 pounds or 4 to 11 fluid ounces of Kathon WT per 1000 gallons of water in the system). Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 15.6 to 23.4 ppm Kathon WT (0.17 to 0.25 pounds or 2 to 3 fluid ounces of Kathon WT per 1000 gallons of water) weekly or as needed to maintain control.

CONTINUOUS FEED METHOD

Initial Dose: When the system is just noticeably fouled, apply 31.3 to 86 ppm Kathon WT (0.33 to 1.0 pounds or 4 to 11 fluid ounces of Kathon WT per 1000 gallons of water in the system). Repeat until control is achieved.

Subsequent Dose: Maintain this treatment level by adding a continuous feed of 15.6 to 23.4 ppm Kathon WT (0.17 to 0.25 pounds or 2 to 3 fluid ounces of Kathon WT per 1000 gallons of makeup water).

Bathy fouled systems must be cleaned before initial treatment.
Note: For use only in industrial air washing systems that maintain effective mist eliminating components.

WOOD AND WOOD PRODUCTS

Kathon WT is recommended for the protection of wood and wood products such as landscape timbers, fences, posts, piling, cross ties, decks and similar exterior structures from mold and mildew. Treat southern yellow pine, hemlock, ponderosa pine and other soft woods with 27 to 86 ppm Kathon WT (0.3 to 1.0 pounds or 3.5 to 11 fluid ounces of Kathon WT per 1000 gallons) as an aqueous dip or pressure treatment for mold and mildew control. Thoroughly wet and allow to dry. A single application will afford protection for 12 weeks.
Kathon WT weighs 10.4 pounds per gallon.

STORAGE AND DISPOSAL

PROHIBITIONS

DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL.
OPEN DUMPING IS PROHIBITED.

PESTICIDE DISPOSAL

Containers or residue which cannot be reused according to label instructions must be disposed of according to Federal or approved state procedures under Section 6 of the Resource Conservation and Recovery Act.


CONTAINER DISPOSAL

METAL CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill or by other approved state and local procedures.

PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill or by other approved state and local procedures.

GENERAL

CONSULT FEDERAL, STATE OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES.



**ROHM
AND
HAAS**
PHILADELPHIA, PA. 19105

707-128



Rohm and Haas Company
Independence Mall West
Philadelphia, PA 19105

16 MAY 1982

Attention: G. R. Ackermann
Manager, Govt. Regulatory Affairs

Gentlemen:

Subject: Kathon WT
EPA Registration No. 707-128
Your Submission Dated September 21, 1982

The amendment referred to above, submitted in connection with registration under FIFRA sec. 3(c)(7)(A), is acceptable, provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data.
2. Make the labeling changes listed below before you release the product for shipment bearing the amended labeling:
 - a. Place the statement "Keep out of Reach of Children" to appear directly above the word "Danger" (center panel only).
3. Submit five (5) copies of your final printed labeling before you release the product for shipment.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product bearing the amended labeling constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Note: For all future applications/amendments/resubmissions, always include the EPA Form 8570-1. A copy of Form 8570-1 is enclosed for your files.

Sincerely yours,

JHL
John H. Lee
Product Manager (31)
Disinfectants Branch
Registration Division (TS-767C)

TS-767C:JHLee:DCR-03516:WANG-0877C:lwy:Raven:479-2013:10/27/82