

KATHON[®] WT

Industrial Microbicide for Use in Recirculating Water Cooling Towers,
Wood Mold and Mildew Control, Oil Field Injection Waters and Air
Washer Systems.



ACTIVE INGREDIENTS:	
5-Chloro-2-methyl-4-isothiazolin-3-one	466.49%
2-Methyl-4-isothiazolin-3-one	466.99%
INERT INGREDIENTS:	
Total:	100.0%

KEEP OUT OF REACH OF CHILDREN
DANGER

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Flush eyes immediately with plenty of water for at least 15 minutes. Get medical attention if irritation persists.
IF ON SKIN: Wash thoroughly with soap and plenty of water. Remove and wash contaminated clothing before reuse. Get medical attention if irritation occurs.
IF INHALED: Remove person to fresh air. Get medical attention.
IF SWALLOWED: Wash mouth thoroughly with plenty of water and give water or milk to drink. Get medical attention immediately. Do not give liquids to an unconscious person.
NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

CONDITIONS OF SALE AND WARRANTY

Rohm and Haas warrants that this product conforms to its chemical description and is reasonably fit for the purpose stated on the label only when used in accordance with label directions under normal conditions of use. ROHM AND HAAS MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, EITHER OF MERCHANTABILITY OR FITNESS, FOR A PARTICULAR USE. Handling, storage, and use of the product by Buyer or User are beyond the control of Rohm and Haas and Seller. Risks such as ineffectiveness or other unintended consequences resulting from, but not limited to, failure to follow directions will be assumed by the Buyer or User. IN NO CASE WILL ROHM AND HAAS OR SELLER BE HELD LIABLE FOR CONSEQUENTIAL, SPECIAL, OR INDIRECT DAMAGES RESULTING FROM THE HANDLING, STORAGE, OR USE OF THIS PRODUCT.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER
CORROSIVE
CAUSES SEVERE EYE DAMAGE AND SKIN BURNS
MAY BE FATAL IF ABSORBED THROUGH THE SKIN OR SWALLOWED
MAY CAUSE ALLERGIC SKIN REACTION
HARMFUL IF INHALED

Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid breathing vapor or mist. Avoid contamination of food. Do not take internally. Wash thoroughly after handling.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

PH 83

707-128

9-26-91
Accepted stamp on PG. 2042
1042

Avg. Gross: LB KG
Net: LB KG
Avg. Tare: LB KG

Product
Code
(91)

Lot
Number
()



«LN2»

Container:
Code Number Label Number
«SN2» BU000702

STORAGE AND DISPOSAL.

PROHIBITIONS

The product as supplied evolves gas (largely carbon dioxide) slowly. To prevent buildup of pressure the product is packaged in specially vented containers. Keep this product in the original container when not in use. Container must be stored and transported in an upright position to prevent spilling the contents through the vent. Do not contaminate food or feed by storage, disposal, or cleaning of equipment.

PESTICIDE DISPOSAL.

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL.

METAL CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other state and local authorities.

PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by incinerator or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

GENERAL

CONSULT FEDERAL, STATE, OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES.

Date of Manufacture: location for date
EPA Reg. No. 707-128
EPA Est. No. establishment number

INDICATIONS FOR USE.

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

For the control of bacteria, algae, and fungi add Kathon WT microbicide to the tower basin, distribution box, or some other point to insure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, apply 25-68 ppm Kathon WT (0.27-0.73 pound or 3.2-8.7 fluid ounce of Kathon WT per 1000 gallon of water in the system). Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 12-18 ppm Kathon WT (0.13-0.19 pound or 1.5-2.3 fluid ounce of Kathon WT per 1000 gallon of water in the system) weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

SOIL FIELD INJECTION WATERS

For the control of slime-forming and sulfate-reducing bacteria in oil and gas field water systems, including enhanced recovery injection fluids, drilling, fracturing and completion fluids, slug treat with 7-36 ppm Kathon WT microbicide depending on the severity of contamination.

INITIAL DOSE: Add 14-28 ppm Kathon WT (0.57-1.2 gallon or 6.2-12.5 pound Kathon WT per 1000 barrels of water) at a point in the system where it will be uniformly mixed. Repeat treatment after three days or as needed until control is achieved.

SUBSEQUENT DOSE: Add 5.5-14 ppm Kathon WT (0.22-1.2 gallon or 2.4-6.2 pound Kathon WT per 1000 barrels of water) every seven days or as needed to maintain control.

AIR WASHER SYSTEMS

Add to the air washer sump or chill water sump to insure uniform mixing, 12-68 ppm Kathon WT microbicide (0.12-0.71 pound or 1.5-8.7 fluid ounce of Kathon WT per 1000 gallon of water in the system) depending upon the severity of contamination to control bacteria, fungi, and algae which cause fouling in industrial air washer systems.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 25-68 ppm Kathon WT microbicide (0.26-0.71 pound or 3.2-8.7 fluid ounce of Kathon WT per 1000 gallon of water in the system) depending upon the severity of contamination to control bacteria, fungi, and algae which cause fouling in industrial air washer systems.

SUBSEQUENT DOSE: When microbial control is evident, add 12-18 ppm Kathon WT (0.12-0.20 pound or 1.5-2.3 fluid ounce of Kathon WT per 1000 gallon of water) weekly or as needed to maintain control.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is just noticeably fouled, apply 25-68 ppm Kathon WT (0.26-0.71 pound or 3.2-8.7 fluid ounce of Kathon WT per 1000 gallon of water in the system).

SUBSEQUENT DOSE: Maintain this treatment level by adding a continuous feed of 12-18 ppm Kathon WT (0.12-0.2 pound or 1.5-2.3 fluid ounce of Kathon WT per 1000 gallon of makeup water).

Badly fouled systems must be cleaned before initial treatment.

NOTE: For use only in industrial air washing systems that maintain effective dust-eliminating components.

WOOD AND WOOD PRODUCTS

Kathon WT microbicide is recommended for the protection of wood and wood products, such as landscape timbers, fence posts, pilings, cross ties, decks, and similar exterior structures from mold and mildew. Treat southern yellow pine, hemlock, ponderosa pine, and other soft woods with 21-68 ppm Kathon WT (0.23-0.73 pound or 2.7-8.7 fluid ounce of Kathon WT per 1000 gallon) as an aqueous dip or pressure treatment for mold and mildew control. Under extreme mildew conditions, treat with 170-340 ppm Kathon WT (1.9-3.7 pound or 22-44 fluid ounce) per 1000 gallon of wood treatment solution. Thoroughly wet and allow to dry. A single application will afford protection for 12 weeks.

Kathon WT weighs 10.8 pound per gallon.

ACCEPTED
SEP 26 1997
Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 707-128