

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

DANGER

CORROSIVE
CAUSES EYE DAMAGE AND SKIN BURNS
MAY CAUSE ALLERGIC SKIN REACTION
MAY BE HARMFUL IF INHALED
**MAY BE FATAL IF SWALLOWED OR ABSORBED
THROUGH THE SKIN**

Do not get in eyes, on skin, on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid breathing vapor or mist. Avoid contamination of food. Do not take internally. Wash thoroughly after handling.


ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge into lakes, streams, ponds or public waters unless in accordance with an NPDES permit. For guidance, contact your Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

ACCEPTED

FEB 17 1983

United States Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 707-133



**ROHM
AND
HAAS**
PHILADELPHIA, PA. 19105

KATHON® WT 1.5%

**INDUSTRIAL MICROBICIDE FOR USE IN
RECIRCULATING WATER COOLING TOWERS,
AIR WASHER SYSTEMS, OIL FIELD
INJECTION WATERS, PAPERMILL SLIME
CONTROL AND WOOD MILDEW CONTROL**

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazole-3-one	1.15
2-Methyl-4-isothiazole-3-one	0.35

INERT INGREDIENTS:

	98.50
Total	100.00

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Do not induce vomiting. Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

IF INHALED: Remove immediately to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Call a physician.

IF ON SKIN: Wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse.

IF IN EYES: Flush with plenty of water for at least 15 minutes. Call a physician.

NOTE TO PHYSICIAN:

Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be needed.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

MANUFACTURED BY
ROHM AND HAAS COMPANY
PHILADELPHIA, PA.

EPA Est. No. 707-PA-1
EPA Reg. No. 707-133

NET CONTENTS _____ **GALLONS**

**DIRECTIONS FOR USE
GENERAL CLASSIFICATION**

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

**INDUSTRIAL RECIRCULATING
WATER COOLING TOWERS**

For the control of slime-forming bacteria and sulfate-reducing bacteria in industrial recirculating water cooling towers, add 883 ppm Kathon WT 1.5% (1.26 to 7.46 pounds or ounces of Kathon WT 1.5% per 1000 gallons of water) weekly.

INITIAL DOSE: Add 883 ppm Kathon WT 1.5% (1.26 to 7.46 pounds or ounces of Kathon WT 1.5% per 1000 gallons of water) weekly. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, maintain this treatment by continuous feed of 35 to 219 ppm Kathon WT 1.5% (0.3 to 2.8 fluid ounces of Kathon WT 1.5% per 1000 gallons of water) weekly. Repeat until control is achieved.

AIR WASHER SYSTEMS

Add 883 ppm Kathon WT 1.5% (1.26 to 7.46 pounds or ounces of Kathon WT 1.5% per 1000 gallons of water) weekly. Repeat until control is achieved. System may be cleaned before initial treatment.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is just noticeably fouled, add 883 ppm Kathon WT 1.5% (1.26 to 7.46 pounds or ounces of Kathon WT 1.5% per 1000 gallons of water) weekly. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, maintain this treatment by continuous feed of 35 to 219 ppm Kathon WT 1.5% (0.3 to 2.8 fluid ounces of Kathon WT 1.5% per 1000 gallons of water) weekly. Repeat until control is achieved.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is just noticeably fouled, add 883 ppm Kathon WT 1.5% (1.26 to 7.46 pounds or ounces of Kathon WT 1.5% per 1000 gallons of water) weekly.

SUBSEQUENT DOSE: Maintain this treatment by continuous feed of 35 to 219 ppm Kathon WT 1.5% (0.3 to 2.8 fluid ounces of Kathon WT 1.5% per 1000 gallons of water) weekly.

Badly fouled systems must be cleaned before initial treatment. For use only in industrial air washing systems effective mist eliminating components.

OIL FIELD INJECTION WATER

For the control of slime-forming bacteria and sulfate-reducing bacteria in oil field waters, slug treat with 67,332 ppm (23.58 to 116.8 lbs. of Kathon WT 1.5% per 1000 barrels of water) depending on the severity of contamination.

INITIAL DOSE: Add 166-332 ppm Kathon WT 1.5% (0.3 to 2.8 fluid ounces of Kathon WT 1.5% per 1000 barrels of water) weekly. Repeat until control is achieved.

SUBSEQUENT DOSE: Add 67-166 ppm Kathon WT 1.5% (0.3 to 2.8 fluid ounces of Kathon WT 1.5% per 1000 barrels of water) weekly. Repeat until control is achieved.

Reduced copy (approximately 4/5 size)
to fit 6 1/8" x 9 1/4" paper.

KATHON WT 1.5%

INDUSTRIAL MICROBICIDE FOR USE IN
RECIRCULATING WATER COOLING TOWERS,
AIR WASHER SYSTEMS, OIL FIELD
INJECTION WATERS, PAPERMILL SLIME
CONTROL AND WOOD MILDEW CONTROL

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one	1.15
2-Methyl-4-isothiazolin-3-one	0.35

INERT INGREDIENTS:

98.50
Total 100.00

KEEP OUT OF REACH OF CHILDREN ANGER

STATEMENT OF PRACTICAL TREATMENT

ALLOWED: Do not induce vomiting. Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

HALED: Remove immediately to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Call a physician.

SKIN: Wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse.

EYES: Flush with plenty of water for at least 15 minutes. Call a physician.

TE TO PHYSICIAN:

able mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression, convulsions may be needed.

IDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

FACTURED BY:
I AND HAAS COMPANY
DELPHIA, PA.

Est. No. 707-PA-1
Reg. No. 707-133

NET CONTENTS _____
GALLONS

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal Law to use this product in a manner inconsistent with the label.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

For the control of slime-forming bacteria and sulfate-reducing bacteria in industrial recirculating water cooling towers, add 1.5% Kathon WT 1.5% to the water.

INITIAL DOSE: Add 166-332 ppm Kathon WT 1.5% (6.9-13.9 gallons or 58.0-116.8 lbs. Kathon WT 1.5% per 1000 gallons of water) at a point in the system where it will be uniformly mixed. Repeat treatment after three days or as needed until control is achieved.

SUBSEQUENT DOSE: Add 67-166 ppm Kathon WT 1.5% (2.8-6.9 gallons or 23.5-58.0 lbs. Kathon WT 1.5% per 1000 gallons of water) every seven days or as needed to maintain control.

AIR WASHER SYSTEMS

Add to the air washer pump tank. Add 1.5% Kathon WT 1.5% to the water. Add 166-332 ppm Kathon WT 1.5% (6.9-13.9 gallons or 58.0-116.8 lbs. Kathon WT 1.5% per 1000 gallons of water) at a point in the system where it will be uniformly mixed. Repeat treatment after three days or as needed until control is achieved.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is not easily fouled, apply 148 to 883 ppm Kathon WT 1.5% (1.26 to 7.46 pounds or 19 to 113 fluid ounces of Kathon WT 1.5% per 1000 gallons of water in the system). Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 35 to 219 ppm Kathon WT 1.5% (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of Kathon WT 1.5% per 1000 gallons of water) weekly or as needed to maintain control.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is just not easily fouled, apply 148 to 883 ppm Kathon WT 1.5% (1.26 to 7.46 pounds or 19 to 113 fluid ounces of Kathon WT 1.5% per 1000 gallons of water in the system).

SUBSEQUENT DOSE: Maintain this treatment level by adding a continuous feed of 35 to 219 ppm Kathon WT 1.5% (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of Kathon WT 1.5% per 1000 gallons of makeup water).

Badly fouled systems must be cleaned before initial treatment.

NOTE: For use only in industrial air washing systems that maintain effective mist-eliminating components.

OIL FIELD INJECTION WATERS

For the control of slime-forming bacteria and sulfate-reducing bacteria in oil field waters, slug treat with 67-332 ppm Kathon WT 1.5% depending on the severity of contamination.

INITIAL DOSE: Add 166-332 ppm Kathon WT 1.5% (6.9-13.9 gallons or 58.0-116.8 lbs. Kathon WT 1.5% per 1000 barrels of water) at a point in the system where it will be uniformly mixed. Repeat treatment after three days or as needed until control is achieved.

SUBSEQUENT DOSE: Add 67-166 ppm Kathon WT 1.5% (2.8-6.9 gallons or 23.5-58.0 lbs. Kathon WT 1.5% per 1000 barrels of water) every seven days or as needed to maintain control.

WOOD AND WOOD PRODUCTS

Kathon WT 1.5% is a broad-spectrum fungicide for the control of wood decay fungi, including white rot, brown rot, and blue stain. It is also effective against wood-boring insects. For the control of wood decay fungi, apply 1.5% Kathon WT 1.5% to the wood. For the control of wood-boring insects, apply 1.5% Kathon WT 1.5% to the wood. For the control of blue stain, apply 1.5% Kathon WT 1.5% to the wood. For the control of wood decay fungi, apply 1.5% Kathon WT 1.5% to the wood. For the control of wood-boring insects, apply 1.5% Kathon WT 1.5% to the wood. For the control of blue stain, apply 1.5% Kathon WT 1.5% to the wood.

PAPERMILLS

Kathon WT 1.5% is a broad-spectrum fungicide for the control of papermill slime. Apply 1.5% Kathon WT 1.5% to the water.

POINT OF ADDITION: Add 1.5% Kathon WT 1.5% to the water at the point of addition.

DOSAGE: Apply 1.5% Kathon WT 1.5% to the water. For the control of papermill slime, apply 1.5% Kathon WT 1.5% to the water. For the control of papermill slime, apply 1.5% Kathon WT 1.5% to the water.

Kathon WT 1.5% is a broad-spectrum fungicide for the control of papermill slime.

STORAGE AND DISPOSAL

STORAGE: Do not contaminate water, food, or feed by storage or disposal. Open dump only in a plastic container. Do not reuse empty container.

DISPOSAL: Pesticide or rinsate that cannot be used or chemically reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Triple rinse (or equivalent) all containers and, for metal containers, offer for recycling or reconditioning (for plastic containers dispose in an incinerator), or dispose in landfill approved for pesticide containers or bury in a safe place. Consult federal, state or local disposal authorities for approved alternative procedures.

NOTICE: Seller warrants that the product conforms to its chemical description and is reasonably fit for the purpose stated on the label when used in accordance with directions under normal conditions of use, but neither this warranty nor any other warranty of merchantability or fitness for a particular purpose, express or implied, extends to the use, storage or handling of this product in a manner other than as directed by label instructions, or under abnormal conditions or under conditions not reasonably foreseeable by the seller. Seller assumes the risk of any such use.