

707-133

12/14/2000

174



U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Programs
Registration Division (H7505C)
401 "M" St., S.W.
Washington, D.C. 20460

EPA Reg. Number:

707-133

Date of Issuance:

DEC 14 2000

NOTICE OF PESTICIDE:

Registration
 Reregistration
(under FIFRA, as amended)

Term of Issuance: Conditional

Name of Pesticide Product:

Kathon WT 1.5% Industrial
Microbicide

Name and Address of Registrant (include ZIP Code):

Rohm and Haas Company
100 Independence Mall West
Philadelphia, PA 19106-2399

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

Based on your response to the Reregistration Eligibility Document for Methylisothiazolone RED, EPA has reregistered the above named product subject to the comments recorded in the succeeding paragraph. This action is taken under the authority of section 4(g)(2)(C) of the Federal Insecticide, Fungicide, and Rodenticide Act, as amended. Reregistration under this section does not eliminate the need for continual reassessment of pesticides. EPA may require submission of data at any time to maintain the registration of your product.

1. Make the following label changes:

- a. Revise the EPA Registration No. to read "EPA Reg. No. 707-133".

Signature of Approving Official:

Marshall Swindell, PM 33
Regulatory Management Branch 1
Antimicrobial Division (7510C)

Date:

DEC 14 2000


Page 2
EPA Registration No. 707-133

2. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely,



Marshall Swindell
Product Manager 33
Regulatory Management Branch 1
Antimicrobial Division (7510C)

Enclosure

KATHON[®] WT 1.5%

394

Industrial Microbicide for use in Recirculating Water Cooling Towers, Air Washer Systems, Oil Field Injection Waters, Wood Mildew Control, Papermill Slime Control, Recirculating Closed Loop Water Cooling Systems, Brewery Pasteurizer/Can Warmer/Retort Water Systems, Air Conditioner/Refrigeration Condensate Water Systems, Coal Slurry Systems, Evaporative Condenser Water Systems, Hydrostatic Sterilizer Water Systems, Influent Water Filtration Systems, Immersion Ultrasonic Tank Water, Reverse Osmosis and Ultra Filtration Systems, Industrial Scrubbing Systems, Industrial Wastewater Treatment Systems, Laboratory Equipment Water Baths, Sewage Systems, Paint Spray Booth Systems, and Recirculating Electrodeposition Systems.



ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one	1.11%
2-Methyl-4-isothiazolin-3-one	0.39%

INERT INGREDIENTS:

Total: 100.00%

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Do not induce vomiting. Drink promptly a large quantity of egg whites, gelatin solution, or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately. Never give anything by mouth to an unconscious person.

IF ON SKIN: Wash thoroughly with soap and water. Remove and wash contaminated clothing before re-use.

IF IN EYES: Flush with plenty of water for at least 15 minutes. Call a physician.

IF INHALED: Remove immediately to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Call a physician.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

CONDITIONS OF SALE AND WARRANTY

Rohm and Haas warrants that this product conforms to its chemical description and is reasonably fit for the purpose stated on the label only when used in accordance with label directions and as defined under the Directions for Use on this label. ROHM AND HAAS MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES EITHER OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE. Handling, storage, and use of the product by Buyer or User are beyond the control of Rohm and Haas and Seller. Risks such as ineffectiveness or other unintended consequences resulting from, but not limited to, failure to follow label directions will be assumed by the Buyer or User. TO THE EXTENT PERMITTED BY LAW, NEITHER ROHM AND HAAS NOR SELLER SHALL BE LIABLE FOR CONSEQUENTIAL, SPECIAL OR INDIRECT DAMAGES RESULTING FROM THE HANDLING, STORAGE OR USE OF THIS PRODUCT.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

CORROSIVE

CAUSES IRREVERSIBLE EYE DAMAGE AND SKIN BURNS

MAY CAUSE ALLERGIC SKIN REACTION

HARMFUL IF INHALED

HARMFUL IF SWALLOWED OR ABSORBED THROUGH THE SKIN

Do not get in eyes, on skin, or on clothing. Mixers, loaders and others exposed to this product must wear: long-sleeved shirt and long pants; chemical resistant gloves such as nitrile or butyl rubber; shoes plus socks; goggles and face shield, and chemical resistant apron. Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. Users should wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly. This product may cause skin sensitization reactions in some people.

ENVIRONMENTAL HAZARDS

This chemical is toxic to aquatic plants, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

DISPERSED PIGMENT PRESERVATION

Kathon WT 1.5% microbicide is recommended for the control of bacteria and fungi in the manufacture and storage of dispersed pigments such as kaolin and montmorillonite clays, titanium dioxide, calcium carbonate, calcium sulfate, barium sulfate, magnesium silicate, and kieselsuhr used in paint and paper productions. Add 0.43-1.65 pound of Kathon WT 1.5% (195-750 gram) to each 1000 pound (453 kilogram) of fluid to provide 425 to 1675 ppm product (6.25-25 ppm active isothiazolones).

AIR WASHER SYSTEMS/ PAINT SPRAY BOOTHS

Add to the air washer sump, chill water sump, or paint spray booth to insure uniform mixing, 35 - 883 ppm Kathon WT 1.5% microbicide (0.3 - 7.46 pound or 4.5 - 113 fluid ounce of Kathon WT 1.5% per 1000 gallon of water in the system) depending upon the severity of contamination to control bacteria, fungi, and algae which cause fouling in industrial air washer systems and paint spray booths.

INTERMITTENT OR SLUG METHOD

When the system is noticeably fouled, apply 148 - 883 ppm Kathon WT 1.5% microbicide (1.26 - 7.46 pound or 19 - 113 fluid ounce of Kathon WT 1.5% per 1000 gallon of water in the system.) Repeat until control is achieved.

When microbial control is evident, add 35 - 219 ppm Kathon WT 1.5% microbicide (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of Kathon WT 1.5% per 1000 gallon of water) in the system weekly or as needed to maintain control. Badly fouled systems should be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

When the system is noticeably fouled, apply 148 - 883 ppm Kathon WT 1.5% microbicide (1.26 - 7.46 pound or 19 - 113 fluid ounce of Kathon WT 1.5% per 1000 gallon of water in the system.) Maintain this treatment level by adding a continuous feed of 35 - 219 ppm Kathon WT 1.5% (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of Kathon WT 1.5% per 1000 gallon of makeup water). Badly fouled systems must be cleaned before initial treatment.

NOTE: For use only in systems that maintain effective mist-eliminating components.

WOOD AND WOOD PRODUCTS

Kathon WT 1.5% microbicide is recommended for the protection of wood and wood products, such as landscape timbers, fences, posts, terrestrial-use pilings, cross ties, decks, and similar exterior structures from mold and mildew. Treat southern yellow pine, hemlock, ponderosa pine, and other soft woods with 148 - 1000 ppm Kathon WT 1.5% (1.26 - 8.4 pound or 13 - 128 fluid ounce of Kathon WT 1.5% per 1000 gallon) as an aqueous dip or pressure treatment for mold and mildew control. Thoroughly wet and allow to dry. A single application will afford protection for 12 weeks.

OIL FIELD INJECTION WATERS

For the control of slime-forming and sulfate-reducing bacteria in oil and gas field water systems, including enhanced recovery injection fluids, drilling, fracturing and completion fluids, slug treat with 67 - 332 ppm Kathon WT 1.5% microbicide depending on the severity of contamination. This product may be used for terrestrial and off-shore oil drilling muds and packer fluids.

Add 166 - 332 ppm Kathon WT 1.5% (6.9 - 13.9 gallon or 58.0 - 116.8 pound Kathon WT 1.5% per 1000 barrel of water) at a point in the system where it will be uniformly mixed. Repeat treatment after three days or as needed until control is achieved.

Add 67-166 ppm Kathon WT 1.5% (2.8 - 6.9 gallon or 23.5 - 58.0 pound Kathon WT 1.5% per 1000 barrel of water) every seven days or as needed to maintain control

RECIRCULATING ELECTRODEPOSITION SYSTEMS

METHOD OF ADDITION

Kathon WT 1.5% microbicide is recommended as a tankside additive for the control of bacteria, fungi, and algae in recirculating electrodeposition systems and associated rinse systems. Alternatively, Kathon WT 1.5% microbicide may be added through the components of the electrodeposition paint prior to their addition to the electrodeposition system.

TANKSIDE ADDITION TO ELECTRODEPOSITION SYSTEMS

Kathon WT 1.5% microbicide should be dispensed into the recirculating rinse system, ultrafilter permeate, or final distilled rinse system at a point to ensure uniform mixing. When the system is noticeably fouled, add 667-2333 ppm Kathon WT 1.5% microbicide (6.7-23.3 gallon per 10,000 gallon of fluid in the system). This will provide 10-35 ppm of active ingredient. Repeat until control is achieved.

Avg. Gross: LB KG
Net: LB KG
Avg. Tare: LB KG

ACCEPTED
with COMMENTS
in EPA Letter Dated:

4 3 4

DEC 14 2000
Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.
707-133

Container: Label
Code Number Number
WT1.5EPA
10/26/00

STORAGE AND DISPOSAL
PESTICIDE STORAGE

Do not contaminate water, food or feed by storage, disposal or cleaning of equipment.
Do not apply this product in a way that will contact workers or other persons.

PESTICIDE DISPOSAL

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

METAL CONTAINERS

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

PLASTIC CONTAINERS

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

GENERAL

CONSULT FEDERAL, STATE, OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES.

Date of Manufacture: location for date
EPA Reg. No. 707-133
EPA Est. No. establishment number

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

For the control of bacteria, algae, and fungi, add Kathon WT 1.5% microbicide to: industrial recirculating water cooling towers, industrial recirculating closed loop water cooling systems, brewery pasteurizers, can warmers, retort water systems, industrial scrubbing systems, evaporative condenser water systems, hydrostatic sterilizer water systems, air conditioner/refrigeration condensate water systems, coal slurry systems, immersion ultrasonic tank water, laboratory equipment water baths and influent water filtration systems. Add Kathon WT 1.5% microbicide at some point in the system to insure uniform mixing.

When the system is noticeably fouled, apply 148 - 883 ppm Kathon WT 1.5% microbicide (1.26 - 7.46 pound or 19 - 113 fluid ounce of Kathon WT 1.5% per 1000 gallon of water in the system.) Repeat until control is achieved. Badly fouled systems should be cleaned before treatment is begun.

When microbial control is evident, add 35 - 219 ppm Kathon WT 1.5% microbicide (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of Kathon WT 1.5% per 1000 gallon of water in the system) weekly or as needed to maintain control.

PAPERMILLS

For the control of bacteria, algae and fungi, add Kathon WT 1.5% microbicide to the Beater, Hydropulper, or Fan or Broke Storage Pumps or some other point in the system to insure uniform mixing.
Apply 0.44 to 1.5 lb (7 - 23 fluid ounce) of Kathon WT 1.5% microbicide per ton (dry basis) of pulp or paper produced as a slug dose. If needed, repeat daily. Badly fouled systems should be cleaned before initial treatment.

When microbial control is evident, add 333-1000 ppm Kathon WT 1.5% microbicide (3.3-10 gallon per 10,000 gallon of fluid in the system). This will provide 5-15 ppm of active ingredient. A change of frequency of treatment may be required depending upon the rate of dilution of the preservative with the makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness and system design.

TREATMENT OF ELECTRODEPOSITION PAINT COMPONENTS
INITIAL DOSE OF PAINT COMPONENTS

Kathon WT 1.5% microbicide should be added to the resin, pigment, or other component of the electrodeposition paint at a level to ensure that the final use-dilution fluid will contain 333-2333 ppm product (5-35 ppm active ingredient).

SUPPLEMENTAL TANKSIDE DOSING OF ELECTRODEPOSITION SYSTEMS

If additional microbial control is necessary, Kathon WT 1.5% microbicide may be added to the electrodeposition system tankside to supplement microbicide incorporated through paint components. If the system becomes noticeably fouled, add 667 - 2333 ppm Kathon WT 1.5% microbicide (6.7 - 23.3 gallon per 10,000 gallon of fluid in the system). This will provide 10 - 35 ppm of active ingredient. Repeat until control is achieved.

When microbial control is evident, add 333-1000 ppm Kathon WT 1.5% microbicide (3.3-10 gallon per 10,000 gallon of fluid in the system) weekly or as needed. This will provide 5-15 ppm of active ingredient.

NOTE: Regardless of the manner of incorporation, the total active ingredient level in the system should at no time exceed 35 ppm (equivalent to 2333 ppm Kathon WT 1.5% microbicide or 23.3 gallon per 10,000 gallon system fluid).

ULTRA FILTRATION UNITS AND NON-MEDICAL/NON-POTABLE REVERSE OSMOSIS SYSTEMS

Kathon WT 1.5% Microbicide is recommended for the control of bacteria and fungi in ultra filtration units and non-medical/non-potable reverse osmosis systems. Use of Kathon WT 1.5% microbicide in potable water or dialysis is prohibited. Add 10 - 333 ppm of Kathon WT 1.5% microbicide (0.15 - 5 ppm active ingredient) into industrial ultra filtration or reverse osmosis systems by either continuous feed or periodic injection. Compatibility of Kathon WT 1.5% microbicide with reverse osmosis membranes should be confirmed with membrane manufacturers.

For the control of bacteria and fungi in carbon beds, add 10 - 333 ppm of Kathon WT 1.5% microbicide (0.15 - 5 ppm active ingredient) by either continuous or batch feed. For periodic membrane cleaning, add 0.4 - 1.0 lb of Kathon WT 1.5% microbicide to every 120 gallon of cleaning solution (6 - 15 ppm active ingredient). Badly fouled systems should be cleaned before treatment is begun.

INDUSTRIAL WASTEWATER TREATMENT SYSTEMS AND SEWAGE SYSTEMS

Kathon WT 1.5% microbicide is recommended for the control of bacteria, fungi, and algae in industrial wastewater treatment and sewage systems. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority.

When the system is noticeably fouled, apply 148 - 883 ppm Kathon WT 1.5% microbicide (1.26 - 7.46 pound or 19 - 113 fluid ounce of Kathon WT 1.5% per 1000 gallon of water in the system.) Repeat until control is achieved. Badly fouled systems should be cleaned before treatment is begun.

When microbial control is evident, add 35 - 219 ppm Kathon WT 1.5% microbicide (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of Kathon WT 1.5% per 1000 gallon of water in the system) weekly or as needed to maintain control.

Kathon WT 1.5% microbicide weighs 8.4 pound/gallon.