

KATHON[®] 886 MW 1.5%

Made in USA

Avg. Gross: 1.13 KG
 Net: 1.13 KG
 Avg. Tare: 1.13 KG

Industrial Microbicide for use in Metalworking and Hydraulic Fluids
 Polymer Latices, Adhesives, Paints, Tackifiers, Dispersed Pigments,
 Building Materials, Metal Cleaning Fluids, and Photoprocessing Systems



100 INDEPENDENCE MALL WEST
 PHILADELPHIA, PA 19108
 TELEPHONE: (215) 592-3000

Lot
 Number
 ()



ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one	1.11%
2-Methyl-4-isothiazolin-3-one	0.39%

INERT INGREDIENTS:

Total:	98.5%
	100.0%

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Do not induce vomiting. Drink promptly a large quantity of milk, egg whites, gelatin solution, or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

IF ON SKIN: Wash thoroughly with soap and water. Remove and wash contaminated clothing before re-use.

IF IN EYES: Flush with plenty of water for at least 15 minutes. Call a physician.

IF INHALED: Remove immediately to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Call a physician.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression, and convulsions may be necessary.

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

CONDITIONS OF SALE AND WARRANTY

Rohm and Haas warrants that this product conforms to its chemical description and is reasonably fit for the purpose stated on the label only when used in accordance with label directions under normal conditions of use. ROHM AND HAAS MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, EITHER OF MERCHANTABILITY OR FITNESS, FOR A PARTICULAR USE. Handling, storage, and use of the product by Buyer or User are beyond the control of Rohm and Haas and Seller. Risks such as ineffectiveness or other unintended consequences resulting from, but not limited to, failure to follow directions will be assumed by the Buyer or User. IN NO CASE WILL ROHM AND HAAS OR SELLER BE HELD LIABLE FOR CONSEQUENTIAL, SPECIAL, OR INDIRECT DAMAGES RESULTING FROM THE HANDLING, STORAGE, OR USE OF THIS PRODUCT.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER
CORROSIVE
 CAUSES EYE DAMAGE AND SKIN BURNS
 MAY CAUSE ALLERGIC SKIN REACTION
 MAY BE HARMFUL IF INHALED
 MAY BE FATAL IF SWALLOWED OR ABSORBED THROUGH THE SKIN

Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid breathing vapor or mist. Avoid contamination of food. Do not take internally. Wash thoroughly after handling.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

U.S. Patent 4,279,762

PM 33

107-134

4-26-91

Accepted Stamp on pg. 3 of 4
 107-4

Product
Code
(91)

«LNI»

Container:
Code Number Label Number
«SNI» 886MWEPA

STORAGE AND DISPOSAL

PROHIBITIONS

This product is corrosive to mild steel. Do not store or transport in unlined metal containers. Do not contaminate food or feed by storage, disposal, or cleaning of equipment.

PESTICIDE DISPOSAL

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

METAL CONTAINERS

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

PLASTIC CONTAINERS

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

GENERAL

CONSULT FEDERAL, STATE, OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES.

Date of Manufacture: location for date
EPA Reg. No. 707-134
EPA Est. No: establishment number.

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling

METALWORKING FLUIDS

Kathon 886 MW 1.5% microbicide is recommended for the control of bacteria and fungi in soluble and emulsifiable-type aqueous metalworking fluids.

For the maintenance of a non-fouled system, use Kathon 886 MW 1.5% microbicide at 32 fluid ounce per 1000 gallon of emulsion (2 pound) every 4 weeks or 32-154 fluid ounce per 1000 gallon emulsion (2-10 pound) every 8-12 weeks.

For a noticeably fouled system, use an initial dose of 64-154 fluid ounce per 1000 gallon emulsion (4-10 pound) to be followed by subsequent maintenance dosages depending upon the treatment interval noted above. A higher dosage range and/or increased frequency of treatment may be required depending upon rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

The preservative should be dispensed into the use-dilution of the metalworking fluid using a metering pump and uniformly dispersed throughout the system.

HYDRAULIC FLUIDS

Kathon 886 MW 1.5% microbicide is recommended as a preservative for use in the manufacture and use of high water-based hydraulic fluids and invert emulsion hydraulic fluids typically prepared by emulsifying 40% by volume water in 60% by volume of mineral oil using an oil-soluble emulsifying agent.

For the maintenance of a non-fouled system, use Kathon 886 MW 1.5% microbicide at 110-135 fluid ounce (7.2-8.8 pound) per 1000 gallon fluid every 8 weeks.



For a noticeably fouled system, use an initial dose of 135-235 fluid ounce (8.8-15.4 pound) per 1000 gallon fluid to be followed by subsequent maintenance dosage.

A higher dosage range and/or increased frequency of treatment may be required depending upon rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. The preservative should be dispensed into the use-dilution of the hydraulic fluid using a metering pump and uniformly dispersed throughout the system.

POLYMER LATEX PRESERVATION

Kathon LX 1.5% microbicide is recommended for the control of bacteria and fungi in the manufacture and storage of synthetic and natural polymer latices including: acrylic; styrene/butadiene; carboxylated styrene/butadiene; ethylene/vinyl acetate; and biopolymers intended for industrial use, such as a xanthum gum, gum arabic, guar gum, protein-derived polymers, starches, and casein-derived polymers. Add 0.43-3.3 pound of Kathon LX 1.5% (195 gram-1.5 kilogram) to each 1000 pound (453 kilogram) of emulsion to provide 425-3350 ppm product (6.25-50 ppm active isothiazolones).

NOTE: To insure uniform mixing, add Kathon LX 1.5% to latex or solutions slowly with agitation. The actual required concentrations will depend upon such factors as the specific substance to be treated, frequency of repeated microbial contamination expected, and level of production required.



W
10/14

ADHESIVE AND TACKIFIER PRESERVATION

Kathon LX 1.5% microbicide is recommended as an in-container preservative for the control of bacteria and fungi in water-soluble and water-dispersed adhesives such as animal glues, vegetable glues, natural rubber latices, polyvinyl acetate, styrene butadiene and acrylic latices. Kathon LX 1.5% is recommended as a preservative for tackifiers derived from rosin and hydrocarbon resins. Add 0.43-1.65 pound of Kathon LX 1.5% (195-750 gram) to each 1000 pound (453 kilogram) of fluid to provide 425-1675 ppm (6.25-25 ppm active isothiazolones).

PAINT AND COATING PRESERVATION

Kathon LX 1.5% microbicide is recommended as an in-container preservative for the control of bacteria and fungi in water-based coatings such as paper and wood coatings and paints used for architectural product finishes, and special-purpose coatings. Add 0.43-1.65 pound of Kathon LX 1.5% (195-750 gram) to each 1000 pound (453 kilogram) of fluid to provide 425-1675 ppm product (6.25-25 ppm active isothiazolones).

BUILDING MATERIAL PRESERVATION

Kathon LX 1.5% microbicide is recommended as an in-container preservative for the control of bacteria and fungi in building materials such as mastics, caulks, joint cements, spackling, and grouting. Add 0.43-1.65 pound of Kathon LX 1.5% microbicide (195-750 gram) to each 1000 pound (453 kilogram) of fluid to provide 425-1675 ppm product (6.25 to 25 ppm active isothiazolones).

DISPERSED PIGMENT PRESERVATION

Kathon LX 1.5% microbicide is recommended for the control of bacteria and fungi in the manufacture and storage of dispersed pigments such as kaolin and montmorillite clays, titanium dioxide, calcium carbonate, calcium sulfate, barium sulfate, magnesium silicate, and kieselguhr used in paint and paper productions. Add 0.43-1.65 pound of Kathon LX 1.5% (195-750 gram) to each 1000 pound (453 kilogram) of fluid to provide 425 to 1675 ppm product (6.25-25 ppm active isothiazolones).

METAL CLEANING FLUID PRESERVATION

Kathon LX 1.5% microbicide is recommended as a preservative for use in the manufacture and use of alkaline, acid and emulsion-based metal cleaning fluids typically used in electroplating, phosphatizing, galvanizing, and general metal cleaning operations. For addition to a metal cleaning concentrate, add Kathon LX 1.5% at a level to ensure that the final use-dilution fluid will contain 425-1675 ppm product (6.25-25 ppm active isothiazolones). For direct addition to a fouled system, add 54-214 fluid ounce (3.6-14.1 pound) of Kathon LX 1.5% to each 1000 gallon of use-dilution metal cleaning fluid every 3-4 weeks to provide 425-1675 ppm product (6.25-25 ppm active isothiazolones). A higher dosage range and/or increased frequency of treatment may be required depending upon rate of dilution of the preservative with make-up fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. The preservative should be dispensed into the use-dilution metal cleaning fluid using a metering pump and uniformly dispersed throughout the system.

COMMERCIAL PHOTOPROCESSING SYSTEM PRESERVATION

Kathon LX 1.5% microbicide is recommended to prevent slime formation or accumulation in filters and ion exchange resin tanks of commercial photoprocessing systems. For the maintenance of a non-fouled system, use Kathon LX 1.5% at 32-64 fluid ounce (2.1-4.2 pound) per 1000 gallon water in the system once weekly, or as needed, to maintain control of slime. For a noticeably fouled system, use an initial dose of 64-154 fluid ounce (4.2-10.1 pound) per 1000 gallon water to be followed by subsequent maintenance dosage. A high dosage range and/or increased frequency of treatment may be required depending upon rate of dilution of preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. The preservative should be dispensed into the final rinse or used water collection tank.

Kathon 886 MW 1.5% microbicide weighs 8.4 pound/gallon.