11012 17

144

CENTER PANEL

KATHON ED 1.5%

INDUSTRIAL MICROBICIDE FOR USE IN RECIRCULATING ELECTRODEPOSITION SYSTEMS

ACTIVE INGREDIENTS:	
5-Chloro-2-methyl-4-isothiazolin-3-one	1.15%
2-Methyl-4-isothiazolin-3-one	0.35%
INERT INGREDIENTS:	
TOTAL	100.00%

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Do not induce vomiting. Drink promptly a large quantity of egg

whites, gelatin solution, or if these are not available, drink large quantities of water. Avoid alcohol. Call physician immediately. Never give anything by mouth to an unconscious

person.

IF ON SKIN: Wash thoroughly with soap and water. Remove and wash

contaminated clothing before re-use.

IF IN EYES: Flush with plenty of water for at least 15 minutes. Call a

physician.

IF INHALED: Remove immediately to fresh air. If not breathing, apply

artificial respiration. If breathing is difficult, give

oxygen. Call physician.

NOTE TO PHYSICIAN:

Probably mucosal damage may contraindicate the use of gastric lavage.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

MANUFACTURED BY:

Rohm and Haas Company Philadelphia, PA 19105 EPA Est. No. 707-EN-1 EPA Reg. No. 707-218

1	A	(7	C	•	E	P	T	E	D
			Ur		,	5	19	89		
				e F e d l ed l v	пo	lerd d R lor	il In	nteci nteri pest	had ide ide ioid	e. Act. e

NET CONTENTS_____

uzm + 5 !989

TITRECTIONS FOR USE

1 1

It is a violation of Federal Law to use this product in a mamber incommittent with its labeling.

METHOD OF ADDITION

Kathon ED 1.5% microbicide is recommended as a tankside additive for the control of bacteria, fungi, and algae in recirculating electrodeposition systems and associated rinse systems.

Alternatively, Kathon ED 1.5% microbicide may be added through the components of the electrodeposition paint prior to their addition to the electrodeposition system.

TANKSIDE ADDITION TO ELECTRODEPOSITION SYSTEMS

Kathon ED 1.5% microbicide should be dispensed into the recirculating rinse system, ultrafilter permeate, or final distilled rinse system at a point to ensure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, add 667-2333 ppm Kathon ED 1.5% microbicide (5.6-19.6 gallons per 10.000 gallons of fluid in the system). This will provide 10 to 35 ppm of active ingredient. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 333 to 1000 ppm Kathon ED 1.5% microbicide (2.8-8.4 gallons per 10,000 gallons of fluid in the system) weekly or as needed to maintain the system. This will provide 5-15 ppm of active ingredient. A change of frequency of treatment may be required depending on the rate of dilution of the preservative with the makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

TREATMENT OF ELECTRODEPOSITION PAINT COMPONENTS

INITIAL DOSE OF PAINT COMPONENTS

Kathon ED 1.5% microbicide should be added to the resin, pigment, or other component of the electrodeposition paint at a level to ensure that the final use-dilution fluid will contain 333-2333 ppm product (5-35 ppm active ingredient).

SUPPLEMENTAL TANKSIDE DOSING OF ELECTRODEPOSITION SYSTEM

If additional microbial control is necessary, Kathon ED 1.5% microbicide may be added to the electrodeposition system tankside to supplement microbicide incorporated through paint components.

If the system becomes noticeably fouled, add 667-2333 ppm Kathon ED 1.5% microbicide (5.6-19.6 gallons per 10,000 gallons of fluid in the system). This will provide 10-35 ppm of active ingredient. Repeat until control is achieved.

When microbial control is evident, the system can be maintained by addition of 333-1600 ppm Kathon ED 1.5% microbicide (2.8-8.4 gallons per 10,000 gallons of fluid in the system) weekly or as needed. This will provide 5-15 ppm of active ingredient.

RIGHT PANEL -- (Continued)

NOTE: Regardless of the manner of incorporation, the total active ingredient level in the system should at no time exceed 35 ppm (equivalent to 2333 ppm Kathon ED 1.5% microbicide or 19.6 gallons per 10.000 gallons system fluid).

Kathon ED 1.5% microbicide weighs 9.9 lbs./gallon.

STORAGE AND DISPOSAL

PROHIBITIONS

1-11 -

This product is corrosive to mild steel. Do not store or transport in unlined metal containers. Do not contaminate food or feed by storage, disposal, or cleaning of equipment.

PESTICIDE DISPOSAL

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

METAL CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incinerator, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

GENERAL

CONSULT FEDERAL, STATE, OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES.

SEP | 5 | 989

Under the Federal I or on the Fungicide, and Rederic in the case amended, for the pestitude registered under EPA Reg. No. 1992 - 28

Made in U.K.

1791-718

4004

LEFT PANEL

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

CORROSIVE

CAUSES EYE DAMAGE AND SKIN BURNS

MAY CAUSE ALLERGIC SKIN REACTION

HARMFUL IF INHALED

HARMFUL IF SWALLOWED

Do not get in eyes, on skin, on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid breathing vapor or mist. Avoid contamination of food. Do not take internally. Wash thoroughly after handling.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

CONDITIONS OF SALE AND WARRANTY

Rohm and Haas warrants that the product conforms to its chemical description and is reasonably fit for the purpose stated on the label only when used in accordance with label directions under normal conditions of use. ROHM AND HAAS MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES EITHER OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE. Handling, storage and use of the product by Buyer or User are beyond the control of Rohm and Haas and Seller. Risks such as ineffectiveness or other unintended consequences resulting from, but not limited to, failure to follow label directions will be assumed by the Buyer or User. IN NO CASE WILL ROHM AND HAAS OR SELLER BE HELD LIABLE FOR CONSEQUENTIAL, SPECIAL OR INDIRECT DAMAGES RESULTING FROM THE HANDLING, STORAGE OR USE OF THIS PRODUCT.

ACCEPTED

SEP 1 5 1989

Under the Fe teral Inecticade, Fungicide, and hidenticals Act as amended, for the pessuade resistered under EPA Reg. No. 477

(0142n/11n)