

Malacoat

CAUTION HARMFUL IF SWALLOWED

Do not take internally. If swallowed, give emetic of mustard and call a physician. Avoid breathing of mist. Avoid contact with skin. In case of spillage on skin, wash with soap and water. Do not use in milk house or in the edible products areas of food processing plants. Store away from feed and food stuffs. Do not store near fire or flame. Keep out of reach of children.

This product is toxic to fish. Do not contaminate water by cleaning of equipment, or disposal of wastes.

WARRANTY: M.F.A. Oil Company warrants that this product conforms to its chemical description and is reasonably fit for the purpose stated on the label when used in accordance with directions under normal conditions of use. Neither this warranty nor any other warranty of merchantability or fitness for a particular purpose, express or implied, extends to the use of this product contrary to label instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to M.F.A. Oil Company, and buyer assumes the risk of any such use. K70

CAUTION

KEEP OUT OF REACH OF CHILDREN
SEE OTHER CAUTIONS ON SIDE PANEL



MALACOAT

Emulsifiable Concentrate
of premium grade technical Malathion
FOR PROTECTION OF
STORED GRAIN AGAINST INSECTS

ACTIVE INGREDIENTS	
Malathion*	57%
Xylene	32%
INERT INGREDIENTS	11%
	100%

*O, O-dimethyl dithiophosphate of diethyl mercaptosuccinate
One Gallon Net Contents

Manufactured
For



Columbia,
Mo.

USDA Reg. No. 74619

Malacoat

DIRECTIONS

For the protection of Stored Grains such as wheat, oats, rice, corn, rye, barley, grain sorghum, and field or garden seeds, against confused flour beetle, rice weevil, granary weevil, saw-toothed grain borer, flat grain beetle, red flour beetle, rusty grain borer, lesser grain borer, and Indian meal moth.

Apply 1 pint Malacoat mixed in 2 to 5 gallons water for each 1,000 bushels as grain is loaded or turned into final storage.

To protect stored grains from attack by Indian meal moth, apply Malacoat mixed 1/2 pint in 1 to 2 gallons of water per 1,000 square feet of grain surface. Treat immediately after grain is loaded into storage and repeat if necessary.

For residual wall, floor, and machinery spray in grain elevators, box cars, truck beds, empty feed warehouses, etc., apply 1 gallon Malacoat mixed in 25 gallons of water, wetting surface thoroughly. Clean facilities and remove and burn all sweepings and debris prior to treatment.

ACCEPTED

FEB 8 - 1971

UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC PESTION REGISTERED
UNDER NO. 7719 SUBJECT
TO ATTACHED