

USE DIRECTIONS

This product can be used in conventional applicators. Use this product only for the recommended use and at the recommended dosages.

Applications are to be made only by, or under the directions of trained or experienced personnel of public health agencies or pest control operators.

Mix this product with water and agitate while using and reagitrate if allowed to stand.

SUB-SURFACE TERMITE CONTROL

Mix 1 gallon of this product with 60 gallons water for a resultant of 0.3% emulsion.

(A) Buildings with Crawl Spaces

- (1) Apply 2 gallons finished emulsion per 5 linear feet to critical areas only under the house, such as along the inside of foundation walls, around piers, sewer pipes, conduits, etc. Trench according to directions in part (2) below.
- (2) Along the outside of foundation walls, dig a narrow trench, with a band no wider than six inches, such trench to be dug no deeper than the top of the footing. If the trench is less than 15 inches in depth to the top of the footings, apply 1 gallon per 5 linear feet. Replace the soil and apply another 1 gallon per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply 2 gallons per 5 linear feet. Replace the soil and apply another 2 gallons per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. A trench 30 inches deep is a maximum depth required alongside those foundations where the top of the footings is greater than 30 inches deep. In lieu of trenching to a 30 inch depth, make the trench 12 to 15 inches deep and rod to footing, spacing the holes about 1 foot apart. Cover final treatment with a layer of soil.
- (3) Apply 1 gallon per 10 square feet of soil surface under attached porches, entrance platforms, utility entrances and similar situations where slab or fill is at the grade level. Where crawl spaces exist, treat as described in part (1) above.
- (4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footing.

(B) Building with Concrete Slab on the Ground.

- (1) Apply 1 gallon finished emulsion per 10 square feet as an over all treatment under the slab as well as under attached porches, entrance platforms, utility entrances and similar situations where slab or fill is at grade level. In case of washed gravel, cinders, or similar coarse material, increase the dosage by at least one-half. Preconstruction treatment of soil beneath concrete slabs: If soil is treated and the concrete slab is not poured shortly thereafter on the same day, a polyethylene sheeting or other waterproof material must be placed over the treated soil.
- (2) Apply 2 gallons finished emulsion per 5 linear feet to critical areas only under the slab, such as along the inside foundation walls around sewer pipes, conduits, etc. Trench as in part (3) below.
- (3) Along the outside of foundation walls dig a narrow trench with a band no wider than six inches, no deeper than the top of the footings, but no deeper than 15 inches unless the footing is much deeper in some places on account of the slope of the land, then treat as under (A) (2) and cover with a layer of soil.
- (4) Treat all voids in hollow masonry units of the foundation at the rate of

(Continued on other side)



ACCEPTED
SEP 10 1973
NET CONTENTS
INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
REGISTERED
SUBJECT
TO ESTABLISHED COMMENTS

DIELDRIIN E.C. 1.5

For Professional Use Only
for subsurface termite control

WARNING

KEEP OUT OF REACH OF CHILDREN
SEE OTHER WARNINGS ON SIDE PANEL

ACTIVE INGREDIENTS:

Dieldrin*	18.7%
Xylene Range Aromatic Solvent	78.3%
INERT INGREDIENTS	3.0%

*Equivalent to 15.9% W. Hexachloro-epoxyoctahydro-endo, exo-dimethanonaphthalene and 2.8% W of Related Compounds.

(Contains 1.5 pound actual Dieldrin per gallon)

WARNING — FLAMMABLE!

KEEP AWAY FROM HEAT OR OPEN FLAME



Manufactured for

Columbia, Mo. 65201

EPA Reg. No. 746-117

at least 1 gallon per 5 linear feet of wall, cal near the footings.

(C) Buildings with Basements

- (1) Apply 1 gallon finished emulsion per 10 treatment under the basement flooring, as entrance platforms, utility entrances, and fill is at the grade level. In case of wash coarse material, increase the dosage by a spaces exist, treat as described in part (2
- (2) Apply 2 gallons per 5 linear feet to critic ment floorings, as well as porches and e such as along the inside of foundation walls piers, etc. Trench according to directions i
- (3) Along the outside of foundation walls, dig no wider than six inches, such trench to t of the footings. If the trench is less than of the footings, apply 1 gallon per 5 line apply another 1 gallon per 5 linear feet to fill with a thin layer of soil. If the trenc depth to the top of the footings, apply 2 place the soil and apply another 2 gallons fill. Cover the back fill with a thin layer deep is a maximum depth required alongs of the footing is greater than 30 inches d 30 inch depth, make the trench 12 to 1 wider than six inches, and rod to footin foot apart and cover final treatment with
- (4) Treat all voids in hollow masonry units of 1 gallon per 5 linear feet of wall. It is b the footings.

WARNING

Hazardous if Swallowed, Inhaled or Absorbed through or spray mist. Do not get in eyes, on skin or clothin or clothing, immediately remove clothing and flush water. For eyes, get medical attention. If swallowed, and get medical attention.

Wash thoroughly with soap and water after handling protective clothing. During commercial applications o wear clean rubber gloves and a mask or respirator of Bureau of Mines.

For subsurface use only. Do not apply or allow to dri tected humans or animals or aquatic environments, foodstuffs.

This product is toxic to fish and wildlife. Birds fee treated areas may be killed. Keep out of lakes, s product only as specified on the label.

Do not reuse empty containers. Follow flush and dr bury in non-crop land away from water supplies.

NOTICE OF WARRANTY

M.F.A. OIL COMPANY MAKES NO WARRANTY FITNESS OR ANY PURPOSE, OR OTHERWISE concerning this product or its uses, which extend b under normal conditions in accord with the stateme

1-16-117

ACCEPTED

SEP 10 1973

NET CONTENTS

THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT

REGISTERED

SUBJECT

TO THE FOLLOWING COMMENTS



DIELDRIIN

E.C. 1.5

For Professional Use Only
for subsurface termite control

WARNING
KEEP OUT OF REACH OF CHILDREN
SEE OTHER WARNINGS ON SIDE PANEL

ACTIVE INGREDIENTS:	
Dieldrin*	18.7%
Xylene Range Aromatic Solvent	78.3%
INERT INGREDIENTS	3.0%

*Equivalent to 15.9% W. Hexachloro-epoxyoctahydro-endo, exo-dimethanonaphthalene and 2.8% W of Related Compounds.

(Contains 1.5 pound actual Dieldrin per gallon)

WARNING — FLAMMABLE!
KEEP AWAY FROM HEAT OR OPEN FLAME

Manufactured for  Columbia, Mo. 65201

EPA Reg. No. 746-117

- at least 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footings.
- (C) Buildings with Basements
- (1) Apply 1 gallon finished emulsion per 10 square feet as on an over-all treatment under the basement flooring, as well as under attached porches, entrance platforms, utility entrances, and similar situations where slab fill is at the grade level. In case of washed gravel, cinders, or similar coarse material, increase the dosage by at least one-half. Where crawl spaces exist, treat as described in part (2) below.
 - (2) Apply 2 gallons per 5 linear feet to critical areas only under the basement floorings, as well as porches and entrances having crawl spaces, such as along the inside of foundation walls, around sewer pipes, conduits, piers, etc. Trench according to directions in part (3) below.
 - (3) Along the outside of foundation walls, dig a narrow trench, with a band no wider than six inches, such trench to be dug no deeper than the top of the footings. If the trench is less than 15 inches in depth to the top of the footings, apply 1 gallon per 5 linear feet. Replace the soil and apply another 1 gallon per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply 2 gallons per 5 linear feet. Replace the soil and apply another 2 gallons per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. A trench 30 inches deep is a maximum depth required alongside foundations where the top of the footing is greater than 30 inches deep. In lieu of trenching to a 30 inch depth, make the trench 12 to 15 inches deep with a band no wider than six inches, and rod to footing, spacing the holes about 2 foot apart and cover final treatment with a layer of soil.
 - (4) Treat all voids in hollow masonry units of the foundation at the rate of 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footings.

WARNING

Hazardous if Swallowed, Inhaled or Absorbed through Skin. Do not breathe vapors or spray mist. Do not get in eyes, on skin or clothing. In case of spillage on skin or clothing, immediately remove clothing and flush eyes or skin with plenty of water. For eyes, get medical attention. If swallowed, induce vomiting immediately and get medical attention.

Wash thoroughly with soap and water after handling in any circumstances. Wear protective clothing. During commercial applications or prolonged mixing operations, wear clean rubber gloves and a mask or respirator of a type approved by the U. S. Bureau of Mines.

For subsurface use only. Do not apply or allow to drift to areas occupied by unprotected humans or animals or aquatic environments. Do not contaminate feed or foodstuffs.

This product is toxic to fish and wildlife. Birds feeding on uncovered sub-surface treated areas may be killed. Keep out of lakes, streams or ponds. Apply this product only as specified on the label.

Do not reuse empty containers. Follow flush and drain procedure then crush and bury in non-crop land away from water supplies.

NOTICE OF WARRANTY

M.F.A. OIL COMPANY MAKES NO WARRANTY OF MERCHANTABILITY, FITNESS OR ANY PURPOSE, OR OTHERWISE, EXPRESS OR IMPLIED, concerning this product or its uses, which extend beyond the use of the product under normal conditions in accord with the statements made on this label.

M-1427B-H