

PITTCOLOR[®]

**WATER-TREATING AGENT
BACTERICIDE • ALGAECIDE • BLEACH**

Granular Calcium Hypochlorite	65% Available Chlorine
ACTIVE INGREDIENT	Calcium Hypochlorite 65%
INERT INGREDIENTS	35%
	<hr/> 100%

DANGER!
KEEP OUT OF THE REACH OF CHILDREN.

PRACTICAL TREATMENT (FIRST AID)

- **EYE OR SKIN CONTACT:** Flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. For eye contact get immediate medical attention. If skin irritation occurs get medical attention.
- **INHALATION:** Remove to fresh air. If signs of irritation or discomfort occur take immediately to a hospital or physician.
- **SWALLOWING:** If conscious feed bread soaked in milk followed by olive oil or cooking oil. **DO NOT** induce vomiting. Take immediately to a hospital or physician. If unconscious or in convulsions take immediately to a hospital or physician. Do not give anything by mouth to an unconscious person.

**SEE ADDITIONAL PRECAUTIONS
ON BACK PANEL**



25 Pounds
11.3 Kilograms

L10A-1B-1181C3

PPG
INDUSTRIES

EPA Reg. No. 748-217
EPA Est. 748-OH-1

Manufactured by
PPG INDUSTRIES INC
Chemicals Group
One Gateway Center
Pittsburgh, PA 15222

ACCEPTED
748-217
MAY 1982

KEEP OUT OF THE REACH OF CHILDREN

CAUTION: IRRITANT • IRRITABLE • CAUSES SKIN AND EYE DAMAGE • MAY BE FATAL IF SWALLOWED • IRRITATING TO NOSE AND THROAT. Wear goggles and gloves when using. Avoid contact with eyes. Rinse thoroughly with water. If swallowed, seek medical attention immediately.

For more information, contact the manufacturer or the regulatory office of EPA.

STRONG OXIDIZING AGENT. MIX ONLY WITH WATER. USE ONLY A CLEAN, DRY SCOOP MADE OF METAL OR PLASTIC. EACH TIME PITTCOLOR® IS TAKEN FROM THE CONTAINER. Do not add to fire. If any sparks or fire occur, immediately stop using the product. Such use may cause a violent reaction leading to fire or explosion. CONTAMINATION WITH MOISTURE, ACIDS, ORGANIC MATTER, OTHER CHEMICALS OR EASILY COMBUSTIBLE MATERIALS SUCH AS PETROLEUM OR PAINT PRODUCTS MAY START A CHEMICAL REACTION WITH GENERATION OF HEAT, LIBERATION OF HAZARDOUS GASES AND POSSIBLE GENERATION OF A FIRE OR EXPLOSION. Do not use in a confined space. Do not use in a metal container. If possible, isolate material in a container with vented area. Flood with large volumes of water if necessary.

DIRECTIONS FOR SWIMMING POOLS PITTCOLOR SWIMMING POOL DISINFECTANT AND POOL SANITATION

PITTCOLOR® disinfectant contains 65% available chlorine. It provides a rapid source of chlorine needed to protect pools against the growth of bacteria and algae. For effective pool sanitation, maintain a free chlorine residual of 0.6 to 1.0 parts per million (ppm) of the amount required by local regulations. Free chlorine residual is determined by a test kit which may be obtained from your swimming pool dealer.

PITTCOLOR® disinfectant may be added to the pool by treating the entire pool surface with a solution of 1.0 to 1.5 parts per million (ppm) as a stock solution prepared by adding 1.0 to 1.5 ounces of PITTCOLOR® disinfectant to 100 gallons of water.

For every 10,000 gallons of water, add 1.0 to 1.5 ounces of PITTCOLOR® disinfectant to 100 gallons of water. For every 10,000 gallons of water, add 1.0 to 1.5 ounces of PITTCOLOR® disinfectant to 100 gallons of water. For every 10,000 gallons of water, add 1.0 to 1.5 ounces of PITTCOLOR® disinfectant to 100 gallons of water.

For every 10,000 gallons of water, add 1.0 to 1.5 ounces of PITTCOLOR® disinfectant to 100 gallons of water. For every 10,000 gallons of water, add 1.0 to 1.5 ounces of PITTCOLOR® disinfectant to 100 gallons of water. For every 10,000 gallons of water, add 1.0 to 1.5 ounces of PITTCOLOR® disinfectant to 100 gallons of water.

For every 10,000 gallons of water, add 1.0 to 1.5 ounces of PITTCOLOR® disinfectant to 100 gallons of water. For every 10,000 gallons of water, add 1.0 to 1.5 ounces of PITTCOLOR® disinfectant to 100 gallons of water. For every 10,000 gallons of water, add 1.0 to 1.5 ounces of PITTCOLOR® disinfectant to 100 gallons of water.

A dosage of 1.0 to 1.5 ounces of PITTCOLOR® disinfectant or 2 quarts of stock solution per 10,000 gallons of water is suggested. This dosage will add 1.0 to 1.5 ppm free chlorine residual (0.6 to 1.0 ppm).

One ounce = 1 tablespoon
2 quarts of stock solution
One cup = 9.0 ounces = 16 tablespoons
4 quarts = stock solution

Supplement the test kit with a pH test kit to determine the pH of the pool water. The proper pH is 7.2 to 7.8. If the pH is below 7.2, add 1.0 to 1.5 ounces of pH increaser to 10,000 gallons of water. If the pH is above 7.8, add 1.0 to 1.5 ounces of pH reducer to 10,000 gallons of water.

Maintain the proper pH and alkalinity of the pool water is necessary to obtain proper disinfection with PITTCOLOR® disinfectant. The proper pH is 7.2 to 7.8. The proper alkalinity is 100 to 150 ppm. Check the pH and alkalinity daily with a pH test kit. At a total alkalinity of 100 ppm, add 1.0 to 1.5 ounces of alkalinity increaser to 10,000 gallons of water. At a total alkalinity of 150 ppm, add 1.0 to 1.5 ounces of alkalinity reducer to 10,000 gallons of water. For more information, contact your swimming pool dealer.

L10A-1B-1181C4



OXIDIZER

5

CALCIUM HYPOCHLORITE, HYDRATED UN2880

EMERGENCY TELEPHONE NUMBER
PPG INDUSTRIES, INC., NATHAN, WV (304) 843-1300