	COFPILD
1153914 VATE	R BORME PRESERVATIVE CONCENTRATE II
WOOD PRESER	VATIVE FOR INDUSTRIAL USE ONLY
VARNI NG !	PRESERVES AND PROTECTS WOOD FROM ROT AND MILDEW KEEP OUT OF THE REACH OF CHILDREN
	Active ingredient: Eis (tributyltin) oxide
	INERT INGREDIENTS:
	PRECAUTIONARY STATEMENTS
	HAZARD TO HUMANS & DOMESTIC ANIMALS
	WARNING: CAUSES EYE AND SKIN IRRITATION. DO NOT GET ON SKIN, ON CLOTHING, OR
	IN EYES, VEAR FACE SHIELD AND RUBBER GLOVES WHEN HANDLING, MAY BE FATAL IF
	swallowed. Avoid breathing vapors or spray mist. Use in a ventilated area.
	PRACTICAL TREATMENT: IN CASE OF SKIN CONTACT, REMOVE CONTAMINATED CLOTHING AND
	IMMEDIATELY WASH SKIN WITH SOAP AND WATER. GET MEDICAL ATTENTION. WASH CONTAMI-
	NATED CLOTHING BEFORE REUSE. IF IN EYES, FLUSH EYES IMMEDIATELY WITH WATER FOR

AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. IF SWALLOWED, DO NOT INDUCE VOMIT-ING. GET IMMEDIATE MEDICAL ATTENTION. ENVIRONMENTAL HAZARD: THIS PRODUCT IS TOXIC TO FISH AND WILDLIFE. KEEP OUT OF ANY BODY OF WATER. DO NOT CONTAMINATE WATER BY CLEANING EQUIPMENT OR DISPOSAL OF

PPG INDUSTRIES, INC. COATINGS AND RESINS DIVISION ONE GATEWAY CENTER PITTSBURGH, PA 15222

WASTE.

NET CONTENTS: 53 GALLONS POUNDS PER GALLON: 8.22

18

BEST DOCUMENT AVAILABLE

W53914 WATER BORNE PRESERVATIVE CULLENTRATE II WOOD PRESERVATIVE FOR INDUSTRIAL USE ONLY

DIRECTIONS FOR USE: It is a violation of federal law to use this product in a manner inconsistent with its labeling. Elend 1 part by volume of \'53914 Mater Borne Preservative Concentrate II with 3 parts by volume of water before making application. Must be applied to unpainted, clean, dry wood. Immerse the wood parts by either flowcoating or dipping. Allow the wooden parts to dwell in the flowcoater or dip tank in contact with the water base preservative a minimum of fifteen seconds. Remove from the water base preservative and allow the wood to dry at ambient temperatures above 60°F in an area with engineered ventilation prior to painting. Use water for clean-up solvent. Mear protective clothing and rubber gloves when handling freshly-treated wooden parts. Protective clothing should be washed before reuse.

STORAGE AND DISPOSAL

PROHIBITIONS: DO NOT CONTAMINATE WATER, FOOD, OR FEED BY STORAGE OR DISPOSAL. OPEN DUMPING IS PROHIBITED.

Wood Preservative Disposal: Wood preservative flowcoat or dipping material that cannot be used or chemically reprocessed should be disposed of according to procedures approved by federal, state, or local disposal authorities.

CONTAINER DISPOSAL: 55-GALLON DRUMS SHOULD BE EITHER:

- A) Resealed and offered for reconditioning or,
- B) TRIPLE RINSED AND OFFERED FOR RECYCLING, RECONDITIONING, OR DISPOSAL IN APPROVED LANDFILL.

GENERAL DISPOSAL: CONSULT FEDERAL, STATE, OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED AETEBNATE PROCEDURES.

> EPA Reg. No. 748-228 EPA Est. No. 748-GA1 19

BEST DOCUMENT AVAILABLE