

W53470R PILT "70"

748-EUU

122

pm 21

748-244

WOOD PRESERVATIVE - FOR INDUSTRIAL USE ONLY

DANGER!

PRESERVES AND PROTECTS WOOD FROM ROT AND MILDEW
KEEP OUT OF THE REACH OF CHILDREN

ACTIVE INGREDIENT: BIS (TRIBUTYL TIN) OXIDE	0.75%
INERT INGREDIENTS:	99.25%
TOTAL	100.00%

PRECAUTIONARY STATEMENTS

HAZARD TO HUMANS & DOMESTIC ANIMALS

DANGER: CORROSIVE, CAUSES SKIN DAMAGE. DO NOT GET ON SKIN, ON CLOTHING, OR IN EYES. WEAR FACE SHIELD AND RUBBER GLOVES WHEN HANDLING. MAY BE FATAL IF SWALLOWED OR INHALED. AVOID BREATHING VAPORS. USE ONLY IN A WELL-VENTILATED AREA. DO NOT BREATHE VAPORS OR SPRAY MIST.

PRACTICAL TREATMENT: IN CASE OF SKIN CONTACT, REMOVE CONTAMINATED CLOTHING AND IMMEDIATELY WASH SKIN WITH SOAP AND WATER. GET MEDICAL ATTENTION. WASH CONTAMINATED CLOTHING BEFORE REUSE. IF IN EYES, FLUSH EYES WITH WATER. GET MEDICAL ATTENTION. IF SWALLOWED, DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION. IF INHALED, REMOVE TO FRESH AIR. USE ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. GET IMMEDIATE MEDICAL ATTENTION.

ENVIRONMENTAL HAZARDS: THIS PRODUCT IS TOXIC TO FISH AND WILDLIFE. DO NOT APPLY DIRECTLY TO WATER OR WET LANDS. DO NOT CONTAMINATE WATER BY CLEANING EQUIPMENT OR DISPOSAL OF WASTE.

CHEMICAL AND PHYSICAL HAZARDS: FLAMMABLE. KEEP AWAY FROM HEAT AND OPEN FLAME.

PPG INDUSTRIES, INC.
COATINGS AND RESINS DIVISION
ONE PPG PLACE
PITTSBURGH, PA 15272

NET CONTENTS: 55 GALLONS

ACCEPTED
 OCT 29 1984
 Under the Federal Insecticide,
 Fungicide, and Rodenticide Act,
 registered under
 EPA Reg. No. 748-244

DIRECTIONS FOR USE: W5347OR PILT "70" WOOD PRESERVATIVE - IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING. FOR INDUSTRIAL USE ONLY. MUST BE APPLIED TO UNPAINTED CLEAN, DRY WOOD. IMMERSE THE WOODEN PARTS BY EITHER FLOWCOATING OR DIPPING. ALLOW THE WOODEN PARTS TO DWELL IN THE FLOWCOATER OR DIP TANK IN CONTACT WITH THE PILT SOLUTION A MINIMUM OF 15 SECONDS. REMOVE FROM SOLUTION AND ALLOW THE WOOD TO DRY AT 65-75°F IN AN AREA WITH ENGINEERED VENTILATION FOR 90 SECONDS PRIOR TO PAINTING. USE ALIPHATIC HYDROCARBON SOLVENT FOR CLEAN-UP.

NOTE TO USER: THIS PRODUCT IS DESIGNED TO BE USED ON WOOD MILLWORK, PLYWOOD, OUTDOOR FURNITURE AND SIDING FOR ABOVE GROUND APPLICATIONS. DO NOT USE FOR BELOW OR GROUND CONTACT APPLICATIONS REQUIRING PRESERVATIVE QUALITIES. WEAR PROTECTIVE CLOTHING AND RUBBER GLOVES WHEN HANDLING FRESHLY TREATED WOODEN PARTS OR STRUCTURES. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING. REMOVE CONTAMINATED CLOTHING BEFORE REUSE.

STORAGE AND DISPOSAL: DO NOT CONTAMINATE WATER, FOOD, OR FEED BY STORAGE OR DISPOSAL.

STORAGE: DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.

WOOD PRESERVATIVE DISPOSAL: PILT "70" WOOD PRESERVATIVE FLOWCOAT OR DIPPING MATERIAL OR MINERAL SPIRITS CLEAN-UP SOLVENT THAT CANNOT BE USED ACCORDING TO LABEL INSTRUCTIONS MUST BE DISPOSED OF ACCORDING TO APPLICABLE FEDERAL, STATE, OR LOCAL PROCEDURES.

CONTAINER DISPOSAL: TRIPLE RINSE (OR EQUIVALENT). THEN OFFER FOR RECYCLING OR RECONDITIONING OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER PROCEDURES APPROVED BY STATE AND LOCAL AUTHORITIES.

EPA REG. No. 748-

EPA EST. No. 748-