

U.S. ENVIRONMENTAL PROTECTION AGENCY
OFFICE OF PESTICIDES PROGRAMS
REGISTRATION DIVISION (WH-567)
WASHINGTON, D.C. 20460

EPA REGISTRATION NO.
748-249

DATE OF ISSUANCE
MAR 20 1985

NOTICE OF PESTICIDE: REGISTRATION
 REREGISTRATION
(Under the Federal Insecticide, Fungicide,
and Rodenticide Act, as amended)

TERM OF ISSUANCE

NAME OF PESTICIDE PRODUCT

Rez Stain and Wood Preservative-
Solid Color Oil

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

PIG Industries, Inc.
151 Colfax St.
P.O. Box 127
Springdale, PA 15144

160 125215
18 L

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data.
2. Make the labeling changes listed below before you release the product for shipment:
 - a. Add the phrase "EPA Registration No. 748-249."
 - b. Delete "or wetlands."
3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Henry M. Jacoby
Product Manager (21)
Fungicide-Herbicide Branch
Registration Division (WH-567)

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL

Henry M. Jacoby

DATE

3/20/85

748-200

77-610

Water Repellant

Front Panel

Logo

Exterior

REZ® Stain & Wood Preservative

Solid Color - Oil

White Mixing Base 77-610

EPA Reg. No.

EPA Est. No.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

MAR 19 1985

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.

748-249

Exceeds Federal Specifications TT-W-572B Paragraph 3.7 for
Water Repellancy

Active Ingredients:

Bis(tributyltin)oxide (TBTO)	0.50%
Folpet [n-([trichloromethyl]thio) phthalimide]	0.50%
Inert Ingredients	99.00%
Total	<u>100.00%</u>

KEEP OUT OF REACH OF CHILDREN

WARNING!

See Back Panel For Additional Precautions

Net 125 fl oz (3 qt 1 pt 13 oz)/3.69 L

Back Panel

PRECAUTIONARY STATEMENT - HAZARDS TO HUMANS AND DOMESTIC ANIMALS.

WARNING!

CONTAINS PETROLEUM DISTILLATE AND Bis(tributyltin)oxide and
Folpet [n-([trichloromethyl]thio)phthalimide]

Harmful if swallowed; may be absorbed through skin. Causes
skin irritation. Avoid breathing vapor or spray mist. Do not get
in eyes, on skin, or on clothing.

FIRST AID STATEMENT: If swallowed, do not induce vomiting; Call
a physician immediately. In case of contact, immediately flush
eyes or skin with plenty of water. Get medical attention if
irritation persists.

Note: Wear goggles, rubber gloves, and protective clothing when
applying or handling treated lumber.

ENVIRONMENTAL HAZARDS: Do not apply directly to water or wetlands. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL/CHEMICAL HAZARDS: Combustible. Keep away from heat, sparks or flame. Use with forced ventilation. Do not take internally. Close container after each use.

STORAGE AND DISPOSAL: Securely wrap original container in several layers of newspaper and discard in trash. Do not reuse container. Rinse thoroughly before discarding in trash.

For Emergency Medical or Spill Control Information, (304) 843-1300.

Important: Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. Spraying of any material can be hazardous. Wear respirator, eye protection, and protective clothing.

REZ® Stain -- Solid Color - Oil

This solid color stain helps to preserve wood and repels water. It exceeds the Federal Specification for water repellency, TT-W-572-B Paragraph 3.7.

REZ® stain enhances the natural beauty of wood and resists cracking, peeling, and the fading caused by the effects of the sun's harmful rays. It will also guard against wood rot and mildew growth on the stain film.

Where to Use: Decks, porches, sawn siding, beams, shakes, fencing, shingles, wood trim and previously stained wood surfaces. Do not use below ground, or on abraded plywood.

Directions For Use:

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

Coverage: Approx. 300 to 600 sq.ft. (27.8 to 55.7 sq.m) per gallon (3.78 L) depending on wood texture.

Surface Preparation: Surface must be dry and free from dirt, saw dust, loose fibers, mildew, flaking or peeling paint or stain, grease, and other surface contamination. Countersink and spot prime all ferrous nails and fill voids with putty. Sand surface smooth, always with the grain. For woods prone to bleeding, such as redwood or red cedar, white or light colored stains are not recommended.

Application: Stir thoroughly. Apply a full even coat by brush, pad, spray or roller. Apply thoroughly to ends, cuts and edges.

4

Avoid applying in direct sun light or when surface temperature is below 60° F. (10° C). No thinning is usually required. If necessary, thin up to 25% with a 50/50 mixture of paint thinner and linseed oil. If applied by spray, stains must be back rolled or brushed to provide maximum substrate wetting and penetration to prevent premature failure. Stain effects may vary slightly in color on different species of wood. Test in a remote area before proceeding.

Drying: Normally dries in 2 to 4 hours at 77° F (25° C) and 50% Relative Humidity. May be recoated in 24 hours.

Clean-Up: Paint Thinner

Side Panel

Label Date Code: 20484

PPG Industries, Inc.
Coatings and Resins
Pittsburgh, PA 15272
(412) 434-3131

Tint with Section 5 Color Formulas

YOUR SATISFACTION IS GUARANTEED

PPG guarantees your satisfaction with this product. If you're not satisfied, simply return the unused portion of the product to the store where you bought it, with proof of purchase and the dealer will refund your purchase price or furnish you with replacement product whichever you prefer.