

U.S. ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (WH-567) WASHINGTON, D.C. 20460	EPA REGISTRATION NO. 748-251	DATE OF ISSUANCE MAR 15 1985
	TERM OF ISSUANCE	
<b>NOTICE OF PESTICIDE:</b> <input checked="" type="checkbox"/> REGISTRATION <input type="checkbox"/> REREGISTRATION <i>(Under the Federal Insecticide, Fungicide,          and Rodenticide Act, as amended)</i>	NAME OF PESTICIDE PRODUCT ...	
	NAME AND ADDRESS OF REGISTRANT (Include ZIP code)	
<p> <input type="checkbox"/> ... Inc.          ... St.          ...          ...       </p> <p style="text-align: right;">100-128833 78</p>		
<p><b>NOTE:</b> Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.</p>		
<p>On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.</p> <p>A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.</p> <p>Registration is in no way to be construed as an endorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.</p> <p>This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:</p> <ol style="list-style-type: none"> <li>1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data.</li> <li>2. Make the labeling changes listed below and as you release the product for shipment:</li> </ol> <ol style="list-style-type: none"> <li>a. Add the phrase "EPA Registration No. 748-251."</li> <li>b. Delete "or wetlands."</li> </ol> <ol style="list-style-type: none"> <li>3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-78 Enclosure for a further description of final printed labeling.</li> </ol> <p>If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(a). Your release for shipment of this product constitutes acceptance of these conditions.</p> <p>Indicated by an "X" on the label, an enclosure to your product.</p>		
<p style="text-align: right;">Henry M. Jacoby          Product Manager (21)          Fungicide-Herbicide Branch          Registration Division (WH-567)</p>		
<input type="checkbox"/> ATTACHMENT IS APPLICABLE		
SIGNATURE OF APPROVING OFFICIAL <i>Henry M. Jacoby</i>		DATE ...

77-605

Water Repellant

Front Panel

Logo

Exterior

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

MAR 15 1985

Under the Federal Insecticide,  
Fungicide, and Herbicide Act  
as amended, for the pesticide  
registered under EPA Reg. No.

REZ® Stain & Wood Preservative

Other

Solid Color - Oil

Java Brown 77-605

748-251

EPA Reg. No.

EPA Est. No.

Exceeds Federal Specifications TT-W-572B Paragraph 3.7 for  
Water Repellancy

Active Ingredients:

Bis(tributyltin)oxide (TBTO) 0.50%

Inert Ingredients 99.50%

Total 100.00%

KEEP OUT OF REACH OF CHILDREN

WARNING!

See Back Panel For Additional Precautions:

Net 125 fl oz (3 qt 1 pt 13 oz)/3.69 L

Back Panel

PRECAUTIONARY STATEMENT - HAZARDS TO HUMANS AND DOMESTIC ANIMALS.

WARNING!

CONTAINS PETROLEUM DISTILLATE AND Bis(tributyltin)oxide.

Harmful or fatal if swallowed; may be absorbed through skin.  
Causes skin irritation. Avoid breathing vapor or spray mist. Do  
not get in eyes, on skin, or on clothing.

FIRST AID STATEMENT: If swallowed, do not induce vomiting. Call  
a physician immediately. In case of contact, immediately flush  
eyes or skin with plenty of water. Get medical attention if  
irritation persists.

Note: Wear goggles, rubber gloves, and protective clothing when  
applying or handling treated lumber.

ENVIRONMENTAL HAZARDS: Do not apply directly to water or wetlands. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL/CHEMICAL HAZARDS: Combustible. Keep away from heat, sparks or flame. Use with forced ventilation. Do not take internally. Close container after each use.

STORAGE AND DISPOSAL: Securely wrap original container in several layers of newspaper and discard in trash. Do not reuse container. Rinse thoroughly before discarding in trash.

For Emergency Medical or Spill Control Information, (304) 843-1300.

Important: Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. Spraying of any material can be hazardous. Wear respirator, eye protection, and protective clothing.

REZ® Stain -- Solid Color - Oil

This solid color stain helps to preserve wood and repels water. It exceeds the Federal Specification for water repellency, TT-W-572-B Paragraph 3.7.

REZ® stain enhances the natural beauty of wood and resists cracking, peeling, and the fading caused by the effects of the sun's harmful rays. It will also guard against wood rot and mildew growth on the stain film.

Where to Use: Decks, porches, sawn siding, beams, shakes, fencing, shingles, wood trim and previously stained wood surfaces. Do not use below ground, or on abraded plywood.

Directions For Use:

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

Coverage: Approx. 300 to 600 sq.ft. (27.8 to 55.7 sq.m ) per gallon (3.78 L) depending on wood texture.

Surface Preparation: Surface must be dry and free from dirt, saw dust, loose fibers, mildew, flaking or peeling paint or stain, grease, and other surface contamination. Countersink and spot prime all ferrous nails and fill voids with putty. Sand surface smooth, always with the grain. For woods prone to bleeding, such as redwood or red cedar, white or light colored stains are not recommended.

Application: Stir thoroughly. Apply a full even coat by brush, pad, spray or roller. Apply thoroughly to ends, cuts and edges.

Avoid applying in direct sun light or when surface temperature is below 60° F. (10° C). No thinning is usually required. If necessary, thin up to 25% with a 50/50 mixture of paint thinner and linseed oil. If applied by spray, stains must be back rolled or brushed to provide maximum substrate wetting and penetration to prevent premature failure. Stain effects may vary slightly in color on different species of wood. Test in a remote area before proceeding.

Drying: Normally dries in 2 to 4 hours at 77° F (25° C) and 50% Relative Humidity. May be recoated in 24 hours.

Clean-Up: Paint Thinner

Side Panel

Label Date Code: 20484

PPG Industries, Inc.  
Coatings and Resins  
Pittsburgh, PA 15272  
(412) 434-3131

**YOUR SATISFACTION IS GUARANTEED**

PPG guarantees your satisfaction with this product. If you're not satisfied, simply return the unused portion of the product to the store where you bought it, with proof of purchase and the dealer will refund your purchase price or furnish you with replacement product whichever you prefer.