

PILT® 77 READY TO USE

WOOD PRESERVATIVE - FOR INDUSTRIAL USE ONLY
PRESERVES AND PROTECTS WOOD FROM ROT AND MILDEW

Active Ingredient:

3-iodo-2-propynyl butylcarbamate 0.50%
Other Ingredients: 99.50%
Total 100.00%

EPA REG. NO. 748-277
EPA EST. NO. 748-WI-1

Contains Petroleum Distillates

KEEP OUT OF REACH OF CHILDREN

WARNING

See back label for additional precautionary statements.

FIRST AID	
If on Skin Or Clothing	<ul style="list-style-type: none">* Take off contaminated clothing.* Rinse skin immediately with plenty of water for 15-20 minutes.* Call a Poison Control Center or doctor for treatment advice.
If In Eyes	<ul style="list-style-type: none">* Hold eye open and rinse slowly and gently with water for 15-20 minutes.* Remove contact lenses, if present, after the first 5 minutes; then continue rinsing eye.* Call a Poison Control Center or doctor for treatment advice.
If Swallowed	<ul style="list-style-type: none">* Call a Poison Control Center or doctor for treatment advice.* Have person sip a glass of water if able to swallow.* Do not induce vomiting unless told by a Poison Control Center or doctor.
If Inhaled	<ul style="list-style-type: none">* Move person to fresh air.* If person is not breathing, call 911 or an ambulance, then give artificial respiration preferable mouth-to-mouth if possible.* Call a Poison Control Center or doctor for treatment advice.
Contact 1-304-843-1300 or your Poison Control Center for 24-hour emergency medical treatment information. Have the product container or label with you when calling a poison control center or doctor, or going for treatment.	

Manufactured by:
PPG Industries, Inc.
One PPG Place
Pittsburgh, PA 15272

ACCEPTED

FEB 20 2002

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended for 1974, this pesticide, registered under EPA Reg. No. 748-277

NET CONTENTS: _____ GALLONS
_____ LBS./GALLON

10/2001

748-277

2/20/2002

1/2

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes skin irritation. Harmful if absorbed through skin. Causes moderate eye irritation. Do not get on skin or on clothing. Avoid contact with eyes. Prolonged or frequently repeated skin contact may cause allergic reaction in some individuals. Remove contaminated clothing and wash clothing before reuse.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Applicators and other handlers (including handlers of freshly treated lumber) must wear:

- ✓ Coveralls over short-sleeved shirt and short pants
- ✓ Socks and chemical-resistant footwear
- ✓ Chemical resistant gloves (such as barrier laminate, neoprene rubber, nitrile rubber, or viton)
- ✓ Protective eyewear (goggles, face shield, or safety glasses)

USER SAFETY REQUIREMENTS

Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product. Do not reuse them. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions exist for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

USER SAFETY RECOMMENDATIONS

Users should: Wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Remove personal protective equipment immediately after handling this product. Wash the outside of gloves before removing. As soon as possible wash thoroughly.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply directly to water. Do not contaminate water when disposing of equipment washwaters. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your state Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS

Flammable. Keep away from heat and open flame.

DIRECTIONS FOR USE: PILT®77 READY TO USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Do not apply this product in a way that will contact workers or other persons.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage and disposal.

PESTICIDE STORAGE: Do not store near heat sources or open flame.

PESTICIDE DISPOSAL: Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by state and local authorities.

GENERAL INFORMATION

PILT®-77 READY TO USE protects against decay producing fungi, staining fungi and surface mold.

PRODUCT USES: This product is recommended for millwork, shingles (not asbestos), shakes, clapboards, smooth or rough-cut siding, plywood, decks, porches, railings, structural support timbers, flatbeds, coldframes and greenhouses.

GENERAL PRECAUTIONS AND RESTRICTIONS

- ✓ For Industrial Use Only
- ✓ Must be applied to unpainted, clean dry wood.
- ✓ Do not use for below or ground contact applications requiring preservative qualities.
- ✓ Do not use on wood that will be used in contact with food, feed or potable water or where prolonged skin contact will occur.
- ✓ Due to the presence of petroleum distillates in this product, do not use on lumber that can be used where dairy cattle or livestock can come in contact with the treated wood.

APPLICATION INSTRUCTIONS

PILT®-77 READY TO USE is ready to use as is. Immerse individual wooden parts by either flowcoating or dipping. Allow the wooden parts to dwell in the flowcoater or dip tank in contact with **PILT®-77 READY TO USE** a minimum of 15 seconds. Bundles of parts should be immersed for 3 minutes. Remove from solution and, prior to painting, allow the wood to dry at 65°-75°F in an area with engineered ventilation. Use hydrocarbon solvent for clean-up solvent.

2/2