Page 1716

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

June 13, 2003

Ms. Cristina Griffin Delta Analytical Corp. 7910 Woodmont Avenue Suite 1000 Bethesda, MD 20814

Subject:

PPG Industries. Inc.

PPG Calcium Hypochlorite Tablets

EPA Registration No. 748-295

Applications Dated: September 26, 2002 and May 21, 2003

Receipt Date: September 30, 2002 and May 21, 2003

Dear Ms. Griffin:

The Agency required that PPG Industries, Inc. provide a compelling rationale to add drip irrigation to their calcium hypochlorite label.

The following amendment, submitted in connection with registration under section 3(c)(7)(A) of the Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA), as amended, is acceptable.

Rationale

- Calcium hypochlorite is exempted from the requirement of a tolerance under 40 CFR §180.1054 when used on pre-harvest or post harvest in solution on all raw agricultural commodities.
- Post harvest uses for calcium hypochlorite on potatoes is allowed at a 500 ppm level. The proposed label declares a level of 1 to 2 ppm free residual chlorine for continuous feed in drip irrigation lines.
- The 1 to 2 ppm level for drip irrigation is less that the level EPA has approved for direct ingestion in potable water.

CONCURRENCES									
SYMBOL							.,,.,,.,		
SURNAME	I .							1	
DATE	J					!			

General Comments

The Agency has decided that it is not necessary to stamp the supplemental information provided, since it appears on the actual label.

A stamped copy of the labeling accepted with conditions is enclosed. Submit one copy of your final printed labeling before distributing or selling the product bearing the revised labeling.

Should you have any questions or comments concerning this letter, please contact Wanda Mitchell at (703) 308-6345.

Sincerely,

Robert S. Brennis

Product Manager - Team 32

Regulatory Management Branch II Antimicrobials Division (7510C)

PPG CALCIUM HYPOCHLORITE TABLETS

Dry Chlorinating Tablets for Industrial and Potable Water Treatment Applications

This product provides a steady source of available chlorine. It Kills Bacteria, Controls Algae, and Destroys Organic Contaminants in pools and other water systems.

EPA Reg. No. 748-295 EPA Est. No. 58401-IL-1

Minimum 65% Available Chlorine

KEEP OUT OF REACH OF CHILDREN DANGER

See additional precautionary statements on back label.

FIRST AID: Contact 1-304-843-1300 or your poison control center for 24-hour emergency medical treatment information. Have the product container or label with you when calling a poison control center or doctor, or going for treatment. If on skin or clothing, take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. If in eyes, hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice. If inhaled, move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice. If swallowed, call poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person.

Manufactured by PPG INDUSTRIES, INC. One PPG Place Pittsburgh, PA 15272

Emergency Telephone Number: 1-304-843-1300

NET WT. 100 lbs. (45 kg)

5/20/03 g:\abe\ppg\calciumhypo\748295-052003|abe|.doc ACCEPTED
with COMMENTS
FERA Letter Dated:

JUN 13 2003

PRECAUTIONARY STATEMENTS -

HAZARDS TO HUMANS AND DOMESTIC ANIMALS -

DANGER - Highly Corrosive. Causes irreversible eye damage and skin damage. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Remove and wash contaminated clothing and shoes before reuse. May be Fatal if swallowed. Irritating to Nose and Throat. Avoid breathing dust.

[The following PPE information is required to be on the product label only when the agricultural use instructions (pages 11-13 of this master label) are on the label]

Personal Protective Equipment (PPE)

Applicators and other handlers must wear:

- A. Goggles or face shield
- B. Long-sleeved shirt and long pants
- C. Waterproof gloves
- Shoes plus socks D.

Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS: Strong oxidizing agent! Mix only with water. Never add water to product. Always add product to large quantities of water. Use only a clean, dry utensil made of metal or plastic each time product is taken from the container. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause violent reaction leading to fire or explosion. Contamination with moisture, acids, organic matter, other chemicals or easily combustible materials such as petroleum or paint products may start a chemical reaction with generation of heat, liberation of hazardous gases and possible generation of a fire or explosion. In case of contamination or decomposition, do not reseal container. If possible isolate container in open air or well-ventilated area. Flood with large volumes of water, if necessary.

STORAGE AND DISPOSAL: Read before using. Keep in original container in a cool, dry, wellventilated place. Keep container closed when not in use. Keep away from heat sources, sparks, open flames and lighted tobacco products. Use only a clean, dry utensil made of metal or plastic each time product is taken from the container. Container Disposal - Do not reuse container. Residual material remaining in empty container can react to cause fire. Thoroughly flush empty container with water then destroy by placing in trash collection. Pesticide Disposal - Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility. Do not contaminate water, food, or feed by storage or disposal. In Case of Fire - Drench with water. Calcium hypochlorite supplies oxygen; therefore, attempts to smother fire with a wet blanket, carbon dioxide, or a dry chemical extinguisher are ineffective. In Case of Spill or Leak -Use extreme caution. Contamination may cause fire or violent reaction. If fire or reaction occurs in area of spill, douse with plenty of water. Otherwise sweep up spilled material, using a clean, dry shovel and broom and dissolve spilled material in water. Then immediately use solution as directed.

2

with COMMENTS F EPA Letter Dated:

JUN 13 2003

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

DISINFECTION OF DRINKING WATER (Potable Water):

PUBLIC SYSTEMS

Mix a ratio of 1 ounce of this product to 6000 gallons of water. Begin feeding this solution with a hypochlorinator until a free available chlorine residual of at least 0.2 ppm and no more than 0.6 ppm is attained throughout the distribution system. Check water frequently with a chlorine test kit. Bacteriological sampling must be conducted at a frequency no less than that prescribed by the National Interim Primary Drinking Water Regulations. Contact your local Health Department for further details.

INDIVIDUAL SYSTEMS

Dug Wells - Upon completion of the casing (lining) wash the interior of the casing (lining) with a 100 ppm available chlorine solution using a stiff brush. This solution can be made by thoroughly mixing 1 ounce of this product into 40 gallons of water. After covering the well, pour the sanitizing solution into the well through both the pipe sleeve opening and the pipeline. Wash the exterior of the pump cylinder also with the sanitizing solution. Start pump and pump water until strong odor of chlorine in water is noted. Stop pump and wait at least 24 hours. After 24 hours flush well until all traces of chlorine have been removed from the water. Contact your local Health Department for further details.

INDIVIDUAL WATER SYSTEMS

Drilled, Driven & Bored Wells - Run pump until water is as free from turbidity as possible. Pour a 100 ppm available chlorine sanitizing solution into the well. This solution can be made by thoroughly mixing 1 ounce of this product into 40 gallons of water. Add 5 to 10 gallons of clean, chlorinated water to the well in order to force the sanitizer into the rock formation. Wash the exterior of pump cylinder with the sanitizer. Drop pipeline into well, start pump and pump water until strong odor of chlorine in water is noted. Stop pump and wait at least 24 hours. After 24 hours flush well until all traces of chlorine have been removed from the water. Deep wells with high water levels may necessitate the use of special methods for introduction of the sanitizer into the well. Consult your local Health Department for further details.

Flowing Artesian Wells - Artesian wells generally do not require disinfection. If analyses indicate persistent contamination, the well should be disinfected. Consult your local Health Department for further details.

> ACCEPTED with COMMENTS FEPA Letter Dated:

JUN 1 3 2003

Under the Federal Insecticide, Fungicide, and Rodenticide Act as registered under EPA Reg. No.

EMERGENCY DISINFECTION

- When boiling of water for 1 minute is not practical, water can be made potable by using this product. Prior to addition of the sanitizer, remove all suspended material by filtration or by allowing it to settle to the bottom. Decant the clarified, contaminated water to a clean container and add 1 grain of this product to 1 gallon of water. One grain is approximately the size of the letter "O" in this sentence. Allow the treated water to stand for 30 minutes. Properly treated water should have a slight chlorine odor, if not, repeat dosage and allow the water to stand an additional 15 minutes. The treated water can then be made palatable by pouring it between clean containers for several times.

OTHER CALCIUM HYPOCHLORITE USES

Calcium Hypochlorite is also used in the sanitization of water systems, municipal water mains, sewage and industrial waste treatment, pulp bleaching, sanitization in the food industry, restaurants, dairies, and hospitals, odor and taste control in potable water systems, algae control in industrial cooling water systems, and general industrial sanitization. For specific literature on these and other accepted uses, write to: PPG Industries, Inc., One PPG Place, Pittsburgh, Pennsylvania 15272.

SANITIZATION OF NONPOROUS FOOD CONTACT SURFACES

RINSE METHOD - A solution of 100 ppm available chlorine may be used in the sanitizing solution if a chlorine test kit is available. Solutions containing an initial concentration of 100 ppm available chlorine must be tested and adjusted periodically to insure that the available chlorine does not drop below 50 ppm. Prepare a 100 ppm sanitizing solution by thoroughly mixing 1 ounce of this product with 40 gallons of water. If no test kit is available, prepare a sanitizing solution by thoroughly mixing 1 ounce of this product with 20 gallons of water to provide approximately 200 ppm available chlorine by weight. Clean equipment surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for at least 2 minutes. If solution contains less than 50 ppm available chlorine, as determined by a suitable test kit, either discard the solution or add sufficient product to reestablish a 200 ppm residual. Do not rinse equipment with water after treatment and do not soak equipment overnight. Sanitizers used in automated systems may be used for general cleaning but may not be reused for sanitizing purposes.

IMMERSION METHOD - A solution of 100 ppm available chlorine may be used in the sanitizing solution if a chlorine test kit is available. Solutions containing an initial concentration of 100 ppm available chlorine must be tested and adjusted periodically to insure that the available chlorine does not drop below 50 ppm. Prepare a 100 ppm sanitizing solution by thoroughly mixing 1 ounce of this product with 40 gallons of water. If no test kit is available, prepare a sanitizing solution by thoroughly mixing 1 ounce of this product with 20 gallons of water to provide approximately 200 ppm available chlorine by weight. Clean equipment in the normal manner. Prior to use, immerse equipment in the sanitizing solution for at least 2 minutes and allow the sanitizer to drain. If solution contains less than 50 ppm available chlorine, as determined by a suitable test kit, either discard the solution or add sufficient product to reestablish a 200 ppm residual. do not rinse equipment with water after treatment. Sanitizers used in automated systems may be used for general cleaning but may not be reused for sanitizing purposes.

FLOW/PRESSURE METHOD - Disassemble equipment and thoroughly clean after use. Assemble equipment in operating position prior to use. Prepare a volume of a 200 ppm available chlorine sanitizing solution. For a continuous c

with COMMENTS

r EPA Letter Dated:

JUN 1 3 2003

4

product in a ratio of 1 ounce product with 20 gallons of water. Pump solution through the system until full flow is obtained at all extremities, the system is completely filled with the sanitizer and all air is removed from the system. Close drain valves and hold under pressure for at least 2 minutes to insure contact with all internal surfaces. Remove some cleaning solution from drain valve and test with a chlorine test kit. Repeat entire cleaning/sanitizing process if effluent contains less than 50 ppm available chlorine.

CLEAN-IN-PLACE METHOD - Thoroughly clean equipment after use. Prepare a volume of 200 ppm available chlorine sanitizing solution equal to 110% of volume capacity of the equipment by mixing the product in a ratio of 1 ounce product with 20 gallons of water. Pump solution through the system until full flow is obtained at all extremities, the system is completely filled with the sanitizer and all air is removed from the system. Close drain valves and hold under pressure for at least 10 minutes to insure contact with all internal surfaces. Remove some cleaning solution from drain valve and test with a chlorine test kit. Repeat entire cleaning/sanitizing process if effluent contains less than 50 ppm available chlorine.

SPRAY/FOG METHOD - Preclean all surfaces after use. Use a 200 ppm available chlorine solution to control bacteria, mold or fungi and a 600 ppm solution to control bacteriophage. Prepare a 200 ppm sanitizing solution of sufficient size by thoroughly mixing the product in a ratio of 1 ounce product with 20 gallons of water. Prepare a 600 ppm solution by thoroughly mixing the product in a ratio of 3 ounces product with 20 gallons of water. Use spray or fogging equipment which can resist hypochlorite solutions. Always empty and rinse spray/fog equipment with potable water after use. Thoroughly spray or fog all surfaces until wet, allowing excess sanitizer to drain. Vacate area for at least 2 hours. Prior to using equipment, rinse all surfaces treated with a 600 ppm solution with a 200 ppm solution.

SANITIZATION OF POROUS FOOD CONTACT SURFACES

RINSE METHOD - Prepare a 600 ppm solution by thoroughly mixing 3 ounces of this product with 20 gallons of water. Clean surfaces in the normal manner. Rinse all surfaces thoroughly with the 600 ppm solution, maintaining contact for at least 2 minutes. Prepare a 200 ppm sanitizing solution by thoroughly mixing 1 ounce of this product with 20 gallons of water. Prior to using equipment, rinse all surfaces with a 200 ppm available chlorine solution. Do not rinse and do not soak equipment overnight.

IMMERSION METHOD - Prepare a 600 ppm solution by thoroughly mixing, in an immersion tank, 3 ounces of this product with 20 gallons of water. Clean equipment in the normal manner. Prepare a 200 ppm sanitizing solution by thoroughly mixing 2 ounces of this product with 10 gallons of water. Prior to using, immerse equipment in the 200 ppm sanitizing solution for at least 2 minutes and allow the sanitizer to drain. Do not rinse and do not soak equipment overnight.

SPRAY/FOG METHOD - Preclean all surfaces after use. Prepare a 600 ppm available chlorine sanitizing solution of sufficient size by thoroughly mixing the product in a ratio of 3 ounces product with 20 gallons of water. Use spray or fogging equipment which can resist hypochlorite solutions. Always empty and rinse spray/fog equipment with potable water after use. Thoroughly spray or fog all surfaces until wet, allowing excess sanitizer to drain. Vacate area for at least 2 hours. Prior to using equipment, rinse all surfaces with a 200 ppm available chlorine solution. Prepare a 200 ppm sanitizing solution by thoroughly mixing 1 ounce of this product with 20 gallons of water.

SANITIZATION OF NONPOROUS NON-FOOD CONTACT SURFACES

ACCEPTED WITH COMMENTS EPA Letter Dated:

JUN 13 2003

RINSE METHOD - Prepare a sanitizing solution by thoroughly mixing 1 ounce of this product with 20 gallons of water to provide approximately 200 ppm available chlorine by weight. Clean equipment surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for at least 2 minutes. Do not rinse equipment with water after treatment and do not soak equipment overnight.

IMMERSION METHOD - Prepare a sanitizing solution by thoroughly mixing, in an immersion tank, 1 ounce of this product with 20 gallons of water to provide approximately 200 ppm available chlorine by weight. Clean equipment in the normal manner. Prior to use, immerse equipment in the sanitizing solution for at least 2 minutes and allow the sanitizer to drain. Do not rinse equipment with water after treatment.

ACCEPTED with COMMENTS FEPA Letter Dated:

JUN 1 3 2003

SPRAY/FOG METHOD - Preclean all surfaces after use. Prepare a 200 ppm available chlorine sanitizing solution of sufficient size by thoroughly mixing the product in a ratio of 1 ounce product with 20 gallons of water. Use spray or fogging equipment which can resist hypochlorite solutions. Prior to using equipment, thoroughly spray or fog all surfaces until wet, allowing excess sanitizer to drain. Vacate area for at least 2 hours.

DISINFECTION OF NONPOROUS NON-FOOD CONTACT SURFACES

RINSE METHOD - Prepare a disinfecting solution by thoroughly mixing 3 ounces of this product with 20 gallons of water to provide approximately 600 ppm available chlorine by weight. Clean equipment surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the disinfecting solution, maintaining contact with the solution for at least 10 minutes. Do not rinse equipment with water after treatment and do not soak equipment overnight.

IMMERSION METHOD - Prepare a disinfecting solution by thoroughly mixing, in an immersion tank, 3 ounces of this product with 20 gallons of water to provide approximately 600 ppm available chlorine by weight. Clean equipment in the normal manner. Prior to use, immerse equipment in the disinfecting solution for at least 10 minutes and allow the solution to drain. Do not rinse equipment with water after treatment.

SANITIZATION OF POROUS NON-FOOD CONTACT SURFACES

RINSE METHOD - Prepare a sanitizing solution by thoroughly mixing 3 ounces of this product with 20 gallons of water to provide approximately 600 ppm available chlorine by weight. Clean equipment surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for at least 2 minutes. Do not rinse equipment with water after treatment and do not soak equipment overnight.

IMMERSION METHOD - Prepare a sanitizing solution by thoroughly mixing, in an immersion tank. 3 ounces of this product with 20 gallons of water to provide approximately 600 ppm available chlorine by weight. Clean equipment in the normal manner. Prior to use, immerse equipment in the sanitizing solution for at least 2 minutes and allow the sanitizer to drain. Do not rinse equipment with water after treatment.

SPRAY/FOG METHOD - After cleaning, sanitize non-food contact surfaces with 600 ppm available chlorine by thoroughly mixing the product in a ratio of 3 ounces of this product with 20 gallons of water. Use spray or fogging equipment which can resist hypochlorite solutions. Always empty and rinse spray/fog equipment with potable water after use. Prior to using equipment, thoroughly spray or fog all surfaces until wet, allowing excess sanitizer to drain. Vacate area for at least 2 hours.

ACCEPTED
with COMMENTS
FEPA Letter Dated:
JUN 1 3 2003

Table of Recommended Levels and Use Dilutions for Available Chiorine

	Usage Dilution			
	* * *	n Available		
Commodity	250 gallons of water Chlorine			
Apple	7.7 - 10.3	150 - 200		
Artichoke	5.1 - 7.7	100 - 150		
Asparagus	6.4 - 7.7	125 - 150		
Brussels Sprouts	5.1 - 7.7	100 - 150		
Carrots	5.1 - 10.3	100 - 200		
Cauliflower	15.4 - 20.5	300 - 400		
Celery	5.1 - 5.7	100 - 110		
Cherry	3.9 - 5.1	75.0 - 100		
Chopped Cabbage ¹	4.1 - 5.1	80.0 - 100		
Chopped Lettuce ¹	4.1 - 5.1	80.0 - 100		
Citrus Fruits	1.3 - 10.3	25.0 - 200		
Cucumbers	15.4 - 18.0	300 - 350		
Green Onions	3.9 - 6.2	75.0 - 120		
Melons ²	5.1 - 7.7	100 - 150		
Peaches, Nectarines and Plums	2.6 - 5.1	50.0 - 100		
Pears (without buffer)	10.3 - 15.4	200 - 300		
Peppers ^{3, 4}	15.4 - 20.5	300 - 400		
Potatoes ^{3, 4}	3.3 - 6.4	65.0 - 125		
Radishes	5.1 - 7.7	100 - 150		
Stonefruit (Hydrocooler)	1.5 - 3.9	30.0 - 75.0		
Tomatoes ⁴	15.4 - 18.0	300 - 350		

Note:

- 1. After treatment the adhering water must be removed by a centrifugation process.
- 2. For hydrocooling melons use 10 ppm.
- 3. Concentration given for use in a flow through washer system only.
- 4. For treating peppers in a dump tank use 100 135 ppm available chlorine. For treating potatoes in a pit system use 100 - 150 ppm available chlorine. For treating tomatoes in a dump tank system use 70 - 120 ppm available chlorine.

ACCEPTED
with COMMENTS
FEPA Letter Dated:
JUN 1 3 2003

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No.

748-295

8

FOOD PROCESSING

Authorized by USDA for use in federally inspected meat and poultry plants.

Chlorine potable water treatment compounds.

Chlorine may be present in processing water of meat and poultry plants at concentrations up to 5 parts per million calculated as available chlorine. Also, chlorine may be present in poultry chiller intake water, and in carcass wash water at concentrations up to 50 parts per million calculated as available chlorine. Chlorine must be dispensed at a constant and uniform level and the method or system must be such that a controlled rate is maintained.

Cooling and retort water treatment compounds.

Chemical agents may be added to water used to cook and cool containers of meat and poultry products to prevent staining of containers and to control corrosion and deposit formation on surfaces of processing equipment. The amount used should be the minimum sufficient for the purpose.

Calcium hypochlorite solutions providing 1% available chlorine should be fed into tanks or channels by an elevated tank to provide a concentration of 2 ppm available chlorine. The flow may be controlled with a noncorroding valve or a pinch-stop on a rubber hose.

Feed points should be located to provide uniform distribution of solution throughout the entire system. Long and narrow tanks may require the solution to be fed at two points to insure proper distribution.

Test the water for available chlorine. If a residual of 2 ppm is present throughout the system, the water is properly sanitized.

Test for available chlorine every hour until dosage requirements are established. Thereafter, check every 2 or 3 hours to ascertain that an available chlorine residual of 2 ppm is maintained throughout the system.

Compounds for treating boilers, steam lines, and/or cooling systems where neither the treated water nor the steam produced may contact edible products. This does not include compounds added to water used to cook and cool containers of meat and poultry products.

A clogged or fouled system should be mechanically cleaned to remove all physical soil prior to beginning treatment. Initially, treat by adding enough calcium hypochlorite to provide 10 ppm available chlorine (2 ounces per 1000 gallons) as a shock dosage and circulate it thoroughly through the system.

Then, for continuous preventative control of algae and slime growth, regularly add enough calcium hypochlorite to the recirculation system to maintain a 1.0 ppm free chlorine residual.

Other water condition factors, such as pH, should be controlled as recommended by the ACCEPIPE nt manufacturer.

with COMMENTS
- EPA Letter Dated:

JUN 1 3 2003

9

Shell Egg Cleaning

Wash eggs promptly after gathering. Water with an iron content in excess of 2 ppm shall not be used unless equipment capable of removing the excess iron is installed on the water system. Wash water temperature should be 90°F or higher. Maintain the wash water at a temperature which is at least 20°F warmer than the temperature of the eggs to be washed. Spray rinse washed eggs with warm potable water containing an approved sanitizing compound. Eggs should be reasonably dry before casing or breaking.



Shell Egg Destainers

The destainer solution must be at least 20°F warmer than the eggs with a minimum solution temperature of 90°F. Total elapsed time in the destainer solution may not exceed 5 minutes. Eggs are to be rewashed and spray rinsed after destaining. Destainer solution should be replaced daily or whenever it becomes dirty. Destaining is to be done after initial washing has been completed. It is recommended that all eggs be shell protected after they have been destained.

LAUNDRY SANITIZERS

Household Laundry Sanitizers - In Soaking Suds - thoroughly mix 1 tbsp. of this product to 10 gallons of wash water to provide 200 ppm available chlorine. Wait 5 minutes, then add soap or detergent. Immerse laundry for at least 11 minutes prior to starting the wash/rinse cycle. - In Washing Suds - thoroughly mix 1 tbsp. of this product to 10 gallons of wash water containing clothes to provide 200 ppm available chlorine. Wait 5 minutes then add soap or detergent and start the wash/rinse cycle.

Commercial Laundry Sanitizers - Wet fabrics or clothes should be spun dry prior to sanitization. Thoroughly mix 1 oz. of this product with 20 gallons of water to yield 200 ppm available chlorine. Promptly after mixing the sanitizer, add the solution into the prewash prior to washing fabrics/clothes in the regular wash cycle with a good detergent. Test the level of available chlorine, if solution has been allowed to stand. Add more of this product if the available chlorine level has dropped below 200 ppm.

ACCEPTED with COMMENTS EPA Letter Dated:
JUN 1 3 2003

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

AGRICULTURAL USE REQUIREMENTS

Use this product only in accordance with its labeling and with the Worker Protection Standard, 40 CFR part 170. This Standard contains requirement for the protection of agricultural workers on farms, forests, nurseries, greenhouses, and handlers of agricultural pesticides. It contains requirements for training, decontamination, notification, and emergency assistance. It also contains specific instructions and exceptions pertaining to the statements on this label about personal protective equipment (PPE), and restricted-entry interval. The requirements in this box only apply to uses of this product that are covered by the Workers Protection Standard.

The Restricted-Entry Interval (REI) is 0 days when using this product.

There are no posting or notification requirements when using this product.

Personal Protective Equipment should be worn as described under the "Precautionary Statements" section of this label.

DIRECTIONS FOR THE CONTROL OF BACTERIA, ALGAE, SLIME BUILD-UP AND CLOGGING IN SPECIFIED IRRIGATION SYSTEMS

PPG Calcium Hypochlorite Tablets are designed to be used in tablet chlorinator systems. The tablets provide a minimum of 65% available chlorine. The tablets are placed in the chlorinator and the bottom layer of tablets is eroded as water flows through the chlorinator. The inlet water flow controls the rate of chlorination; higher flows result in higher delivery of available chlorine. The Application Rates section provides the levels of free residual chlorine needed to prevent or address bio-fouling occurring in drip/trickle irrigation systems. Consult the instruction manual for the chlorinator system to determine how to achieve this level with the tablet chlorinator in use.

This product is to be applied through drip/trickle sprinkler irrigation systems only for agricultural crops only where this manner of use will not cause crop damage.

ACCEPTED
with COMMENTS
FEPA Letter Dated:

JUN 13 2003

APPLICATION RATES

If the irrigation water has high levels of nutrients causing bacterial, algal, or other bio-fouling that reduces system performance, continuous use of this product may be necessary. The recommended level of free residual chlorine for continuous feed is 1 to 2 ppm, measured at the end of the farthest lateral using a good quality test kit for free chlorine (also called "free residual" or "free available" chlorine).

Periodic shock treatments at a higher available chlorine rate of up to 20 ppm free residual may be appropriate where bacteria and/or algae clogging and build-up are not managed by maintaining a continuous residual. The frequency of the shock application depends upon the frequency and extent of bio-clogging.

Superchlorination, bringing concentrations to as much as 100 ppm total available chlorine, is recommended for reclaiming low-volume irrigation systems if clogged by algae and bacterial slimes. Set the chlorinator to deliver 100 ppm in the drip system and monitor the free chlorine residual at the end of the farthest lateral. As soon as it is established that the free residual reading is between 10 and 20 ppm, shut the system down and leave it undisturbed for up to 24 hours. Then flush all submains and laterals with fresh water. Superchlorination will not dissolve/remove scale or inorganic sediment fouling.

*Note: To correctly establish the dose setting required, it is necessary to measure the free chlorine concentration (ppm) at the end of the treated increment in the field and adjust the dose setting until the desired free chlorine concentration is obtained. This is because contaminants in the water may consume available chlorine resulting in a concentration that is less than the concentration desired as specified above. Only experience can establish the actual chlorinator settings required to provide the amount of free chlorine at the end of the farthest lateral (and consequent treatment of the irrigation system). Normally the treatment level at the end of the farthest lateral will be 1 – 2 ppm free chlorine.

GENERAL APPLICATION INSTRUCTIONS

Chlorination should be started during irrigation, near the end of the irrigation sequence, but early enough to establish the desired free chlorine concentration throughout the system being treated.

Apply this product upstream of the filter to help keep the filter clean.

Determine the level of free chlorine as described above, using a free chlorine test kit. Allow sufficient time to achieve a steady reading.

<u>DO NOT</u> apply this product when fertilizers, herbicides, and insecticides are being injected since they will consume the available chlorine and may produce toxic reaction products.

Shut down the product feed as soon as the irrigation water is switched to the next irrigation sector. Leave the treated water residing in the section that has been shut down.

Refer to the chlorinator use instructions as needed.

ACCEPTED
with COMMENTS
= EPA Letter Dated:
JUN 1 3 2003

SENSITIVE PLANT SPECIES

Certain plants, including various species of trees, flowers, shrubs, agronomic crops, fruits and vegetables are adversely affected by chlorinated irrigation. The use of this product can impact the growth, appearance and health of the plants.

Begonias, geraniums and other ornamental plant species are known to be sensitive to continuous chlorination at levels of 1-2 ppm free chlorine. Plant species such as tomato, lettuce, broccoli, and petunia are sensitive to periodic chlorination levels of 10-20 ppm free chlorine.

If uncertain of a plant's tolerance, consult an agronomist or a support agency or use an alternate method to remove bio-fouling from the irrigation system.

ACCEPTED
with COMMENTS
- EPA Letter Dated:

JUN 1 3 2003

USE INSTRUCTIONS FOR PPG Calcium Hypochlorite Tablets


- 1. Install the PPG chlorinator per the instruction manual.
- Load tablets into the PPG chlorinator.
- 3. Determine the water flow rate of your system in gpm.
- Determine the chlorine demand of your system.
 - When you know the ppm chlorine demand required, calculate the lbs/hr chlorine delivery by the following:


water flow (gpm) x ppm Chlorine Demand x 0.0005 = lbs/hr chlorine

- b. If you are currently using chlorine gas, calculate usage on a lbs/hr basis.
- c. If you are currently using sodium hypochlorite, calculate the usage as (at 10% strength): gallons/hr = lbs/hr chlorine
- 5. From the chart below, determine the flow rate of water necessary through the chlorinator. Multiple chlorinators may be used for higher delivery rates.
- 6. Determine that there is a chlorine residual (i.e., 0.5 ppm for drinking water) in the water stream that meets requirements.
- Operate the chlorinator per the instruction manual.

PPG 3" Calcium Hypochlorite Tablets Delivery

Graphs below are representative of average tested delivery values. Multiply the lbs/hr chlorine delivered by 1.5 to determine the lbs/hr of tablets used.





ACCEPTED
with COMMENTS
- EPA Letter Dated:

JUN 1 3 2003